

Moscow ML Library Documentation

Version 2.00 of June 2000

Sergei Romanenko, Russian Academy of Sciences, Moscow, Russia
Claudio Russo, Cambridge University, Cambridge, United Kingdom
Peter Sestoft, Royal Veterinary and Agricultural University, Copenhagen, Denmark

This document

This manual describes the Moscow ML library, which includes parts of the SML Basis Library and several extensions. The manual has been generated automatically from the commented signature files.

Alternative formats of this document

Hypertext on the World-Wide Web

The manual is available at <http://mosml.org/mosmlib/> for online browsing.

Hypertext in the Moscow ML distribution

The manual is available for offline browsing at `mosml/doc/mosmlib/index.html` in the distribution.

On-line help in the Moscow ML interactive system

The manual is available also in interactive `mosml` sessions. Type `help "lib"`; for an overview of built-in function libraries. Type `help "fromstring"`; for help on a particular identifier, such as `fromString`. This will produce a menu of all library structures which contain the identifier `fromstring` (disregarding the lowercase/uppercase distinction):

```
-----  
| 1 | val Bool.fromString |  
| 2 | val Char.fromString |  
| 3 | val Date.fromString |  
| 4 | val Int.fromString |  
| 5 | val Path.fromString |  
| 6 | val Real.fromString |  
| 7 | val String.fromString |  
| 8 | val Time.fromString |  
| 9 | val Word.fromString |  
| 10 | val Word8.fromString |  
-----
```

Choosing a number from this menu will invoke the help browser on the desired structure, e.g. `Int`.

The Moscow ML home page is <http://mosml.org>

Contents

AppleScript	2	PP	109
Array	3	Parsing	112
Array2	6	Path	114
ArraySlice	10	Polygdbm	118
Arraysort	13	Polyhash	120
BinIO	14	Postgres	122
Binarymap	17	Process	127
Binaryset	19	Random	128
Bool	21	Rbset	129
Buffer	22	Real	132
Byte	23	Redblackmap	135
Callback	24	Regex	137
Char	27	SML90	142
CharArray	30	Signal	143
CharArraySlice	31	Socket	145
CharVector	32	Splaymap	150
CharVectorSlice	33	Splayset	152
CommandLine	34	String	154
Date	35	StringCvt	157
Dynarray	38	Substring	159
Dynlib	39	Susp	163
FileSys	42	TextIO	164
Gdbm	45	Time	168
Gdimage	48	Timer	170
General	52	Unix	171
Hashset	57	Vector	173
Help	59	VectorSlice	175
Int	61	Weak	178
IntInf	64	Word	181
Intmap	65	Word8	184
Inset	67	Word8Array	187
Lexing	69	Word8ArraySlice	188
List	71	Word8Vector	189
ListPair	74	Word8VectorSlice	190
Listsort	76	Index	191
Location	77		
Math	79		
Meta	81		
Mosml	85		
Mosmlcgi	87		
Mosmlcookie	91		
Msp	92		
Mysql	99		
NJ93	104		
Nonstdio	106		
OS	107		
Option	108		

Module AppleScript

```
AppleScript -- Apple MacOS scripting

type OSAID
type OSAerr = int

exception AppleScriptErr of OSAerr * string

val as_compile    : string -> OSAID
val as_dispose   : OSAID -> unit
val as_run_script: OSAID -> string
val as_run_text   : string -> string
```

These Mac specific functions provide the capability to compile and run AppleScript programs.

The exception AppleScriptErr is raised in the event of an error.

[as_compile str] compiles AppleScript source code text, returning an abstract token of type OSAID. This token may be used to run the script. The token may be used repeatedly until it is returned with as_dispose or until mosml exits.

[as_dispose tok] disposes of the resources associated with the OSAID token so that they may be reused by the AppleScript system. AppleScriptErr is raised upon any attempt to reuse a disposed token.

[as_run_script tok] runs the script associated with the token. This typically involves AppleEvent communication with other programs running on the Mac, or networked Macs. The AppleScript result is returned as a string.

[as_run_text str] compiles and runs the AppleScript source code text, disposing all resources allocated in the process, and returns the AppleScript result as a string.

References:

Inside Macintosh: Interapplication Communication, Chapter 10
 AppleScript Language Guide English Edition,
 available at <http://applescript.apple.com/support.html>

Module Array

Array -- SML Basis Library

```
prim_EQtype 'a array
type 'a vector = 'a Vector.vector

val maxLen    : int
val array     : int * '_a -> '_a array
val tabulate  : int * (int -> '_a) -> '_a array
val fromList  : '_a list -> '_a array

val length   : 'a array -> int
val sub      : 'a array * int -> 'a
val update   : 'a array * int * 'a -> unit
val vector   : 'a array -> 'a vector

val copy     : {src: 'a array, dst: 'a array, di: int} -> unit
val copyVec  : {src: 'a vector, dst: 'a array, di: int} -> unit

val find     : ('a -> bool) -> 'a array -> 'a option
val exists   : ('a -> bool) -> 'a array -> bool
val all      : ('a -> bool) -> 'a array -> bool

val app      : ('a -> unit) -> 'a array -> unit
val foldl   : ('a * 'b -> 'b) -> 'b -> 'a array -> 'b
val foldr   : ('a * 'b -> 'b) -> 'b -> 'a array -> 'b
val modify  : ('a -> 'a) -> 'a array -> unit

val findi   : (int * 'a -> bool) -> 'a array -> (int * 'a) option
val appi    : (int * 'a -> unit) -> 'a array -> unit
val foldli  : (int * 'a * 'b -> 'b) -> 'b -> 'a array -> 'b
val foldri  : (int * 'a * 'b -> 'b) -> 'b -> 'a array -> 'b
val modifyi : (int * 'a -> 'a) -> 'a array -> unit

val collate : ('a * 'a -> order) -> 'a array * 'a array -> order
```

[*'ty array*] is the type of one-dimensional, mutable, zero-based constant-time-access arrays with elements of type '*ty*. Type '*'ty array* admits equality even if '*ty* does not. Arrays *a*₁ and *a*₂ are equal if both were created by the same call to a primitive (*array*, *tabulate*, *fromList*).

Functions working on a slices (contiguous subsequence) of an array are found in the *ArraySlice* structure.

[*maxLen*] is the maximal number of elements in an array.

[*array(n, x)*] returns a new array of length *n* whose elements are all *x*. Raises *Size* if *n*<0 or *n*>*maxLen*.

[*tabulate(n, f)*] returns a new array of length *n* whose elements are *f* 0, *f* 1, ..., *f* (*n*-1), created from left to right. Raises *Size* if *n*<0 or *n*>*maxLen*.

[*fromList xs*] returns an array whose elements are those of *xs*. Raises *Size* if length *xs* > *maxLen*.

[*length a*] returns the number of elements in *a*.

[sub(a, i)] returns the i^{th} element of a , counting from 0.
 Raises Subscript if $i < 0$ or $i \geq \text{length } a$. To make 'sub' infix, use
 the declaration

```
infix 9 sub
```

[update(a, i, x)] destructively replaces the i^{th} element of a by x .
 Raises Subscript if $i < 0$ or $i \geq \text{length } a$.

[copy{src, dst, di}] destructively copies the array src to dst ,
 starting at index di .
 Raises Subscript if $di < 0$, or if $di + \text{length } \text{src} > \text{length } \text{dst}$.

[copyVec{src, dst, di}] destructively copies the vector to dst ,
 starting at index di .
 Raises Subscript if $di < 0$, or if $di + \text{Vector.length } \text{src} > \text{length } \text{dst}$.

[find p a] applies p to each element x of a , from left to right,
 until $p(x)$ evaluates to true; returns SOME x if such an x exists,
 otherwise NONE.

[exists p a] applies p to each element x of a , from left to right,
 until $p(x)$ evaluates to true; returns true if such an x exists,
 otherwise false.

[all p a] applies p to each element x of a , from left to right,
 until $p(x)$ evaluates to false; returns false if such an x exists,
 otherwise true.

[foldl f e a] folds function f over a from left to right. That is,
 computes $f(a[\text{len}-1], f(a[\text{len}-2], \dots, f(a[1], f(a[0], e)) \dots))$,
 where len is the length of a .

[foldr f e a] folds function f over a from right to left. That is,
 computes $f(a[0], f(a[1], \dots, f(a[\text{len}-2], f(a[\text{len}-1], e)) \dots))$,
 where len is the length of a .

[app f a] applies f to $a[j]$ for $j=0,1,\dots,\text{length } a-1$.

[modify f a] applies f to $a[j]$ and updates $a[j]$ with the result
 $f(a[j])$ for $j=0,1,\dots,\text{length } a-1$.

The following iterators generalize the above ones by passing also
 the index j to the function being iterated.

[findi p a] applies f to successive pairs $(j, a[j])$ for $j=0,1,\dots,n-1$,
 until $p(j, a[j])$ evaluates to true; returns SOME $(j, a[j])$ if such
 a pair exists, otherwise NONE.

[foldli f e a] folds function f over the array from left to right.
 That is, computes $f(n-1, a[n-1], f(\dots, f(1, a[1], f(0, a[0], e)) \dots))$.

[foldri f e a] folds function f over the array from right to left.
 That is, computes $f(0, a[0], f(1, a[1], \dots, f(n-1, a[n-1], e) \dots))$.

[appi f a] applies f to successive pairs $(j, a[j])$ for $j=0,1,\dots,n-1$.

[modifyi f a] applies f to $(j, a[j])$ and updates $a[j]$ with the
 result $f(j, a[j])$ for $j=0,1,\dots,n-1$.

[collate cmp (xs, ys)] returns LESS, EQUAL or GREATER according as

xs precedes, equals or follows ys in the lexicographic ordering on arrays induced by the ordering cmp on elements.

Module Array2

```
Array2 -- SML Basis Library

eqtype 'a array

datatype traversal = RowMajor | ColMajor

val array      : int * int * '_a -> '_a array
val fromList   : '_a list list -> '_a array
val tabulate   : traversal -> int * int * (int * int -> '_a) -> '_a array

val dimensions : 'a array -> int * int
val nCols      : 'a array -> int
val nRows      : 'a array -> int

val sub         : 'a array * int * int -> 'a
val update     : 'a array * int * int * 'a -> unit

val row         : 'a array * int -> 'a Vector.vector
val column     : 'a array * int -> 'a Vector.vector

type 'a region = { base : 'a array, row : int, col : int,
                   nrows : int option, ncols : int option}

val copy        : { src : 'a region, dst : 'a array,
                   dst_row : int, dst_col : int } -> unit

val app         : traversal -> ('a -> unit) -> 'a array -> unit
val modify     : traversal -> ('a -> 'a) -> 'a array -> unit
val fold       : traversal -> ('a * 'b -> 'b) -> 'b -> 'a array -> 'b

val appi        : traversal -> (int * int * 'a -> unit) -> 'a region -> unit
val modifyi    : traversal -> (int * int * 'a -> 'a) -> 'a region -> unit
val foldi      : traversal -> (int * int * 'a * 'b -> 'b) -> 'b
                  -> 'a region -> 'b
```

[`ty array] is the type of two-dimensional, mutable, zero-based constant-time-access arrays with elements of type `ty.
 Type `ty array admits equality even if `ty does not. Arrays a1 and a2 are equal if both were created by the same call to one of the primitives array, fromList, and tabulate.

[traversal] is the type of traversal orders: row major or column major.

[RowMajor] specifies that an operation must be done in row-major order, that is, one row at a time, from top to bottom, and from left to right within each row. Row-major traversal visits the elements of an (m,n)-array with m rows and n columns in this order:

```
(0,0), (0,1), (0,2), ..., (0,n-1),
(1,0), (1,1), (1,2), ..., (1,n-1),
```

...

that is, in order of lexicographically increasing (i, j). In Moscow ML, row-major traversal is usually faster than column-major traversal.

[ColMajor] specifies that an operation must be done in column-major order, that is, one column at a time, from left to right, and from top to bottom within each column. Column-major traversal visits

the elements of an (m, n) -array with m rows and n columns in this order:

$(0,0), (1,0), (2,0), \dots, (m-1,0),$
 $(0,1), (1,1), (2,1), \dots, (m-1,1),$

...

that is, in order of lexicographically increasing (j, i) .

`[array(m, n, x)]` returns a new $m * n$ matrix whose elements are all x . Raises Size if $n < 0$ or $m < 0$.

`[fromList xs]` returns a new array whose first row has elements xs_1 , second row has elements xs_2, \dots , where $xs = [xs_1, xs_2, \dots, xs_m]$. Raises Size if the lists in xs do not all have the same length.

`[tabulate RowMajor (m, n, f)]` returns a new m -by- n array whose elements are $f(0,0), f(0,1), \dots, f(0, n-1),$
 $f(1,0), f(1,1), \dots, f(1, n-1),$

...

$f(m-1,0), \dots, f(m-1, n-1)$

created in row-major order: $f(0,0), f(0,1), \dots, f(1,0), f(1,1), \dots$

Raises Size if $n < 0$ or $m < 0$.

`[tabulate ColMajor (m, n, f)]` returns a new m -by- n array whose elements are as above, but created in the column-major order:
 $f(0,0), f(1,0), \dots, f(0, 1), f(1, 1), \dots$ Raises Size if $n < 0$ or $m < 0$.

`[dimensions a]` returns the dimensions (m, n) of a , where m is the number of rows and n the number of columns.

`[nCols a]` returns the number of n of columns of a .

`[nRows a]` returns the number of m of rows of a .

`[sub(a, i, j)]` returns the i 'th row's j 'th element, counting from 0. Raises Subscript if $i < 0$ or $j < 0$ or $i >= m$ or $j >= n$ where $(m, n) = \text{dimensions } a$.

`[update(a, i, j, x)]` destructively replaces the (i, j) 'th element of a by x . Raises Subscript if $i < 0$ or $j < 0$ or $i >= m$ or $j >= n$ where $(m, n) = \text{dimensions } a$.

`[row (a, i)]` returns a vector containing the elements of the i th row of a . Raises Subscript if $i < 0$ or $i >= \text{height } a$.

`[column (a, j)]` returns a vector containing the elements of the j th column of a . Raises Subscript if $j < 0$ or $j >= \text{width } a$.

`[app RowMajor f a]` applies f to the elements $a[0,0], a[0,1], \dots, a[0,n-1], a[1,0], \dots, a[m-1, n-1]$ of a , where $(m, n) = \text{dimensions } a$.

`[app ColMajor f a]` applies f to the elements $a[0,0], a[1,0], \dots, a[n-1,0], a[0,1], a[1,1], \dots, a[m-1, n-1]$ of a , where $(m, n) = \text{dimensions } a$.

`[modify RowMajor f a]` applies f to the elements $a[0,0], a[0,1], \dots, a[0,n-1], a[1,0], \dots, a[m-1, n-1]$ of a , updating each element with the result of the application, where $(m, n) = \text{dimensions } a$.

`[modify ColMajor f a]` applies f to the elements $a[0,0], a[1,0], \dots, a[n-1,0], a[0,1], a[1,1], \dots, a[m-1, n-1]$ of a , updating each element with the result of the application, where $(m, n) =$

dimensions a.

[fold RowMajor f b a] folds f left-right and top-down over the elements of a in row-major order. That is, computes
 $f(a[m-1, n-1], f(a[m-1, n-2], \dots, f(a[0,1], f(a[0,0], b)) \dots))$
where (m, n) = dimensions a.

[fold ColMajor f b a] folds f left-right and top-down over the elements of a in column-major order. That is, computes
 $f(a[m-1, n-1], f(a[m-2, n-1], \dots, f(a[1,0], f(a[0,0], b)) \dots))$
where (m, n) = dimensions a.

The following iterators generalize the above ones in two ways:

- * the indexes i and j are also being passed to the function;
- * the iterators work on a region (submatrix) of a matrix.

[region] is the type of records { base, row, col, nrows, ncols } determining the region or submatrix of array base whose upper left corner has index (row, col).

If nrows = SOME r, then the region has r rows: row, row+1, ..., row+r-1.
If nrows = NONE, then the region extends to the bottom of the matrix.
The field ncols similarly determines the number of columns.

A region is valid for an array with dimensions (m, n) if
(1) either nrows = NONE and $0 \leq row \leq m$
or nrows = SOME r and $0 \leq row \leq row + r \leq m$
and (2) either ncols = NONE and $0 \leq col \leq n$
or ncols = SOME c and $0 \leq col \leq col + c \leq n$.

[appi RowMajor f reg] applies f to (i, j, a[i, j]) in order of lexicographically increasing (i, j) within the region reg. Raises Subscript if reg is not valid. Note that appi tr f a is equivalent to appi tr (f o #3) {base=a, row=0, col=0, nrows=NONE, ncols=NONE}

[appi ColMajor f reg] applies f to (i, j, a[i, j]) in order of lexicographically increasing (j, i) within the region reg. Raises Subscript if reg is not valid.

[modifyi RowMajor f reg] applies f to (i, j, a[i, j]) in order of lexicographically increasing (i, j) within the region reg. Raises Subscript if reg is not valid. Note that modifyi tr f a is equivalent to modifyi (f o #3) {base=a, row=0, col=0, nrows=NONE, ncols=NONE}.

[modifyi ColMajor f reg] applies f to (i, j, a[i, j]) in order of lexicographically increasing (j, i) within the region reg. Raises Subscript if reg is not valid.

[foldi RowMajor f b a] folds f over (i, j, a[i, j]) in row-major order within the region reg, that is, for lexicographically increasing (i, j) in the region. Raises Subscript if reg is not valid.

[foldi ColMajor f b a] folds f over (i, j, a[i, j]) in column-major order within the region reg, that is, for lexicographically increasing (j, i) in the region. Raises Subscript if reg is not valid.

[copy { src, dst, dst_row, dst_col }] copies the region determined

by src to array dst such that the upper leftmost corner of src is copied to dst[dst_row, dst_col]. Works correctly even when src and dst are the same and the source and destination regions overlap. Raises Subscript if the src region is invalid, or if src translated to (dst_row, dst_col) is invalid for dst.

Module ArraySlice

ArraySlice -- SML Basis Library

```
type 'a slice

val length    : 'a slice -> int
val sub       : 'a slice * int -> 'a
val update    : 'a slice * int * 'a -> unit
val slice     : 'a Array.array * int * int option -> 'a slice
val full      : 'a Array.array -> 'a slice
val subslice  : 'a slice * int * int option -> 'a slice
val base      : 'a slice -> 'a Array.array * int * int
val vector    : 'a slice -> 'a Vector.vector
val copy      : {src: 'a slice, dst: 'a Array.array, di: int} -> unit
val copyVec   : {src: 'a VectorSlice.slice, dst: 'a Array.array, di: int}
                -> unit
val isEmpty   : 'a slice -> bool
val getItem   : 'a slice -> ('a * 'a slice) option

val find      : ('a -> bool) -> 'a slice -> 'a option
val exists    : ('a -> bool) -> 'a slice -> bool
val all       : ('a -> bool) -> 'a slice -> bool

val app       : ('a -> unit) -> 'a slice -> unit
val foldl    : ('a * 'b -> 'b) -> 'b -> 'a slice -> 'b
val foldr    : ('a * 'b -> 'b) -> 'b -> 'a slice -> 'b
val modify   : ('a -> 'a) -> 'a slice -> unit

val findi    : (int * 'a -> bool) -> 'a slice -> (int * 'a) option
val appi     : (int * 'a -> unit) -> 'a slice -> unit
val foldli   : (int * 'a * 'b -> 'b) -> 'b -> 'a slice -> 'b
val foldri   : (int * 'a * 'b -> 'b) -> 'b -> 'a slice -> 'b
val modifyi  : (int * 'a -> 'a) -> 'a slice -> unit

val collate  : ('a * 'a -> order) -> 'a slice * 'a slice -> order
```

[`ty slice] is the type of array slices, that is, sub-arrays.
 The slice (a,i,n) is valid if $0 \leq i \leq i+n \leq \text{size } s$,
 or equivalently, $0 \leq i$ and $0 \leq n$ and $i+n \leq \text{size } s$.
 A valid slice sli = (a,i,n) represents the sub-array $a[i \dots i+n-1]$,
 so the elements of sli are $a[i], a[i+1], \dots, a[i+n-1]$, and n is
 the length of the slice. Only valid slices can be constructed by
 the functions below.

[length sli] returns the number n of elements in sli = (s,i,n).

[sub (sli, k)] returns the k'th element of the slice, that is,
 $a(i+k)$ where sli = (a,i,n). Raises Subscript if $k < 0$ or $k >= n$.

[update (sli, k, x)] destructively replaces the k'th element of sli
 by x. That is, replaces $a(k+i)$ by x, where sli = (a,i,n). Raises
 Subscript if $i < 0$ or $i > \text{Array.length } a$.

[slice (a, i, NONE)] creates the slice (a, i, length a-i),
 consisting of the tail of a starting at i.
 Raises Subscript if $i < 0$ or $i > \text{Array.length } a$.
 Equivalent to slice (a, i, SOME(Array.length a - i)).

[slice (a, i, SOME n)] creates the slice (a, i, n), consisting of

the sub-array of a with length n starting at i . Raises Subscript if $i < 0$ or $n < 0$ or $i+n > \text{length } a$.

slice	meaning	
(a , 0, NONE)	the whole array	$a[0..len-1]$
(a , 0, SOME n)	a left sub-array (prefix)	$a[0..n-1]$
(a , i , NONE)	a right sub-array (suffix)	$a[i..len-1]$
(a , i , SOME n)	a general slice	$a[i..i+n-1]$

[full a] creates the slice (a , 0, length a).
Equivalent to slice($a, 0, \text{NONE}$)

[subslice (sli, i' , NONE)] returns the slice (a , $i+i'$, $n-i'$) when sli = (a, i, n). Raises Subscript if $i' < 0$ or $i' > n$.

[subslice (sli, i' , SOME n')] returns the slice (a , $i+i'$, n') when sli = (a, i, n). Raises Subscript if $i' < 0$ or $n' < 0$ or $i'+n' > n$.

[base sli] is the concrete triple (a , i , n) when sli = (a , i , n).

[vector sli] creates and returns a vector consisting of the elements of the slice, that is, $a[i..i+n-1]$ when sli = (a, i, n).

[copy {src, dst, di}] copies the elements of slice src = (a, i, n), that is, $a[i..i+n-1]$, to the destination segment dst[di..di+n-1]. Raises Subscript if $di < 0$ or if $di+n > \text{length } dst$. Works also if the array underlying sli is the same as dst, and the slice overlaps with the destination segment.

[copyVec {src, dst, di}] copies the elements of the vector slice src = (v, i, n), that is, $v[i..i+n-1]$, to dst[di..di+n-1]. Raises Subscript if $di < 0$, or if $\text{len}=\text{NONE}$ and $di + n > \text{length } dst$.

[isEmpty sli] returns true if the slice sli = (a, i, n) is empty, that is, if $n=0$.

[getItem sli] returns SOME(x, rst) where x is the first element and rst the remainder of sli, if sli is non-empty; otherwise returns NONE.

[find p sli] applies p to each element x of sli, from left to right, until $p(x)$ evaluates to true; returns SOME x if such an x exists, otherwise NONE.

[exists p sli] applies p to each element x of sli, from left to right, until $p(x)$ evaluates to true; returns true if such an x exists, otherwise false.

[all p sli] applies p to each element x of sli, from left to right, until $p(x)$ evaluates to false; returns false if such an x exists, otherwise true.

[app f sli] applies f to all elements of sli = (a, i, n), from left to right. That is, applies f to $a[j+i]$ for $j=0, 1, \dots, n$.

[foldl f e sli] folds function f over sli = (a, i, n) from left to right. That is, computes $f(a[i+n-1], f(a[i+n-2], \dots, f(a[i+1], f(a[i], e))\dots))$.

[foldr f e sli] folds function f over sli = (a, i, n) from right to left. That is, computes $f(a[i], f(a[i+1], \dots, f(a[i+n-2], f(a[i+n-1], e))\dots))$.

[modify f sli] modifies the elements of the slice $sli = (a, i, n)$ by function f. That is, applies f to $a[i+j]$ and updates $a[i+j]$ with the result $f(a[i+j])$ for $j=0, 1, \dots, n$.

The following iterators generalize the above ones by also passing the index into the array a underlying the slice to the function being iterated.

[findi p sli] applies p to the elements of $sli = (a, i, n)$ and the underlying array indices, and returns the least $(j, a[j])$ for which $p(j, a[j])$ evaluates to true, if any; otherwise returns NONE. That is, evaluates $p(j, a[j])$ for $j=i, \dots, i+n-1$ until it evaluates to true for some j, then returns SOME($j, a[j]$); otherwise returns NONE.

[appi f sli] applies f to the slice $sli = (a, i, n)$ and the underlying array indices. That is, applies f to successive pairs $(j, a[j])$ for $j=i, i+1, \dots, i+n-1$.

[foldli f e sli] folds function f over the slice $sli = (a, i, n)$ and the underlying array indices from left to right. That is, computes $f(i+n-1, a[i+n-1], f(\dots, f(i+1, a[i+1], f(i, a[i], e)) \dots))$.

[foldri f e sli] folds function f over the slice $sli = (a, i, n)$ and the underlying array indices from right to left. That is, computes $f(i, a[i], f(i+1, a[i+1], \dots, f(i+n-1, a[i+n-1], e) \dots))$.

[modifyi f sli] modifies the elements of the slice $sli = (a, i, n)$ by applying function f to the slice elements and the underlying array indices. That is, applies f to $(j, a[j])$ and updates $a[j]$ with the result $f(j, a[j])$ for $j=i, i+1, \dots, i+n-1$.

[collate cmp (sli1, sli2)] returns LESS, EQUAL or GREATER according as sli1 precedes, equals or follows sli2 in the lexicographic ordering on slices induced by the ordering cmp on elements.

Module Arraysort

Arraysort -- Quicksort for arrays, from SML/NJ library

```
val sort    : ('a * 'a -> order) -> 'a Array.array -> unit
val sorted : ('a * 'a -> order) -> 'a Array.array -> bool
```

[sort ordr arr] sorts array arr in-place, using ordering relation ordr.

[sorted ordr arr] returns true if the elements of array arr is
appear in (weakly) increasing order, according to ordering ordr.

Module BinIO

BinIO -- SML Basis Library

```
type elem    = Word8.word
type vector = Word8Vector.vector

Binary input

type instream

val openIn      : string -> instream
val closeIn     : instream -> unit
val input       : instream -> vector
val inputAll   : instream -> vector
val inputNoBlock : instream -> vector option
val input1      : instream -> elem option
val inputN      : instream * int -> vector
val endOfStream : instream -> bool
val lookahead   : instream -> elem option
```

Binary output

```
type outstream

val openOut     : string -> outstream
val openAppend  : string -> outstream
val closeOut    : outstream -> unit
val output      : outstream * vector -> unit
val output1     : outstream * elem -> unit
val flushOut    : outstream -> unit
```

This structure provides input/output functions on byte streams. The functions are state-based: reading from or writing to a stream changes the state of the stream. The streams are buffered: output to a stream may not immediately affect the underlying file or device.

[instream] is the type of state-based byte input streams.

[outstream] is the type of state-based byte output streams.

[elem] is the type Word8.word of bytes.

[vector] is the type of Word8Vector.vector (byte vectors).

BYTE INPUT:

[openIn s] creates a new instream associated with the file named s. Raises Io.Io if file s does not exist or is not accessible.

[closeIn istr] closes stream istr. Has no effect if istr is closed already. Further operations on istr will behave as if istr is at end of stream (that is, will return "" or NONE or true).

[input istr] reads some elements from istr, returning a vector v of those elements. The vector will be empty (size v = 0) if and only if istr is at end of stream or is closed. May block (not return until data are available in the external world).

[inputAll istr] reads and returns the vector v of all bytes remaining in istr up to end of stream.

[inputNoBlock istr] returns SOME(v) if some elements v can be read without blocking; returns SOME("") if it can be determined without blocking that istr is at end of stream; returns NONE otherwise. If istr does not support non-blocking input, raises Io.NonblockingNotSupported.

[input1 istr] returns SOME(e) if at least one element e of istr is available; returns NONE if istr is at end of stream or is closed; blocks if necessary until one of these conditions holds.

[inputN(istr, n)] returns the next n bytes from istr as a vector, if that many are available; returns all remaining bytes if end of stream is reached before n bytes are available; blocks if necessary until one of these conditions holds.

[endOfStream istr] returns false if any elements are available in istr; returns true if istr is at end of stream or closed; blocks if necessary until one of these conditions holds.

[lookahead istr] returns SOME(e) where e is the next element in the stream; returns NONE if istr is at end of stream or is closed; blocks if necessary until one of these conditions holds. Does not advance the stream.

BYTE OUTPUT:

[openOut s] creates a new outstream associated with the file named s. If file s does not exist, and the directory exists and is writable, then a new file is created. If file s exists, it is truncated (any existing contents are lost).

[openAppend s] creates a new outstream associated with the file named s. If file s does not exist, and the directory exists and is writable, then a new file is created. If file s exists, any existing contents are retained, and output goes at the end of the file.

[closeOut ostr] closes stream ostr; further operations on ostr (except for additional close operations) will raise exception Io.Io.

[output(ostr, v)] writes the byte vector v on outstream ostr.

[output1(ostr, e)] writes the byte e on outstream ostr.

[flushOut ostr] flushes the outstream ostr, so that all data written to ostr becomes available to the underlying file or device.

The functions below are not yet implemented:

[setPosIn(istr, i)] sets istr to the position i. Raises Io.Io if not supported on istr.

[getPosIn istr] returns the current position of istr. Raises Io.Io if not supported on istr.

[endPosIn istr] returns the last position of istr.

[getPosOut ostr] returns the current position in stream ostr.
Raises Io.Io if not supported on ostr.

[endPosOut ostr] returns the ending position in stream ostr.
Raises Io.Io if not supported on ostr.

[setPosOut(ostr, i)] sets the current position in stream to ostr to i. Raises Io.Io if not supported on ostr.

[mkInstream sistr] creates a state-based instream from the functional instream sistr.

[getInstream istr] returns the functional instream underlying the state-based instream istr.

[setInstream(istr, sistr)] redirects istr, so that subsequent input is taken from the functional instream sistr.

[mkOutstream sostr] creates a state-based outstream from the outstream sostr.

[getOutstream ostr] returns the outstream underlying the state-based outstream ostr.

[setOutstream(ostr, sostr)] redirects the outstream ostr so that subsequent output goes to sostr.

Module Binarymap

*Binarymap -- applicative maps as balanced ordered binary trees
 From SML/NJ lib 0.2, copyright 1993 by AT&T Bell Laboratories
 Original implementation due to Stephen Adams, Southampton, UK*

```
type ('key, 'a) dict

exception NotFound

val mkDict      : ('key * 'key -> order) -> ('key, 'a) dict
val insert     : ('key, 'a) dict * 'key * 'a -> ('key, 'a) dict
val find       : ('key, 'a) dict * 'key -> 'a
val peek       : ('key, 'a) dict * 'key -> 'a option
val remove     : ('key, 'a) dict * 'key -> ('key, 'a) dict * 'a
val numItems   : ('key, 'a) dict -> int
val listItems  : ('key, 'a) dict -> ('key * 'a) list
val app        : ('key * 'a -> unit) -> ('key, 'a) dict -> unit
val revapp    : ('key * 'a -> unit) -> ('key, 'a) dict -> unit
val foldr      : ('key * 'a * 'b -> 'b) -> 'b -> ('key, 'a) dict -> 'b
val foldl      : ('key * 'a * 'b -> 'b) -> 'b -> ('key, 'a) dict -> 'b
val map        : ('key * 'a -> 'b) -> ('key, 'a) dict -> ('key, 'b) dict
val transform  : ('a -> 'b) -> ('key, 'a) dict -> ('key, 'b) dict
```

[('key, 'a) dict] is the type of applicative maps from domain type 'key to range type 'a, or equivalently, applicative dictionaries with keys of type 'key and values of type 'a. They are implemented as ordered balanced binary trees.

[mkDict ordr] returns a new, empty map whose keys have ordering ordr.

[insert(m, i, v)] extends (or modifies) map m to map i to v.

[find(m, k)] returns v if m maps k to v; otherwise raises NotFound.

[peek(m, k)] returns SOME v if m maps k to v; otherwise returns NONE.

[remove(m, k)] removes k from the domain of m and returns the modified map and the element v corresponding to k. Raises NotFound if k is not in the domain of m.

[numItems m] returns the number of entries in m (that is, the size of the domain of m).

[listItems m] returns a list of the entries (k, v) of keys k and the corresponding values v in m, in order of increasing key values.

[app f m] applies function f to the entries (k, v) in m, in increasing order of k (according to the ordering ordr used to create the map or dictionary).

[revapp f m] applies function f to the entries (k, v) in m, in decreasing order of k.

[foldl f e m] applies the folding function f to the entries (k, v) in m, in increasing order of k.

[foldr f e m] applies the folding function f to the entries (k, v) in m, in decreasing order of k.

[map f m] returns a new map whose entries have form (k, f(k,v)), where (k, v) is an entry in m.

[transform f m] returns a new map whose entries have form (k, f v), where (k, v) is an entry in m.

Module Binaryset

*Binaryset -- sets implemented by ordered balanced binary trees
 From SML/NJ lib 0.2, copyright 1993 by AT&T Bell Laboratories
 Original implementation due to Stephen Adams, Southampton, UK*

```
type 'item set

exception NotFound

val empty      : ('item * 'item -> order) -> 'item set
val singleton   : ('item * 'item -> order) -> 'item -> 'item set
val add         : 'item set * 'item -> 'item set
val addList     : 'item set * 'item list -> 'item set
val retrieve    : 'item set * 'item -> 'item
val peek        : 'item set * 'item -> 'item option
val isEmpty     : 'item set -> bool
val equal       : 'item set * 'item set -> bool
val isSubset    : 'item set * 'item set -> bool
val member      : 'item set * 'item -> bool
val delete      : 'item set * 'item -> 'item set
val numItems    : 'item set -> int
val union       : 'item set * 'item set -> 'item set
val intersection: 'item set * 'item set -> 'item set
val difference  : 'item set * 'item set -> 'item set
val listItems   : 'item set -> 'item list
val app         : ('item -> unit) -> 'item set -> unit
val revapp     : ('item -> unit) -> 'item set -> unit
val foldr       : ('item * 'b -> 'b) -> 'b -> 'item set -> 'b
val foldl       : ('item * 'b -> 'b) -> 'b -> 'item set -> 'b
val find        : ('item -> bool) -> 'item set -> 'item option
```

[`item set] is the type of sets of ordered elements of type 'item.
 The ordering relation on the elements is used in the representation
 of the set. The result of combining two sets with different
 underlying ordering relations is undefined. The implementation
 uses ordered balanced binary trees.

[empty ordr] creates a new empty set with the given ordering
 relation.

[singleton ordr i] creates the singleton set containing i, with the
 given ordering relation.

[add(s, i)] adds item i to set s.

[addList(s, xs)] adds all items from the list xs to the set s.

[retrieve(s, i)] returns i if it is in s; raises NotFound otherwise.

[peek(s, i)] returns SOME i if i is in s; returns NONE otherwise.

[isEmpty s] returns true if and only if the set is empty.

[equal(s1, s2)] returns true if and only if the two sets have the
 same elements.

[isSubset(s1, s2)] returns true if and only if s1 is a subset of s2.

[member(s, i)] returns true if and only if i is in s.

[`delete(s, i)`] removes item `i` from `s`. Raises `NotFound` if `i` is not in `s`.

[`numItems s`] returns the number of items in set `s`.

[`union(s1, s2)`] returns the union of `s1` and `s2`.

[`intersection(s1, s2)`] returns the intersection of `s1` and `s2`.

[`difference(s1, s2)`] returns the difference between `s1` and `s2` (that is, the set of elements in `s1` but not in `s2`).

[`listItems s`] returns a list of the items in set `s`, in increasing order.

[`app f s`] applies function `f` to the elements of `s`, in increasing order.

[`revapp f s`] applies function `f` to the elements of `s`, in decreasing order.

[`foldl f e s`] applies the folding function `f` to the entries of the set in increasing order.

[`foldr f e s`] applies the folding function `f` to the entries of the set in decreasing order.

[`find p s`] returns SOME `i`, where `i` is an item in `s` which satisfies `p`, if one exists; otherwise returns NONE.

Module Bool

Bool -- SML Basis Library

```
datatype bool = datatype bool  
val not      : bool -> bool  
val toString : bool -> string  
val fromString : string -> bool option  
val scan     : (char, 'a) StringCvt.reader -> (bool, 'a) StringCvt.reader
```

[bool] is the type of Boolean (logical) values: true and false.

[not b] is the logical negation of b.

[toString b] returns the string "false" or "true" according as b is false or true.

[fromString s] scans a boolean b from the string s, after possible initial whitespace (blanks, tabs, newlines). Returns (SOME b) if s has a prefix which is either "false" or "true"; the value b is the corresponding truth value; otherwise NONE is returned.

[scan getc src] scans a boolean b from the stream src, using the stream accessor getc. In case of success, returns SOME(b, rst) where b is the scanned boolean value and rst is the remainder of the stream; otherwise returns NONE.

Module Buffer

```
signature Buffer =
sig
    type buf
    val new      : int -> buf
    val contents : buf -> string
    val size     : buf -> int
    val clear    : buf -> unit
    val reset    : buf -> unit

    val addChar   : buf -> char -> unit
    val addString : buf -> string -> unit
    val addSubString : buf -> substring -> unit
end
```

concatenation at the end and automatically expand as necessary. It provides accumulative concatenation of strings in quasi-linear time (instead of quadratic time when strings are concatenated pairwise).

[new hint] creates a new empty buffer. Raises Size if hint <= 0 or hint > String.maxSize.

The argument hint is used as the initial size of the internal string that holds the buffer contents. The internal string is automatically reallocated as contents is stored in the buffer. For best performance, hint should be of the same order of magnitude as the number of characters that are expected to be stored in the buffer (for instance, 80 for a buffer that holds one output line). Nothing bad will happen if the buffer grows beyond that limit, however. In doubt, take hint = 16 for instance.

[contents buf] returns the contents of buf.

[size buf] returns the size of the contents of buf.

[clear buf] emptys buf.

[reset buf] emptys buf and shrink the internal string to the initial hint.

[addChar buf c] appends c at the end of buf.

[addString buf s] appends s at the end of buf.

[addSubString buf ss] appends ss at the end of buf.

Module Byte

Byte -- SML Basis Library

```
val byteToChar      : Word8.word -> Char.char
val charToByte     : Char.char -> Word8.word
val bytesToString  : Word8Vector.vector -> String.string
val stringToBytes  : String.string -> Word8Vector.vector

val unpackStringVec : Word8VectorSlice.slice -> string
val unpackString    : Word8ArraySlice.slice -> string
val packString      : Word8Array.array * int * Substring.substring -> unit
```

Conversions between bytes and characters, and between byte vectors and strings (character vectors).

[byteToChar w] is the character corresponding to the byte w.

[charToByte c] is the byte corresponding to character c.

[bytesToString v] is the string whose character codes are the bytes from vector v.

[stringToBytes s] is the byte vector of character codes of the string s.

In Moscow ML, all the above operations take constant time. That is, no copying is done.

[unpackStringVec v] is the string whose character codes are the bytes from the vector slice v.

[unpackString a] is the string whose character codes are the bytes from the array slice a.

[packString (a, i, ss)] copies the character codes of substring ss into the subarray a[i..i+n-1] where n = Substring.size ss. Raises Subscript if i<0 or i+n > length a.

Module Callback

Callback -- registering ML values with C, and accessing C values from ML

Registering ML values for access from C code:

```
val register      : string -> 'a -> unit
val unregister   : string -> unit
val isRegistered : string -> bool
```

Accessing C variables and functions from ML:

```
type cptr

val getcptr : string -> cptr
val var     : cptr -> 'b
val app1    : cptr -> 'a1 -> 'b
val app2    : cptr -> 'a1 -> 'a2 -> 'b
val app3    : cptr -> 'a1 -> 'a2 -> 'a3 -> 'b
val app4    : cptr -> 'a1 -> 'a2 -> 'a3 -> 'a4 -> 'b
val app5    : cptr -> 'a1 -> 'a2 -> 'a3 -> 'a4 -> 'a5 -> 'b
```

REGISTERING ML VALUES FOR ACCESS FROM C CODE

This example shows how to register the ML function (fn n => 2*n) so that it may be called from C code.

(0) The ML side registers the function:
`Callback.register "myfun" (fn n => 2*n)`

(1) The C side first obtains an ML value pointer:
`valueptr mvp = get_valueptr("myfun");`

(2) The C side then uses the ML value pointer to obtain an ML value, and uses it:
`callback(get_value(mvp), Val_long(42));`

Operation (1) involves a callback to ML, and hence may be slow. Calling `get_valueptr` may cause the garbage collector to run; hence other live ML values must be registered as GC roots. The garbage collector will never move the ML value pointer; hence it need not be registered as a GC root in the C code.

Operation (2) is very fast. If the garbage collector is invoked between the call of `get_value()` and the use of the ML value, then the value must be registered as a GC root. However, the idiom
`callback(get_value(mvp), arg1);`
is safe provided the evaluation of `arg1` does not provoke a garbage collection (e.g. if `arg1` is a variable).

The C function `get_valueptr` returns NULL if nam is not registered.

The C function `get_value` returns NULL if nam has been unregistered (and not reregistered) since mvp was obtained; it raises exception Fail if mvp itself is NULL. Every access to the ML value from C code should use the ML `valueptr` and `get_valueptr`, otherwise the C code will not know when the value has been unregistered and possibly deallocated.

The C functions (in mosml/src/runtime/callback.c)
 void registervalue(char* nam, value mval)
 void unregistervalue(char* nam)
 can be used just as Callback.register and Callback.unregister.

The C functions
 value callbackptr (valueptr mvp, value arg1)
 value callbackptr2(valueptr mvp, value arg1, value arg2)
 value callbackptr3(valueptr mvp, value arg1, value arg2, value arg3)
 can be used for callback via an ML value pointer; they will raise exception Fail if the ML function indicated by mvp has been unregistered.

[register nam v] registers the ML value v, so that it can be retrieved from C code under the name nam. If nam has previously been registered and then unregistered, it will be reregistered with the new value. The new value immediately becomes visible to the C side, both via get_valueptr(nam) and via any ML value pointer previously obtained for nam. Raises exception Fail if nam has been registered and not yet unregistered.

[unregister nam] deletes the registration. This prevents C code from obtaining an ML value pointer for nam and from using an ML value pointer already obtained (but does not prevent C from attempting to use a stored ML value previously obtained with the help of the ML value pointer, which is unsafe anyway). Does nothing if nam is already unregistered. Raises exception Fail if nam has never been registered.

[isRegistered nam] returns true if nam has been registered and not yet unregistered.

ACCESSING REGISTERED C VARIABLES AND FUNCTIONS FROM ML

This example shows how to register the C function

```
value sillycfun(value v)
{ return copy_double(42.42 * Double_val(v)); }
```

so that it may be called from ML.

- (0) The C side registers the function:
`registercptr("mycfun", sillycfun);`
- (1) The ML side obtains a C pointer and defines an ML function via that pointer:
`val sillycfun = app1 (getcptr "mycfun") : real -> real`
 The type ascription is needed to ensure any type safety whatsoever. Mistakes in the types will lead to crashes, as usual with C.
- (2) To the ML side, the new ML function is indistinguishable from other ML functions
`val result = sillyfun(3.4)`

The C function (in mosml/src/runtime/callback.c)

```
void registercptr(char* nam, void* cptr);
```

is used to register C pointers for access from ML. Only pointers to static C variables, and C functions, should be registered. There is no way to unregister a C pointer.

[cptr] is the type of pointers to C variables and C functions.

[getcptr nam] returns a pointer to the C variable or function registered (by the C side) under the name nam. Raises exception Fail if the name nam has not been registered.

[var cptra] returns the value of the C variable associated with cptra.

[app1 cptra arg1] applies the C function associated with cptra to arg1.

[app2 cptra arg1 arg2] applies the C function associated with cptra to (arg1, arg2).

[app3 cptra arg1 arg2 arg3] applies the C function associated with cptra to (arg1, arg2, arg3).

[app4 cptra arg1 arg2 arg3 arg4] applies the C function associated with cptra to (arg1, arg2, arg3, arg4).

[app5 cptra arg1 arg2 arg3 arg4 arg5] applies the C function associated with cptra to (arg1, arg2, arg3, arg4, arg5).

Module Char

Char -- SML Basis Library

```

type char = char

val minChar : char
val maxChar : char
val maxOrd  : int

val chr      : int    -> char      May raise Chr
val ord     : char -> int
val succ    : char -> char      May raise Chr
val pred    : char -> char      May raise Chr

val isLower   : char -> bool    contains "abcdefghijklmnopqrstuvwxyz"
val isUpper   : char -> bool    contains "ABCDEFGHIJKLMNOPQRSTUVWXYZ"
val isDigit   : char -> bool    contains "0123456789"
val isAlpha   : char -> bool    isUpper orelse isLower
val isHexDigit : char -> bool  isDigit orelse contains "abcdefABCDEF"
val isAlphaNum : char -> bool  isAlpha orelse isDigit
val isPrint   : char -> bool    any printable character (incl. # " ")
val isSpace   : char -> bool    contains "\t\r\n\f"
val isPunct   : char -> bool    printable, not space or alphanumeric
val isGraph   : char -> bool    (not isSpace) andalso isPrint
val isAscii   : char -> bool    ord c < 128
val isCntrl   : char -> bool    control character

val toLower   : char -> char
val toUpper   : char -> char

val fromString : string -> char option      ML escape sequences
val toString   : char -> string            ML escape sequences

val fromCString : string -> char option      C escape sequences
val toCString  : char -> string            C escape sequences

val contains   : string -> char -> bool
val notContains : string -> char -> bool

val <       : char * char -> bool
val <=      : char * char -> bool
val >       : char * char -> bool
val >=      : char * char -> bool
val compare  : char * char -> order

```

[char] is the type of characters.

[minChar] is the least character in the ordering <.

[maxChar] is the greatest character in the ordering <.

[maxOrd] is the greatest character code; equals ord(maxChar).

[chr i] returns the character whose code is i. Raises Chr if i<0 or i>maxOrd.

[ord c] returns the code of character c.

[succ c] returns the character immediately following c, or raises

Chr if $c = \text{maxChar}$.
 [pred c] returns the character immediately preceding c , or raises Chr if $c = \text{minChar}$.
 [isLower c] returns true if c is a lowercase letter (a to z).
 [isUpper c] returns true if c is a uppercase letter (A to Z).
 [isDigit c] returns true if c is a decimal digit (0 to 9).
 [isAlpha c] returns true if c is a letter (lowercase or uppercase).
 [isHexDigit c] returns true if c is a hexadecimal digit (0 to 9 or a to f or A to F).
 [isAlphaNum c] returns true if c is alphanumeric (a letter or a decimal digit).
 [isPrint c] returns true if c is a printable character (space or visible)
 [isSpace c] returns true if c is a whitespace character (blank, newline, tab, vertical tab, new page).
 [isGraph c] returns true if c is a graphical character, that is, it is printable and not a whitespace character.
 [isPunct c] returns true if c is a punctuation character, that is, graphical but not alphanumeric.
 [isCntrl c] returns true if c is a control character, that is, if not (isPrint c).
 [isAscii c] returns true if $0 \leq \text{ord } c \leq 127$.
 [toLower c] returns the lowercase letter corresponding to c , if c is a letter (a to z or A to Z); otherwise returns c .
 [toUpper c] returns the uppercase letter corresponding to c , if c is a letter (a to z or A to Z); otherwise returns c .
 [contains s c] returns true if character c occurs in the string s ; false otherwise. The function, when applied to s , builds a table and returns a function which uses table lookup to decide whether a given character is in the string or not. Hence it is relatively expensive to compute val $p = \text{contains } s$ but very fast to compute $p(c)$ for any given character.
 [notContains s c] returns true if character c does not occur in the string s ; false otherwise. Works by construction of a lookup table in the same way as the above function.
 [fromString s] attempts to scan a character or ML escape sequence from the string s . Does not skip leading whitespace. For instance, fromString "\065" equals #" A ".
 [toString c] returns a string consisting of the character c , if c is printable, else an ML escape sequence corresponding to c . A printable character is mapped to a one-character string; bell, backspace, tab, newline, vertical tab, form feed, and carriage return are mapped to the two-character strings "\a", "\b", "\t",

"\\n", "\\v", "\\f", and "\\r"; other characters with code less than 32 are mapped to three-character strings of the form "\\^z", and characters with codes 127 through 255 are mapped to four-character strings of the form "\\ddd", where ddd are three decimal digits representing the character code. For instance,

```

toString # "A"      equals "A"
toString # "\\\"     equals "\\\""
toString # "\\\""    equals "\\\""
toString (chr 0)   equals "\\^@"
toString (chr 1)   equals "\\^A"
toString (chr 6)   equals "\\^F"
toString (chr 7)   equals "\\a"
toString (chr 8)   equals "\\b"
toString (chr 9)   equals "\\t"
toString (chr 10)  equals "\\n"
toString (chr 11)  equals "\\v"
toString (chr 12)  equals "\\f"
toString (chr 13)  equals "\\r"
toString (chr 14)  equals "\\^N"
toString (chr 127) equals "\\127"
toString (chr 128) equals "\\128"

```

[fromCString s] attempts to scan a character or C escape sequence from the string s. Does not skip leading whitespace. For instance, fromString "\\065" equals "#A".

[toCString c] returns a string consisting of the character c, if c is printable, else an C escape sequence corresponding to c. A printable character is mapped to a one-character string; bell, backspace, tab, newline, vertical tab, form feed, and carriage return are mapped to the two-character strings "\\a", "\\b", "\\t", "\\n", "\\v", "\\f", and "\\r"; other characters are mapped to four-character strings of the form "\\ooo", where ooo are three octal digits representing the character code. For instance,

```

toString # "A"      equals "A"
toString # "A"      equals "A"
toString # "\\\"     equals "\\\""
toString # "\\\""    equals "\\\""
toString (chr 0)   equals "\\000"
toString (chr 1)   equals "\\001"
toString (chr 6)   equals "\\006"
toString (chr 7)   equals "\\a"
toString (chr 8)   equals "\\b"
toString (chr 9)   equals "\\t"
toString (chr 10)  equals "\\n"
toString (chr 11)  equals "\\v"
toString (chr 12)  equals "\\f"
toString (chr 13)  equals "\\r"
toString (chr 14)  equals "\\016"
toString (chr 127) equals "\\177"
toString (chr 128) equals "\\200"

```

[<]
[<=]
[>]

[>=] compares character codes. For instance, c1 < c2 returns true if ord(c1) < ord(c2), and similarly for <=, >, >=.

[compare(c1, c2)] returns LESS, EQUAL, or GREATER, according as c1 is precedes, equals, or follows c2 in the ordering Char.< .

Module CharArray

CharArray -- SML Basis Library

```

eqtype array
type elem    = Char.char
type vector = CharVector.vector

val maxlen   : int
val array    : int * elem -> array
val tabulate : int * (int -> elem) -> array
val fromList : elem list -> array

val length   : array -> int
val sub      : array * int -> elem
val update   : array * int * elem -> unit
val vector   : array -> vector

val copy     : {src: array, dst: array, di: int} -> unit
val copyVec  : {src: vector, dst: array, di: int} -> unit

val find     : (elem -> bool) -> array -> elem option
val exists   : (elem -> bool) -> array -> bool
val all      : (elem -> bool) -> array -> bool

val app      : (elem -> unit) -> array -> unit
val foldl   : (elem * 'b -> 'b) -> 'b -> array -> 'b
val foldr   : (elem * 'b -> 'b) -> 'b -> array -> 'b
val modify  : (elem -> elem) -> array -> unit

val findi   : (int * elem -> bool) -> array -> (int * elem) option
val appi    : (int * elem -> unit) -> array -> unit
val foldli  : (int * elem * 'b -> 'b) -> 'b -> array -> 'b
val foldri  : (int * elem * 'b -> 'b) -> 'b -> array -> 'b
val modifyi : (int * elem -> elem) -> array -> unit

val collate : (elem * elem -> order) -> array * array -> order

```

[array] is the type of one-dimensional, mutable, zero-based constant-time-access arrays with elements of type Char.char, that is, characters. Arrays a1 and a2 are equal if both were created by the same call to a primitive, or if both are empty.

All operations are as for Array.array.

Module CharArraySlice

CharArraySlice -- SML Basis Library

```
type elem = char
type array = CharArray.array
type vector = CharVector.vector
type vector_slice = CharVectorSlice.slice

type slice

val length    : slice -> int
val sub       : slice * int -> elem
val update   : slice * int * elem -> unit
val slice    : array * int * int option -> slice
val full     : array -> slice
val subslice : slice * int * int option -> slice
val base     : slice -> array * int * int
val vector   : slice -> vector
val copy     : {src: slice, dst: array, di: int} -> unit
val copyVec  : {src: vector_slice, dst: array, di: int} -> unit
val isEmpty  : slice -> bool
val getItem  : slice -> (elem * slice) option

val find      : (elem -> bool) -> slice -> elem option
val exists   : (elem -> bool) -> slice -> bool
val all       : (elem -> bool) -> slice -> bool

val app      : (elem -> unit) -> slice -> unit
val foldl   : (elem * 'b -> 'b) -> 'b -> slice -> 'b
val foldr   : (elem * 'b -> 'b) -> 'b -> slice -> 'b
val modify  : (elem -> elem) -> slice -> unit

val findi   : (int * elem -> bool) -> slice -> (int * elem) option
val appi    : (int * elem -> unit) -> slice -> unit
val foldli  : (int * elem * 'b -> 'b) -> 'b -> slice -> 'b
val foldri  : (int * elem * 'b -> 'b) -> 'b -> slice -> 'b
val modifyi : (int * elem -> elem) -> slice -> unit

val collate : (elem * elem -> order) -> slice * slice -> order
```

[slice] is the type of CharArray slices, that is, sub-arrays of CharArray.array values.

The slice (a,i,n) is valid if $0 \leq i \leq i+n \leq \text{size } s$,
or equivalently, $0 \leq i$ and $0 \leq n$ and $i+n \leq \text{size } s$.
A valid slice sli = (a,i,n) represents the sub-array $a[i\dots i+n-1]$,
so the elements of sli are $a[i], a[i+1], \dots, a[i+n-1]$, and n is
the length of the slice. Only valid slices can be constructed by
the functions below.

All operations are as for ArraySlice.slice.

Module CharVector

CharVector -- SML Basis Library

```
type vector = string
type elem = Char.char

val maxlen    : int
val fromList : elem list -> vector
val tabulate : int * (int -> elem) -> vector

val length   : vector -> int
val sub      : vector * int -> elem
val update   : vector * int * elem -> vector
val concat   : vector list -> vector

val find     : (elem -> bool) -> vector -> elem option
val exists   : (elem -> bool) -> vector -> bool
val all      : (elem -> bool) -> vector -> bool

val app      : (elem -> unit) -> vector -> unit
val map      : (elem -> elem) -> vector -> vector
val foldl   : (elem * 'b -> 'b) -> 'b -> vector -> 'b
val foldr   : (elem * 'b -> 'b) -> 'b -> vector -> 'b

val findi   : (int * elem -> bool) -> vector -> (int * elem) option
val appi   : (int * elem -> unit) -> vector -> unit
val mapi   : (int * elem -> elem) -> vector -> vector
val foldli : (int * elem * 'b -> 'b) -> 'b -> vector -> 'b
val foldri : (int * elem * 'b -> 'b) -> 'b -> vector -> 'b

val collate : (elem * elem -> order) -> vector * vector -> order
```

[vector] is the type of one-dimensional, immutable, zero-based constant-time-access vectors with elements of type Char.char, that is, characters. Type vector admits equality, and vectors v1 and v2 are equal if they have the same length and their elements are equal. The type vector is the same as String.string.

All operations are as for Vector.vector.

Module CharVectorSlice

CharVectorSlice -- SML Basis Library

```
type elem = Char.char
type vector = CharVector.vector

type slice = Substring.substring

val length    : slice -> int
val sub       : slice * int -> elem
val slice     : vector * int * int option -> slice
val full      : vector -> slice
val subslice  : slice * int * int option -> slice
val base      : slice -> vector * int * int
val vector    : slice -> vector
val concat    : slice list -> vector
val isEmpty   : slice -> bool
val getItem   : slice -> (elem * slice) option

val find      : (elem -> bool) -> slice -> elem option
val exists   : (elem -> bool) -> slice -> bool
val all       : (elem -> bool) -> slice -> bool

val app       : (elem -> unit) -> slice -> unit
val map       : (elem -> elem) -> slice -> vector
val foldl    : (elem * 'b -> 'b) -> 'b -> slice -> 'b
val foldr    : (elem * 'b -> 'b) -> 'b -> slice -> 'b

val findi    : (int * elem -> bool) -> slice -> (int * elem) option
val appi     : (int * elem -> unit) -> slice -> unit
val mapi     : (int * elem -> elem) -> slice -> vector
val foldli   : (int * elem * 'b -> 'b) -> 'b -> slice -> 'b
val foldri   : (int * elem * 'b -> 'b) -> 'b -> slice -> 'b

val collate  : (elem * elem -> order) -> slice * slice -> order
```

[slice] is the type of CharVector slices, that is, sub-vectors of CharVector.vector values. Since a CharVector.vector is a string, a slice is the same as a substring, and slices may be processed using the functions defined as well as those in structure Substring.

The slice (a,i,n) is valid if $0 \leq i \leq i+n \leq \text{size } s$,
or equivalently, $0 \leq i$ and $0 \leq n$ and $i+n \leq \text{size } s$.
A valid slice sli = (a,i,n) represents the sub-vector $a[i\dots i+n-1]$,
so the elements of sli are $a[i]$, $a[i+1]$, ..., $a[i+n-1]$, and n is
the length of the slice. Only valid slices can be constructed by
these functions.

All operations are as for VectorSlice.slice.

Module CommandLine

CommandLine -- SML Basis Library

```
val name      : unit -> string
val arguments : unit -> string list
```

[name ()] returns the name used to start the current process.

[arguments ()] returns the command line arguments of the current process.
Hence List.nth(arguments (), 0) is the first argument.

Module Date

Date -- SML Basis Library

```
datatype weekday = Mon | Tue | Wed | Thu | Fri | Sat | Sun
datatype month = Jan | Feb | Mar | Apr | May | Jun
                | Jul | Aug | Sep | Oct | Nov | Dec
type date
exception Date

val date : {
    year      : int,           e.g. 1999
    month     : month,         Jan, Feb, ...
    day       : int,           1-31
    hour      : int,           0-23
    minute    : int,           0-59
    second    : int,           0-61, permitting leap seconds
    offset   : Time.time option time zone west of UTC
} -> date

val year      : date -> int
val month     : date -> month
val day       : date -> int
val hour      : date -> int
val minute    : date -> int
val second    : date -> int
val weekDay  : date -> weekday
val yearDay  : date -> int
val isDst     : date -> bool option
val offset   : date -> Time.time option

val compare   : date * date -> order

val toString  : date -> string
val fmt        : string -> date -> string
val fromString: string -> date option
val scan      : (char, 'a) StringCvt.reader -> (date, 'a) StringCvt.reader

val fromTimeLocal : Time.time -> date
val fromTimeUniv  : Time.time -> date
val toTime       : date -> Time.time
val localOffset  : unit -> Time.time
```

These functions convert times to dates and vice versa, and format and scan dates.

[date] is the type of points in time in a given time zone. If the offset is NONE, then the date is in the local time zone. If the offset is SOME t, then t is the offset of the main timezone (ignoring daylight savings time) west of UTC.

When 0 hours \leq t < 12 hours, the represented time is to the west of UTC and the local time is UTC-t.

When 12 hours \leq t < 23 hours, the represented time is to the East of UTC and the local time is UTC+(24-t).

[date { year, month, day, hour, minute, second, offset }] returns a canonical date value. Seconds outside the range 0..59 are

converted to the equivalent minutes and added to the minutes argument; leap seconds are ignored. Similarly, excess minutes are converted to hours, hours to days, days to months, and months to years. Then the weekday and day number in the year are computed. Leap years are assumed in accordance with the Gregorian calendar, for any year after year 0 A.D.

If the offset is greater than one day (24 hours), then the excess days are added to the days, and the offset modulo 24 hours is used.

[year dt] returns the year of dt, e.g. 1999.

[month dt] returns the month of dt.

[day dt] returns the day of dt

[hour dt] returns the hour of dt.

[minute dt] returns the minute of dt.

[second dt] returns the second of dt.

[weekDay dt] returns the weekday of dt.

[yearDay dt] returns the number of the day in the year of dt. January 1 is day 0, and December 31 is day 364 (and 365 in leap years).

[isDst dt] returns SOME(true) if daylight savings time is in effect at the date dt; returns SOME(false) if not; and returns NONE if this information is unavailable.

[offset dt] returns NONE if the date dt is in the local time zone; returns SOME t where t is the offset west of UTC otherwise. Thus SOME(Time.zeroTime) is UTC.

[compare(dt1, dt2)] returns LESS, EQUAL, or GREATER, according as date dt1 precedes, equals, or follows dt2 in time. Lexicographically compares the dates. Ignores timezone offset and DST. Does not detect invalid dates.

[toString dt] returns a 24 character string representing the date dt in the following format:

Wed Mar 8 19:06:45 1995

The result may be wrong if the date is not representable as a Time.time value. Raises Date if dt is an invalid date. Corresponds to the ANSI C function 'asctime'.

[fmt fmtstr dt] formats the date dt according to the format string fmtstr. The format string has the same meaning as with the ANSI C function 'strftime'. These ANSI C format codes should work on all platforms:

%a	abbreviated weekday name (e.g. "Mon")
%A	full weekday name (e.g. "Monday")
%b	abbreviated month name (e.g. "Oct")
%B	full month name (e.g. "October")
%c	date and time (e.g. "Dec 2 06:55:15 1979")
%d	day of month (01..31)
%H	hour (00..23)
%I	hour (01..12)
%j	day of year (001..366)

%m	month number (01..12)
%M	minutes (00..59)
%p	locale's equivalent of a.m./p.m.
%S	seconds (00..61, allowing for leap seconds)
%U	week number (00..53), with Sunday as the first day of week 01
%w	day of week, with 0 representing Sunday (0..6)
%W	week number (00..53), with Monday as the first day of week 01
%x	locale's appropriate date representation
%y	year of century (00..99)
%Y	year including century (e.g. 1997)
%Z	time zone name if it exists; otherwise the empty string
%%	the percent character

Example: The current local date in ISO format (e.g. 1998-04-06) can be obtained by using:

```
fmt "%Y-%m-%d" (fromTimeLocal (Time.now ()))
```

[fromString s] scans a 24-character date from the string s, after possible initial whitespace (blanks, tabs, newlines). The format of the string must be as produced by `toString`. The fields `isDst` and `offset` in the resulting date will be `NONE`. No check of the consistency of the date (weekday, date in the month, ...) is performed.

[scan getc src] scans a 24-character date from the stream src, using the stream accessor `getc`. Otherwise works as `fromString`. In case of success, returns `SOME(date, rst)` where date is the scanned date and `rst` is the remainder of the stream; otherwise returns `NONE`.

[fromTimeLocal t] returns the local date at (UTC) time t. The resulting date will have `offset = NONE`. The fields `year`, `month`, `day`, `hour`, `minute`, and `second` are as expected. The resulting `isDst` may be `NONE` if the system cannot determine whether daylight savings time is in effect at the given time. Corresponds to the ANSI C function '`localtime`'.

[fromTimeUniv t] is similar to `fromTime`, but returns the UTC date at (UTC) time t. The resulting date will have `offset = SOME Time.zeroTime`. Corresponds to the ANSI C function '`gmtime`'.

[toTime dt] returns the (UTC) time corresponding to the date dt. Uses the `isDst` time field if it is present (`SOME _`) and cannot be calculated from the given date. May raise `Date` if the given date is invalid. Raises `Time.Time` if the Date cannot be represented as a `Time.time` value. At least the dates in the interval 1970-2030 can be represented as `Time.time` values. Corresponds to the ANSI C function '`mktimed`'.

[localOffset ()] is the local time zone offset west of UTC. It holds that $0 \text{ hours} \leq \text{localOffset} () < 24 \text{ hours}$.

Module Dynarray

Dynarray -- polymorphic dynamic arrays a la SML/NJ library

```
type 'a array

val array    : int * '_a -> '_a array
val subArray : '_a array * int * int -> '_a array
val fromList : '_a list * '_a -> '_a array
val tabulate : int * (int -> '_a) * '_a -> '_a array
val sub     : 'a array * int -> 'a
val update  : '_a array * int * '_a -> unit
val default : 'a array -> 'a
val bound   : 'a array -> int
```

[*'ty array*] is the type of one-dimensional, mutable, zero-based unbounded arrays with elements of type '*ty*. Type '*'ty array* does not admit equality.

[*array(n, d)*] returns a dynamic array, all of whose elements are initialized to the default *d*. The parameter *n* is used as a hint of the upper bound on non-default elements. Raises *Size* if *n < 0*.

[*subArray(a, m, n)*] returns a new array with the same default value as *a*, and whose values in the range [0, *n-m*] equal the values in *a* in the range [*m, n*]. Raises the exception *Size* if *n < m*.

[*fromList (xs, d)*] returns an array whose first elements are those of [*xs*], and the rest are the default *d*.

[*tabulate(n, f, d)*] returns a new array whose first *n* elements are *f 0, f 1, ..., f (n-1)*, created from left to right, and whose remaining elements are the default *d*. Raises *Size* if *n < 0*.

[*sub(a, i)*] returns the *i*'th element of *a*, counting from 0. Raises *Subscript* if *i < 0*.

[*update(a, i, x)*] destructively replaces the *i*'th element of *a* by *x*. Raises *Subscript* if *i < 0*.

[*default a*] returns the default value of the array *a*.

[*bound a*] returns an upper bound on the indices of non-default values.

Module Dynlib

Dynlib -- dynamic linking with foreign functions

```
type dlHandle
type symHandle

exception Closed

datatype flag = RTLD_LAZY | RTLD_NOW
val dlopen : { lib : string, flag : flag, global : bool } -> dlHandle
val dlsym : dlHandle -> string -> symHandle
val dlclose : dlHandle -> unit

val var : symHandle -> 'b
val appl : symHandle -> 'a1 -> 'b
val app2 : symHandle -> 'a1 -> 'a2 -> 'b
val app3 : symHandle -> 'a1 -> 'a2 -> 'a3 -> 'b
val app4 : symHandle -> 'a1 -> 'a2 -> 'a3 -> 'a4 -> 'b
val app5 : symHandle -> 'a1 -> 'a2 -> 'a3 -> 'a4 -> 'a5 -> 'b
```

Structure Dynlib provides dynamic loading and calling of C functions, using the dlfcn interface. A dynamic library is a collection of symbols (C variables and functions).

An ML value passed to or returned from a symbol has type 'value' as defined in src/runtime/mlvalues.h. The C functions should use the macros defined there to access and produce ML values. When writing a C function, remember that the garbage collector may be activated whenever you allocate an ML value. Also, remember that the garbage collector may move values from the young heap to the old one, so that a C pointer pointing into the ML heap may need to be updated. Use the Push_roots and Pop_roots macros to achieve this.

[dlHandle] is the type of dynamic library handles. A dynamic library handle is created by opening a dynamic library using dlopen. This will load the library into the runtime system. The dynamic library handle is used for accessing symbols in that library. The library may be closed and removed from the runtime system using dlclose.

The same library may be opened more than once, resulting in different library handles. The physical library will be loaded only once, though, and will remain in the runtime system until all handles to the library have been closed.

[symHandle] is the type of symbol handles. A symbol handle is used to access a symbol (variable or function) in the dynamic library, using the functions var, appl, app2, ..., app5. Type safety is the responsibility of the programmer; the runtime system performs no type checking. Hence you are advised to add explicit types whenever you define an ML function in terms of var, appl, ..., app5.

How to create a dynamically loadable library

Assume file "xyz.c" contains your C functions.

To compile xyz.c into xyz.o and then create a dynamic library libxyz.so from xyz.o:

```

Under Linux and OSF/1 (Digital Unix):
  gcc -c -o xyz.o xyz.c
  ld -shared -o libxyz.so xyz.o
Under Solaris (ignore the warnings from ld):
  gcc -c -o xyz.o xyz.c
  ld -G -B symbolic -z nodefs -o libxyz.so xyz.o
Under HP-UX:
  gcc -fPIC -c -o xyz.o xyz.c
  ld -b -B symbolic -E -o libxyz.so xyz.o

```

If "xyz.o" depends on another library "libabc.a" you may link the required functions into libxyz.so just by adding -labc or libabc.a to the above linker command.

If "xyz.o" depends on another dynamic library "libabc.so" you may specify this by adding -labc to the above linker command. Then Dynlib.dlopen will automatically load libabc.so before libxyz.so.

[dlopen { lib, flag, global }] will load and open the library in file 'lib', returning a handle to it. Libraries are usually specified just by file name, leaving out the directory path. Linux/Unix-specific information: Libraries are searched for in those directories mentioned in LD_LIBRARY_PATH, those mentioned in /etc/ld.so.cache, in /usr/lib and /lib. (Note that /etc/ld.so.cache is created from /etc/ld.so.conf by running ldconfig; you must be superuser to do that). If 'global' is true, then the library's global symbols are made available for other libraries subsequently loaded.

[flag] is the type of library loading modes: RTLD_LAZY and RTLD_NOW.

[RTLD_LAZY] specifies that only symbol relocations will be performed when calling dlopen, whereas function relocations will be performed later when a function is invoked for the first time (if ever). This is the normal situation.

[RTLD_NOW] specifies that all function relocations must be performed immediately, also for functions that will never be called. This checks that all functions are defined, but may waste some time.

[dlsym dlh nam] returns a symbol handle for the symbol called 'nam' in the library associated with dlh. Raises Closed if dlh has been closed.

[dlclose dlh] closes the library handle and deallocates the library if there are no more open handles to this library.

The following functions raise Closed if the associated handle has been closed.

[var sym] returns the value of the C variable associated with sym.

[app1 sym arg1] applies the C function associated with sym to arg1.

[app2 sym arg1 arg2] applies the C function associated with sym to (arg1, arg2).

[app3 sym arg1 arg2 arg3] applies the C function associated with

sym to (arg1, arg2, arg3).

[app4 sym arg1 arg2 arg3 arg4] applies the C function associated with sym to (arg1, arg2, arg3, arg4).

[app5 sym arg1 arg2 arg3 arg4 arg5] applies the C function associated with sym to (arg1, arg2, arg3, arg4, arg5).

Module FileSys

```
OS.FileSys -- SML Basis Library

type dirstream

val openDir    : string -> dirstream
val readDir   : dirstream -> string option
val rewindDir : dirstream -> unit
val closeDir  : dirstream -> unit

val chDir      : string -> unit
val getDir    : unit -> string
val mkdir     : string -> unit
val rmDir     : string -> unit
val isDir     : string -> bool

val realPath  : string -> string
val fullPath  : string -> string
val isLink    : string -> bool
val readLink  : string -> string

val modTime   : string -> Time.time
val setTime   : string * Time.time option -> unit
val remove    : string -> unit
val rename    : {old: string, new: string} -> unit

datatype access_mode = A_READ | A_WRITE | A_EXEC
val access    : string * access_mode list -> bool

val fileSize  : string -> int

val tmpName   : unit -> string

eqtype file_id
val fileId    : string -> file_id
val hash      : file_id -> word
val compare   : file_id * file_id -> order
```

These functions operate on the file system. They raise OS.SysErr in case of errors.

[openDir p] opens directory p and returns a directory stream for use by readDir, rewindDir, and closeDir. Subsequent calls to readDir will return the directory entries in some unspecified order.

[readDir dstr] returns SOME(s), consuming an entry s from the directory stream if it is non-empty; returns NONE if it is empty (when all directory entries have been read). Only entries distinct from the parent arc and the current arc (that is, .. and . in Unix, DOS, and Windows; see the Path structure) will be returned.

[rewindDir dstr] resets the directory stream as if it had just been opened.

[closeDir dstr] closes the directory stream. All subsequent operations on the stream will raise OS.SysErr.

[chDir p] changes the current working directory to p. This affects

calls to the functions use, load, compile in the interactive system, as well as all functions defined in this library. If p specifies a volume name, then this command also changes the current volume (relevant under DOS, Windows, OS/2, etc.).

[getDir ()] returns the name of the current working directory.

[mkDir p] creates directory p on the file system.

[rmDir p] removes directory p from the file system.

[isDir p] tests whether p is a directory.

[fullPath p] returns a canonical form of path p, where all occurrences of the arcs ".", "..", "" have been expanded or removed, and (under Unix) symbolic links have been fully expanded. Raises SysErr if a directory on the path, or the file or directory named, does not exist or is not accessible, or if there is a link loop.

[realPath p] behaves as fullPath(p) if p is absolute. If p is relative and on the same volume as the current working directory, it returns a canonical path relative to the current working directory, where superfluous occurrences of the arcs ".", "..", "" have been removed, and (under Unix) symbolic links have been fully expanded. Raises SysErr if a directory on the path, or the file or directory named, does not exist or is not accessible, or if there is a link loop. Raises Path if p is relative and on a different volume than the current working directory.

[isLink p] returns true if p names a symbolic link. Raises SysErr if the file does not exist or there is an access violation. On operating systems without symbolic links, it returns false, or raises SysErr if the file does not exist or there is an access violation.

[readLink p] returns the contents of the symbolic link p. Raises SysErr if p does not exist or is not a symbolic link, or there is an access violation. On operating systems without symbolic links, it raises SysErr.

[modTime p] returns the modification time of file p.

[setTime (p, tmopt)] sets the modification and access time of file p. If tmopt is SOME t, then the time t is used; otherwise the current time, that is, Time.now(), is used.

[remove p] deletes file p from the file system.

[rename {old, new}] changes the name of file 'old' to 'new'.

[access_mode] is the type of access permissions:

[A_READ] specifies read access.

[A_WRITE] specifies write access.

[A_EXEC] specifies permission to execute the file (or directory).

[access (p, accs)] tests the access permissions of file p, expanding symbolic links as necessary. If the list accs of

required access permission is empty, it tests whether p exists. If accs contains A_READ, A_WRITE, or A_EXEC, respectively, it tests whether the user process has read, write, or execute permission for the file.

Under Unix, the access test is done with the 'real' user id and group id (as opposed to the 'effective' user id and group id) of the user process. Hence access("file", [A_READ]) may return false, yet the file may be readable by the process, in case the effective user id or group id has been changed by setuid.

[fileSize p] return the size, in bytes, of the file p. Raises SysErr if p does not exist or its directory is not accessible.

[tmpName ()] returns a file name suitable for creating a fresh temporary file. Note that there is no guarantee that the file name will be unique, since a file of that name may be created between the call to tmpName and a subsequent call to openOut which creates the file. The file name will be absolute, usually of the form /tmp/xxxxxxxx provided by POSIX tmpnam (3).

[file_id] is the type of unique identities of file system objects (including device ids and volume ids, but possibly insensitive to volume changes on removable volumes, such as tapes and diskettes). The set of file ids is equipped with a total linear order.

[fileId p] returns the file_id of the file system object named by path p. It holds that fileId p1 = fileId p2 if and only if p1 and p2 name the same file system object.

[hash fid] returns a hashvalue for fid, suitable for use in a hashtable of file ids (and hence files).
If fid1 = fid2 then hash fid1 = hash fid2.

[compare (fid1, fid2)] returns LESS, EQUAL, or GREATER, according as fid1 precedes, equals, or follows fid2 in the total linear order on file ids. This is suitable for e.g. an ordered binary tree of file ids (and hence files).

Module Gdbm

```
Gdbm -- GNU gdbm persistent string hashtables -- requires Dynlib

type table

datatype openmode =
  READER
  | WRITER
  | WRCREAT
  | NEWDB
                                read-only access (nonexclusive)
                                read/write, table must exist
                                read/write, create if necessary
                                read/write, create empty table

type datum = string

exception NotFound
exception AlreadyThere
exception NotWriter
exception Closed
exception GdbmError of string

val withtable : string * openmode -> (table -> 'a) -> 'a
val withtables : (string * openmode) list -> (table list -> 'a) -> 'a
val add      : table -> datum * datum -> unit
val insert   : table -> datum * datum -> unit
val find     : table -> datum -> datum
val peek     : table -> datum -> datum option
val hasKey   : table -> datum -> bool
val remove   : table -> datum -> unit
val listKeys : table -> datum list
val numItems : table -> int
val listItems: table -> (datum * datum) list
val app      : (datum * datum -> unit) -> table -> unit
val map      : (datum * datum -> 'a) -> table -> 'a list
val fold     : (datum * datum * 'a -> 'a) -> 'a -> table -> 'a
val fastwrite: bool ref
val reorganize: table -> unit
```

[table] is the type of an opened table. A value of type table can be used only in the argument f to the withtable function. This makes sure that the table is closed after use.

[openmode] is the type of opening modes. Read-only access (READER) is non-exclusive; read/write access (WRITER, WRCREAT, NEWDB) is exclusive.

[withtable (nam, mod) f] first opens the table db in file nam with mode mod, then applies f to db, then closes db. Makes sure to close db even if an exception is raised during the evaluation of f(db). Raises GdbmError with an informative message in case the table cannot be opened. E.g. the table cannot be opened for reading if already opened for writing, and cannot be opened for writing if already opened for reading.

A table is only guaranteed to work properly if created by withtable using open modes WRCREAT or NEWDB. If you create a table by creating and then opening an empty file, then numItems, listKeys, listItems, etc. will raise an exception.

[withtables nammod f], where nammod = [(nam1, mod1), ..., (namn, modn)], is equivalent to

```
withtable (nam1, mod1) (fn db1 =>
  withtable (nam2, mod2) (fn db2 =>
    ...
      f [db1, db2, ...]))
```

That is, first opens the databases db1, db2, ... in that order in files nam1, nam2, ... with modes mod1, mod2, ..., then applies f to [db1, db2, ...], and finally closes [db1, db2, ...]. Makes sure to close all databases even if an exception is raised during the opening of db1, db2, ... or during the evaluation of f[db1, db2, ...].

[add db (k,v)] adds the pair (k, v) to db. Raises AlreadyThere if there is a pair (k, _) in db already. Raises NotWriter if db is not opened in write mode.

[insert db (k, v)] adds the pair (k, v) to db, replacing any pair (k, _) at k if present. Raises NotWriter if db is not opened in write mode.

[find db k] returns v if the pair (k, v) is in db; otherwise raises NotFound.

[peek db k] returns SOME v if the pair (k, v) is in db; otherwise returns NONE.

[hasKey db k] returns true if there is a pair (k, _) in db; otherwise returns false.

[remove db k] deletes the pair (k, _) from the table if present; otherwise raises NotFound. Raises NotWriter if db is not opened in write mode.

[listKeys db] returns a list of all keys in db in an unspecified order.

[numItems db] is the number of (key, value) pairs in db. Equivalent to length(listKeys db).

[listItems db] returns a list of all (key, value) pairs in db in some order. Equivalent to

$$\text{List.map } (\text{fn key } \Rightarrow \text{(key, find(db, key))}) \text{ (listKeys db)}$$

[app f db] is equivalent to List.app f (listItems db), provided the function f does not change the set of keys in the table. Otherwise the effect is unpredictable.

[map f db] is equivalent to List.map f (listItems db), provided the function f does not change the set of keys in the table. Otherwise the result and effect are unpredictable.

[fold f a db] is equivalent to

$$\text{List.foldr } (\text{fn } ((\text{k}, \text{v}), \text{r}) \Rightarrow \text{f(k, v, r)}) \text{ a (listItems db)}$$

 provided the function f does not change the set of keys in the table. Otherwise the result and effect are unpredictable.

[fastwrite] can be set to speed up writes to a table. By default, !fastwrite is false and every write to a table will be followed by file system synchronization. This is safe, but slow if you perform thousands of writes. However, if !fastwrite is true when calling withtable, then writes may not be followed by synchronization, which may speed up writes considerably. In any case, the file system is synchronized before withtable returns.

[reorganize db] has no visible effect, but may be called after a lot of deletions to shrink the size of the table file.

Module Gdimage

```
Gdimage -- creating PNG images -- requires Dynlib

type image

type color

datatype style =
  ColorS of color
 | TransparentS

datatype mode =
  Color of color
 | Transparent
 | Brushed of image
 | Styled of style vector
 | StyledBrushed of bool vector * image
 | Tiled of image

datatype font =
  Tiny
 | Small
 | MediumBold
 | Large
 | Giant

type rgb = int * int * int           RGB color components, 0..255
type xy  = int * int                 points (x, y) and sizes (w, h)

val image      : xy -> rgb -> image
val fromPng   : string -> image
val toPng     : image -> string -> unit
val stdoutPng : image -> unit
val size       : image -> xy

val color      : image -> rgb -> color
val rgb        : image -> color -> rgb
val htmlcolors : image -> { aqua : color, black : color, blue : color,
                            fuchsia : color, gray : color,
                            green : color, lime : color, maroon : color,
                            navy : color, olive : color, purple : color,
                            red : color, silver : color, teal : color,
                            white : color, yellow : color }

val getTransparent : image -> color option
val setTransparent : image -> color -> unit
val noTransparent : image -> unit

val drawPixel   : image -> mode -> xy -> unit
val drawLine    : image -> mode -> xy * xy -> unit
val drawRect    : image -> mode -> xy * xy -> unit
val fillRect    : image -> mode -> xy * xy -> unit
val drawPolygon : image -> mode -> xy vector -> unit
val fillPolygon : image -> mode -> xy vector -> unit
val drawArc     : image -> mode -> { c : xy, wh : xy, from : int, to : int } -> unit
val fill        : image -> mode -> xy -> unit
val fillBorder  : image -> mode -> xy -> color -> unit

val copy        : { src : image, srcxy : xy, srcwh : xy,
```

```

        dst : image, dstxy : xy } -> unit
val copyResize  : { src : image, srcxy : xy, srcwh : xy,
                     dst : image, dstxy : xy, dstwh : xy } -> unit

val char       : image -> color -> font -> xy -> char -> unit
val charUp     : image -> color -> font -> xy -> char -> unit
val string     : image -> color -> font -> xy -> string -> unit
val stringUp   : image -> color -> font -> xy -> string -> unit
val charsize   : font -> xy

```

This is an interface to version 1.7.3 of Thomas Boutell's gd image package for creating PNG images.

[image] is the type of images being drawn. They can be created from scratch, imported from PNG files, and exported to PNG files.

All functions correctly clip to the actual size of the image.

[color] is the type of colors. Currently there can be at most 256 different colors in an image.

[style] is the type of drawing styles. A style is either a color, or transparent.

[mode] is the type of drawing modes for line drawing and filling.
It may be one of

Color c	where c is a color
Transparent	
Brushed img	for line drawing using the given image as brush
Styled stys	for line drawing, cyclically using the styles in the given vector to create a dashed line
StyledBrushed (vis, img)	for line drawing, using the given image as a brush, cyclically switching it on and off according to the given bool vector
Tiled img	for filling, using the given image as a tile

[font] is the type of fonts: Tiny, Small, MediumBold, Large, Giant

[rgb] is the type of (r, g, b) triples, where the components indicate color intensity as an integer value in the range 0..255.

[xy] is the type of pairs, used for (x, y) coordinates and to indicate dimensions (width, height). The origin (0, 0) is the upper left-hand corner of the image. The x coordinates increase to the right; the y coordinates increase downwards.

[image (w, h) rgb] creates a new empty image with size (w, h) and the background color rgb. Raises Fail if the image cannot be created.

[fromPng filename] reads an image from the given PNG file. Raises Fail if the file does not exist or does not contain a PNG image.

[size img] returns (w, h) where w is the width and h the height of img.

[toPng img filename] write the image to the given file in PNG format.

[stdoutPng img] writes the image to standard output in PNG format, preceded by the HTTP header "Content-type: image/png\n\n". Useful in CGI scripts.

[color img rgb] returns the color code corresponding to rgb in the color table of img. Reuses the color code if it has already been allocated; otherwise allocates the color if possible; otherwise returns an approximation to the color rgb.

[htmlcolors im] returns a record containing the 16 standard HTML colors: aqua, black, blue, fuchsia, gray, green, lime, maroon, navy, olive, purple, red, silver, teal, white, yellow. This call will allocate all these colors in the color table of the image, even if you do not use all of them.

[rgb img color] returns (r, g, b) where r, g, b are the component intensities of the given color in the color table of img.

[getTransparent img] returns SOME c where c is the 'transparent' color of the image, if any; otherwise returns NONE.

[setTransparent img col] makes the given color transparent in the image.

[noTransparent img] makes all colors non-transparent in the image. This is useful for images that are to be used as tiles for filling. Such images are not allowed to have a transparent color.

[drawPixel img mode xy] draws the pixel in img at xy using the given mode.

[drawLine img mode (xy1, xy2)] draws a line in img from xy1 to xy2 using the given mode.

[drawRect img mode (xy1, xy2)] draws a rectangle in img with opposing corners xy1 and xy2 using the given mode.

[fillRect img mode (xy1, xy2)] draws a filled rectangle in img with opposing corners xy1 and xy2 using the given mode.

[drawPolygon img mode xys] draws a polygon in img with corners as given by the vector xys of coordinates using the given mode.

[fillPolygon img mode xys] draws a filled polygon in img with corners as given by the vector xys of coordinates using the given mode.

[drawArc img mode { c, wh, from, to }] draw part of an ellipsis arc in img, with center c, width and height wh, using the given 'from' and 'to' angles, given in degrees (0..360).

[fill img mode xy] fills the region in img around xy which has the same color as the point at img, using the given mode.

[fillBorder img mode xy col] fills the region in img around xy which is delimited by the color col, using the given mode.

[copy { src, srcxy, srcwh, dst, dstxy }] copies part of the image src into the image dst, without rescaling. More precisely, copies the subimage of src whose upper left-hand corner is srcxy and whose size is srcwh, into the subimage of dst whose upper left-hand

corner is dstxy. The images src and dst may be the same, but if the subimages overlap, then the result is unpredictable.

[copyResize { src, srcxy, srcwh, dst, dstxy, dstwh }] copies part of the image src into the image dst, rescaling to the given size dstwh of the destination subimage. Otherwise works as copy.

[char img col font xy ch] draws the character ch left-right (to be read from south) in img at xy using the given color.

[charUp img col font xy ch] draws the character ch bottom-up (to be read from east) in img at xy using the given color.

[string img col font xy s] draws the string s left-right (to be read from south) in img at xy using the given color.

[stringUp img col font xy s] draws the string s bottom-up (to be read from east) in img at xy using the given color.

[charsize font] returns (w, h) where w is the width and h the height, in pixels, of each character in the given font.

Module General

SML Basis Library and Moscow ML top-level declarations

SML Basis Library types

```
type      exn
eqtype    unit
datatype order = LESS | EQUAL | GREATER
```

Additional Moscow ML top-level types

```
datatype bool = false | true
eqtype char
eqtype int
datatype 'a option = NONE | SOME of 'a
type ppstream
eqtype real
eqtype string
type substring
type syserror
type 'a vector
eqtype word
eqtype word8
datatype 'a list = nil | op :: of 'a * 'a list
datatype 'a ref = ref of 'a
datatype 'a frag = QUOTE of string | ANTIQUOTE of 'a
```

SML Basis Library exceptions

```
exception Bind
exception Chr
exception Div
exception Domain
exception Fail of string
exception Match
exception Overflow
exception Option
exception Subscript
exception Size
exception Span
```

Additional Moscow ML top-level exceptions

```
exception Graphic of string
exception Interrupt
exception Invalid_argument of string
exception Io of {function : string, name : string, cause : exn }
exception Out_of_memory
exception SysErr of string * syserror option
```

SML Basis Library values

```
val !         : 'a ref -> 'a
val :=        : 'a ref * 'a -> unit

val o         : ('b -> 'c) * ('a -> 'b) -> ('a -> 'c)
val ignore    : 'a -> unit
val before    : 'a * unit -> 'a

val exnName   : exn -> string
```

```
val exnMessage : exn -> string
```

Additional Moscow ML top-level values

```
val not    : bool -> bool
```

```
val ^     : string * string -> string
```

```
val =    : "a * "a -> bool
val <>   : "a * "a -> bool
```

```
val ceil   : real -> int
```

round towards plus infinity

```
val floor  : real -> int
```

round towards minus infinity

```
val real   : int -> real
```

equals Real.fromInt

```
val round  : real -> int
```

round to nearest even

```
val trunc  : real -> int
```

round towards zero

```
val vector : 'a list -> 'a vector
```

Below, numtxt is int, Word.word, Word8.word, real, char, string:

```
val <   : numtxt * numtxt -> bool
```

```
val <=  : numtxt * numtxt -> bool
```

```
val >   : numtxt * numtxt -> bool
```

```
val >=  : numtxt * numtxt -> bool
```

```
val makestring : numtxt -> string
```

Below, realint is int or real:

```
val ~   : realint -> realint           raises Overflow
```

```
val abs : realint -> realint           raises Overflow
```

Below, num is int, Word.word, Word8.word, or real:

```
val +   : num * num -> num           raises Overflow
```

```
val -   : num * num -> num           raises Overflow
```

```
val *   : num * num -> num           raises Overflow
```

```
val /   : real * real -> real         raises Div, Overflow
```

Below, wordint is int, Word.word or Word8.word:

```
val div : wordint * wordint -> wordint raises Div, Overflow
```

```
val mod : wordint * wordint -> wordint raises Div
```

[exn] is the type of exceptions.

[unit] is the type containing the empty tuple () which equals the empty record {}.

[order] is used as the return type of comparison functions.

[bool] is the type of booleans: false and true. Equals Bool.bool.

[char] is the type of characters such as #"*A*". Equals Char.char.

[int] is the type of integers. Equals Int.int.

[option] is the type of optional values. Equals Option.option.

[ppstream] is the type of pretty-printing streams, see structure PP.

Pretty-printers may be installed in the top-level by function `Meta.installPP`; see the Moscow ML Owner's Manual.

`[real]` is the type of floating-point numbers. Equals `Real.real`.

`[string]` is the type of character strings. Equals `String.string`.

`[substring]` is the type of substrings. Equals `Substring.substring`.

`[syserror]` is the abstract type of system error codes. Equals `OS.syserror`.

`[vector]` is the type of immutable vectors. Equals `Vector.vector`.

`[word]` is the type of unsigned words. Equals `Word.word`.

`[word8]` is the type of unsigned bytes. Equals `Word8.word`.

`['a list]` is the type of lists of elements of type `'a`. Equals `List.list`.

`['a ref]` is the type of mutable references to values of type `'a`.

`['a frag]` is the type of quotation fragments, resulting from the parsing of quotations '`...`' and antiquotations. See the Moscow ML Owner's Manual.

`[Bind]` is the exception raised when the right-hand side value in a valbind does not match the left-hand side pattern.

`[Chr]` signals an attempt to produce an unrepresentable character.

`[Div]` signals an attempt to divide by zero.

`[Domain]` signals an attempt to apply a function outside its domain of definition; such as computing `Math.sqrt(~1)`.

`[Fail]` signals the failure of some function, usually in the Moscow ML specific library structures.

`[Match]` signals the failure to match a value against the patterns in a case, handle, or function application.

`[Option]` is raised by `Option.valOf` when applied to `NONE`.

`[Overflow]` signals the attempt to compute an unrepresentable number.

`[Subscript]` signals the attempt to use an illegal index in an array, dynarray, list, string, substring, vector or weak array.

`[Size]` signals the attempt to create an array, string or vector that is too large for the implementation.

`[Graphic]` signals the failure of Graphics primitives (DOS only).

`[Interrupt]` signals user interrupt of the computation.

`[Invalid_argument]` signals the failure of a function in the runtime system.

`[Io { function, name, cause }]` signals the failure of an

input/output operation (function) when operating on a file (name). The third field (cause) may give a reason for the failure.

[Out_of_memory] signals an attempt to create a data structure too large for the implementation, or the failure to extend the heap or stack.

[SysErr (msg, err)] signals a system error, described by msg. A system error code may be given by err. If so, it will usually hold that msg = OS.errorMsg err.

SML Basis Library values

[! rf] returns the value pointed to by reference rf.

[:= (rf, e)] evaluates rf and e, then makes the reference rf point to the value of e. Since := has infix status, this is usually written
rf := e

[o(f, g)] computes the functional composition of f and g, that is,
fn x => f(g x). Since o has infix status, this is usually written
f o g

[ignore e] evaluates e, discards its value, and returns () : unit.

[before(e1, e2)] evaluates e1, then evaluates e2, then returns the value of e1. Since before has infix status, this is usually written
e1 before e2

[exnName exn] returns a name for the exception constructor in exn. Never raises an exception itself. The name returned may be that of any exception constructor aliasing with exn. For instance,
let exception E1; exception E2 = E1 in exnName E2 end
may evaluate to "E1" or "E2".

[exnMessage exn] formats and returns a message corresponding to exception exn. For the exceptions defined in the SML Basis Library, the message will include the argument carried by the exception.

Additional Moscow ML top-level values

[not b] returns the logical negation of b.

[^] is the string concatenation operator.

[=] is the polymorphic equality predicate.

[<>] is the polymorphic inequality predicate.

[ceil r] is the smallest integer >= r (rounds towards plus infinity). May raise Overflow.

[floor r] is the largest integer <= r (rounds towards minus infinity). May raise Overflow.

[real i] is the floating-point number representing integer i.
Equivalent to Real.fromInt.

[round r] is the integer nearest to r, using the default rounding

mode. May raise Overflow.

[trunc r] is the numerically largest integer between r and zero (rounds towards zero). May raise Overflow.

[vector [x1, ..., xn]] returns the vector #[x1, ..., xn].

```
[< (x1, x2)]
[<=(x1, x2)]
[> (x1, x2)]
[>=(x1, x2)]
```

These are the standard comparison operators for arguments of type int, Word.word, Word8.word, real, char or string.

[makestring v] returns a representation of value v as a string, for v of type int, Word.word, Word8.word, real, char or string.

[~ x] is the numeric negation of x (which can be real or int). May raise Overflow.

[abs x] is the absolute value of x (which can be real or int). May raise Overflow.

```
[+ (e1, e2)]
[- (e1, e2)]
[* (e1, e2)]
```

These are the standard arithmetic operations for arguments of type int, Word.word, Word8.word, and real. They are unsigned in the case of Word.word and Word8.word. May raise Overflow.

[/ (e1, e2)] is the floating-point result of dividing e1 by e2. May raise Div and Overflow.

[div(e1, e2)] is the integral quotient of dividing e1 by e2 for arguments of type int, Word.word, and Word8.word. See Int.div and Word.div for more details. May raise Div, Overflow.

[mod(e1, e2)] is the remainder when dividing e1 by e2, for arguments of type int, Word.word, and Word8.word. See Int.mod and Word.mod for more details. May raise Div.

Module Hashset

Hashset -- sets implemented by hashtables

```
signature Hashset = sig
type 'item set

exception NotFound

val empty      : ('_item -> word) * ('_item * '_item -> bool) -> '_item set
val singleton   : ('_item -> word) * ('_item * '_item -> bool) -> '_item
                  -> '_item set

val member      : '_item set * '_item -> bool
val retrieve    : '_item set * '_item -> '_item
val peek        : '_item set * '_item -> '_item option

val add          : '_item set * '_item -> unit
val addList     : '_item set * '_item list -> unit
val delete      : '_item set * '_item -> unit

val isEmpty     : '_item set -> bool
val isSubset    : '_item set * '_item set -> bool
val equal       : '_item set * '_item set -> bool
val numItems    : '_item set -> int
val listItems   : '_item set -> '_item list

val app          : ('_item -> unit) -> '_item set -> unit
val fold         : ('_item * 'b -> 'b) -> 'b -> '_item set -> 'b
val all          : ('_item -> bool) -> '_item set -> bool
val exists      : ('_item -> bool) -> '_item set -> bool
val find         : ('_item -> bool) -> '_item set -> '_item option
val copy         : '_item set -> '_item set

val hash         : '_item set -> word
val polyHash    : 'a -> word

end
```

[`item set] is the type of sets of elements of type `item, with a given hash function and equality predicate.

[empty (hash, equal)] creates a new empty set with the given hash function and equality predicate. It must hold that equal(x, y) implies hash x = hash y.

[singleton (hash, equal) i] creates the singleton set containing i, with the given hash function and equality predicate.

[member(s, i)] returns true if and only if i is in s.

[retrieve(s, i)] returns i if it is in s; raises NotFound otherwise.

[peek(s, i)] returns SOME i if i is in s; returns NONE otherwise.

[add(s, i)] adds item i to set s.

[addList(s, xs)] adds all items from the list xs to the set s.

[delete(s, i)] removes item i from s. Raises NotFound if i is not in s.

[isEmpty s] returns true if the set is empty; false otherwise.

[equal(s1, s2)] returns true if and only if the two sets have the same elements.

[isSubset(s1, s2)] returns true if and only if s1 is a subset of s2.

[numItems s] returns the number of items in set s.

[listItems s] returns a list of the items in set s, in some order.

[app f s] applies function f to the elements of s, in some order.

[fold f e s] applies the folding function f to the entries of the set in some order.

[find p s] returns SOME i, where i is an item in s which satisfies p, if one exists; otherwise returns NONE.

[hash s] returns the hashcode of the set, which is the sum of the hashcodes of its elements, as computed by the hash function given when the set was created.

[polyHash v] returns a system-defined hashcode for the value v. This pseudo-polymorphic hash function can be used together with the standard equality function (=) to create a HashSet for any type that admits equality, as follows:

```
val set = HashSet.empty (HashSet.hash, op =);
```

Module Help

Help -- on-line help functions

```
val help          : string -> unit
val displayLines : int ref
val helpdirs     : string list ref
val indexfiles   : string list ref
val specialfiles : {term : string, file : string, title : string} list ref
val welcome      : string vector ref
val browser       : (string -> unit) ref
val defaultBrowser: string -> unit
```

[help s] provides on-line help on the topic indicated by string s.

help "lib"; gives an overview of the Moscow ML library.
 help "id"; provides help on identifier id (case-insensitive).

If exactly one identifier in the library matches id (case-insensitive), then the browser opens the signature defining that identifier, positioning the first occurrence of id at the center of the screen.

If more than one identifier matches id (case-insensitive), then a small menu lists the signatures containing the identifier. To invoke the browser, just type in the number of the desired signature.

The browser accepts the following commands, which must be followed by a newline:

```
d      move down by half a screen
u      move up by half a screen
t      move to top of file
b      move to bottom of file
/str   cyclically search for string str in help file (case-insensitive)
n      search for next occurrence of str
q      quit the browser
```

A newline by itself moves down one screen (24 lines).

[helpdirs] is a reference to a list of additional directories to be searched for help files. The directories are searched in order, after the -stdlib directory.

[indexfiles] is a reference to a list of full paths of help term index files. Setting 'indexfiles' affects subsequent invocations of 'help'. (Every invocation of 'help' reads the index files anew).

[specialfiles] is a reference to a list of {term, file, title} records, each of which maps a search term to the specified file with the specified title (in the browser). The string in the 'term' field should be all lowercase, since the argument passed to 'help' will be converted to lowercase.

[welcome] is a reference to the text shown in response to the query help "". This is a vector of lines of text.

[browser] is a reference to the function that gets invoked on the text of the help file. Initially set to defaultBrowser.

[defaultBrowser] is the default (built-in) help browser.

[displayLines] is a reference to the size of the display (window) assumed by the defaultBrowser; initially 24 lines. Set it to the actual size of your window for best results.

Module Int

Int -- SML Basis Library

```
type int = int

val precision : int option
val minInt    : int option
val maxInt    : int option

val ~      : int -> int          Overflow
val *      : int * int -> int     Overflow
val div    : int * int -> int     Div, Overflow
val mod    : int * int -> int     Div
val quot   : int * int -> int     Div, Overflow
val rem    : int * int -> int     Div
val +      : int * int -> int     Overflow
val -      : int * int -> int     Overflow
val >      : int * int -> bool
val >=    : int * int -> bool
val <      : int * int -> bool
val <=    : int * int -> bool
val abs    : int -> int          Overflow
val min   : int * int -> int
val max   : int * int -> int

val sign   : int -> int
val sameSign : int * int -> bool
val compare : int * int -> order

val toInt   : int -> int
val fromInt : int -> int
val toLarge  : int -> int
val fromLarge : int -> int

val scan    : StringCvt.radix
             -> (char, 'a) StringCvt.reader -> (int, 'a) StringCvt.reader
val fmt     : StringCvt.radix -> int -> string

val toString : int -> string
val fromString : string -> int option  Overflow
```

[precision] is SOME n, where n is the number of significant bits in an integer. In Moscow ML n is 31 in 32-bit architectures and 63 in 64-bit architectures.

[minInt] is SOME n, where n is the most negative integer.

[maxInt] is SOME n, where n is the most positive integer.

[~]
[*]
[+]

[-] are the usual operations on integers. They raise Overflow if the result is not representable as an integer.

[abs] returns the absolute value of its argument. Raises Overflow if applied to the most negative integer.

[div] is integer division, rounding towards minus infinity.

Evaluating `i div 0` raises `Div`. Evaluating `i div ~1` raises `Overflow` if `i` is the most negative integer.

`[mod]` is the remainder for `div`. If $q = i \text{ div } d$ and $r = i \text{ mod } d$ then it holds that $qd + r = i$, where either $0 \leq r < d$ or $d < r \leq 0$. Evaluating `i mod 0` raises `Div`, whereas `i mod ~1 = 0`, for all `i`.

`[quot]` is integer division, rounding towards zero. Evaluating `quot(i, 0)` raises `Div`. Evaluating `quot(i, ~1)` raises `Overflow` if `i` is the most negative integer.

`[rem(i, d)]` is the remainder for `quot`. That is, if $q = \text{quot}(i, d)$ and $r = \text{rem}(i, d)$ then $d * q + r = i$, where `r` is zero or has the same sign as `i`. If made infix, the recommended fixity for `quot` and `rem` is

infix 7 quot rem

`[min(x, y)]` is the smaller of `x` and `y`.

`[max(x, y)]` is the larger of `x` and `y`.

`[sign x]` is `~1`, `0`, or `1`, according as `x` is negative, zero, or positive.

`[<]`
`[<=]`
`[>]`
`[>=]`

`[>=]` are the usual comparisons on integers.

`[compare(x, y)]` returns `LESS`, `EQUAL`, or `GREATER`, according as `x` is less than, equal to, or greater than `y`.

`[sameSign(x, y)]` is true iff `sign x = sign y`.

`[toInt x]` is `x` (because this is the default int type in Moscow ML).

`[fromInt x]` is `x` (because this is the default int type in Moscow ML).

`[toLarge x]` is `x` (because this is the largest int type in Moscow ML).

`[fromLarge x]` is `x` (because this is the largest int type in Moscow ML).

`[fmt radix i]` returns a string representing `i`, in the radix (base) specified by `radix`.

radix	description	output format
BIN	signed binary	(base 2) ~?[01]+
OCT	signed octal	(base 8) ~?[0-7]+
DEC	signed decimal	(base 10) ~?[0-9]+
HEX	signed hexadecimal	(base 16) ~?[0-9A-F]+

`[toString i]` returns a string representing `i` in signed decimal format. Equivalent to `(fmt DEC i)`.

`[fromString s]` returns `SOME(i)` if a decimal integer numeral can be scanned from a prefix of string `s`, ignoring any initial whitespace; returns `NONE` otherwise. A decimal integer numeral must have form, after possible initial whitespace:

`[+~-]?[0-9]+`

`[scan radix getc chars]` attempts to scan an integer numeral

from the character source `charsrc`, using the accessor `getc`, and ignoring any initial whitespace. The radix argument specifies the base of the numeral (BIN, OCT, DEC, HEX). If successful, it returns `SOME(i, rest)` where `i` is the value of the number scanned, and `rest` is the unused part of the character source. A numeral must have form, after possible initial whitespace:

radix	input format
BIN	[+~-]?[0-1]+
OCT	[+~-]?[0-7]+
DEC	[+~-]?[0-9]+
HEX	[+~-]?[0-9a-fA-F]+

Module IntInf

*LargeInt -- arbitrary-precision integers 1995-09-04, 1998-04-12
 This module requires Dynlib and the GNU GMP package to be installed*

```

type int

val precision : int option
val minInt    : int option
val maxInt    : int option

val ~     : int -> int
val +     : int * int -> int
val -     : int * int -> int
val *     : int * int -> int
val div   : int * int -> int
val mod   : int * int -> int
val quot  : int * int -> int
val rem   : int * int -> int
val <    : int * int -> bool
val >    : int * int -> bool
val <=   : int * int -> bool
val >=   : int * int -> bool
val eq    : int * int -> bool
val ne    : int * int -> bool
val abs   : int -> int
val min   : int * int -> int
val max   : int * int -> int

val divMod  : int * int -> int * int
val quotRem : int * int -> int * int
val pow     : int * Int.int -> int
val log2    : int -> Int.int

val sign    : int -> Int.int
val sameSign: int * int -> bool
val compare : int * int -> order

val fromInt  : Int.int -> int
val toInt    : int -> Int.int Overflow
val toLarge  : int -> int
val fromLarge: int -> int

val fromString : string -> int option
val toString   : int -> string

val scan : StringCvt.radix
          -> (char, 'a) StringCvt.reader -> (int, 'a) StringCvt.reader
val fmt   : StringCvt.radix -> int -> string

```

Module Intmap

*Intmap -- Applicative maps with integer keys
 From SML/NJ lib 0.2, copyright 1993 by AT&T Bell Laboratories
 Original implementation due to Stephen Adams, Southampton, UK*

```
type 'a intmap

exception NotFound

val empty      : unit -> 'a intmap
val insert     : 'a intmap * int * 'a -> 'a intmap
val retrieve   : 'a intmap * int -> 'a
val peek       : 'a intmap * int -> 'a option
val remove     : 'a intmap * int -> 'a intmap * 'a
val numItems   : 'a intmap -> int
val listItems  : 'a intmap -> (int * 'a) list
val app        : (int * 'a -> unit) -> 'a intmap -> unit
val revapp    : (int * 'a -> unit) -> 'a intmap -> unit
val foldr      : (int * 'a * 'b -> 'b) -> 'b -> 'a intmap -> 'b
val foldl      : (int * 'a * 'b -> 'b) -> 'b -> 'a intmap -> 'b
val map        : (int * 'a -> 'b) -> 'a intmap -> 'b intmap
val transform  : ('a -> 'b) -> 'a intmap -> 'b intmap
```

[*'a intmap*] is the type of applicative maps from int to '*a*.

[empty] creates a new empty map.

[insert(*m*, *i*, *v*)] extends (or modifies) map *m* to map *i* to *v*.

[retrieve(*m*, *i*)] returns *v* if *m* maps *i* to *v*; otherwise raises NotFound.

[peek(*m*, *i*)] returns SOME *v* if *m* maps *i* to *v*; otherwise NONE.

[remove(*m*, *i*)] removes *i* from the domain of *m* and returns the modified map and the element *v* corresponding to *i*. Raises NotFound if *i* is not in the domain of *m*.

[numItems *m*] returns the number of entries in *m* (that is, the size of the domain of *m*).

[listItems *m*] returns a list of the entries (*i*, *v*) of integers *i* and the corresponding values *v* in *m*, in increasing order of *i*.

[app *f* *m*] applies function *f* to the entries (*i*, *v*) in *m*, in increasing order of *i*.

[revapp *f* *m*] applies function *f* to the entries (*i*, *v*) in *m*, in decreasing order of *i*.

[foldl *f* *e* *m*] applies the folding function *f* to the entries (*i*, *v*) in *m*, in increasing order of *i*.

[foldr *f* *e* *m*] applies the folding function *f* to the entries (*i*, *v*) in *m*, in decreasing order of *i*.

[map *f* *m*] returns a new map whose entries have form (*i*, *f(i,v)*), where (*i*, *v*) is an entry in *m*.

[transform f m] returns a new map whose entries have form (i, f(i,v)), where (i, v) is an entry in m.

Module Intset

*Intset -- applicative sets of integers
 From SML/NJ lib 0.2, copyright 1993 by AT&T Bell Laboratories
 Original implementation due to Stephen Adams, Southampton, UK*

```
type intset

exception NotFound

val empty      : intset
val singleton   : int -> intset
val add         : intset * int -> intset
val addList     : intset * int list -> intset
val isEmpty     : intset -> bool
val equal       : intset * intset -> bool
val isSubset    : intset * intset -> bool
val member      : intset * int -> bool
val delete      : intset * int -> intset
val numItems    : intset -> int
val union       : intset * intset -> intset
val intersection: intset * intset -> intset
val difference  : intset * intset -> intset
val listItems   : intset -> int list
val app         : (int -> unit) -> intset -> unit
val revapp     : (int -> unit) -> intset -> unit
val foldr       : (int * 'b -> 'b) -> 'b -> intset -> 'b
val foldl       : (int * 'b -> 'b) -> 'b -> intset -> 'b
val find        : (int -> bool) -> intset -> int option
```

[intset] is the type of sets of integers.

[empty] is the empty set of integers.

[singleton i] is the singleton set containing i.

[add(s, i)] adds item i to set s.

[addList(s, xs)] adds all items from the list xs to the set s.

[isEmpty s] returns true if and only if the set is empty.

[equal(s1, s2)] returns true if and only if the two sets have the same elements.

[isSubset(s1, s2)] returns true if and only if s1 is a subset of s2.

[member(s, i)] returns true if and only if i is in s.

[delete(s, i)] removes item i from s. Raises NotFound if i is not in s.

[numItems s] returns the number of items in set s.

[union(s1, s2)] returns the union of s1 and s2.

[intersection(s1, s2)] returns the intersectionof s1 and s2.

[difference(s1, s2)] returns the difference between s1 and s2 (that is, the set of elements in s1 but not in s2).

[listItems s] returns a list of the items in set s, in increasing order.

[app f s] applies function f to the elements of s, in increasing order.

[revapp f s] applies function f to the elements of s, in decreasing order.

[foldl f e s] applies the folding function f to the entries of the set in increasing order.

[foldr f e s] applies the folding function f to the entries of the set in decreasing order.

[find p s] returns SOME i, where i is an item in s which satisfies p, if one exists; otherwise returns NONE.

Module Lexing

*Lexing -- run-time library for lexers generated by mosmllex
 Closely based on the library for camllex. Copyright 1993 INRIA, France*

```
local open Obj in

type lexbuf

val createLexerString : string -> lexbuf
val createLexer      : (CharArray.array -> int -> int) -> lexbuf

val getLexeme       : lexbuf -> string
val getLexemeChar   : lexbuf -> int -> char
val getLexemeStart  : lexbuf -> int
val getLexemeEnd    : lexbuf -> int

For internal use in generated lexers:

val dummyAction      : lexbuf -> obj
val backtrack        : lexbuf -> 'a
prim_val getNextChar : lexbuf -> char = 1 "get_next_char"

prim_val getLexBuffer     : lexbuf -> string          = 1 "field1"
prim_val getLexAbsPos    : lexbuf -> int             = 1 "field2"
prim_val getLexStartPos  : lexbuf -> int             = 1 "field3"
prim_val getLexCurrPos   : lexbuf -> int             = 1 "field4"
prim_val getLexLastPos   : lexbuf -> int             = 1 "field5"
prim_val getLexLastAction: lexbuf -> (lexbuf -> obj) = 1 "field6"

prim_val setLexAbsPos    : lexbuf -> int -> unit      = 2 "setfield2"
prim_val setLexStartPos  : lexbuf -> int -> unit      = 2 "setfield3"
prim_val setLexCurrPos   : lexbuf -> int -> unit      = 2 "setfield4"
prim_val setLexLastPos   : lexbuf -> int -> unit      = 2 "setfield5"
prim_val setLexLastAction: lexbuf -> (lexbuf -> obj) -> unit = 2 "setfield6"
end
```

These functions are for use in mosmllex-generated lexers. For further information, see the Moscow ML Owner's Manual. For examples, see mosml/examples/lexyacc and mosml/examples/calc.

[lexbuf] is the type of lexer buffers. A lexer buffer is the argument passed to the scanning functions defined by the mosmllex-generated scanners. The lexer buffer holds the current state of the scanner, plus a function to refill the buffer from the input.

[createLexerString s] returns a lexer buffer which reads from the given string s. Reading starts from the first character in the string. An end-of-input condition is generated when the end of the string is reached.

[createLexer f] returns a lexer buffer that will use the given function f for reading additional input. When the lexer needs more characters, it will call the given function as (f carr n), where carr is a character array, and n is an integer. The function should put at most characters or in carr, starting at character number 0, and return the number of characters actually stored. A return value of 0 means end of input.

A lexer definition (input to mosmllex) consists of fragments of this form

```
parse
  lhs1  { rhs1 }
  | lhs2  { rhs2 }
  | lhs3  { rhs3 }
  | ...
```

where the lhs are regular expressions matching some string of characters, and the rhs are corresponding semantic actions, written in ML. The following functions can be used in the semantic actions:

[getLexeme lexbuf] returns the string matched by the left-hand side regular expression.

[getLexemeChar lexbuf i] returns character number i in the matched string.

[getLexemeStart lexbuf] returns the start position of the matched string (in the input stream). The first character in the stream has position 0.

[getLexemeEnd lexbuf] returns the end position, plus one, of the matched string (in the input stream). The first character in the stream has position 0.

Module List

List -- SML Basis Library

```
datatype list = datatype list

exception Empty

val null      : 'a list -> bool
val hd        : 'a list -> 'a                                Empty
val tl        : 'a list -> 'a list                            Empty
val last      : 'a list -> 'a                                Empty

val nth       : 'a list * int -> 'a                          Subscript
val take     : 'a list * int -> 'a list                      Subscript
val drop     : 'a list * int -> 'a list                      Subscript

val length    : 'a list -> int

val rev       : 'a list -> 'a list

val @         : 'a list * 'a list -> 'a list
val concat   : 'a list list -> 'a list
val revAppend : 'a list * 'a list -> 'a list

val app       : ('a -> unit) -> 'a list -> unit
val map      : ('a -> 'b) -> 'a list -> 'b list
val mapPartial : ('a -> 'b option) -> 'a list -> 'b list

val find      : ('a -> bool) -> 'a list -> 'a option
val filter    : ('a -> bool) -> 'a list -> 'a list
val partition : ('a -> bool) -> 'a list -> ('a list * 'a list)

val foldr    : ('a * 'b -> 'b) -> 'b -> 'a list -> 'b
val foldl    : ('a * 'b -> 'b) -> 'b -> 'a list -> 'b

val exists   : ('a -> bool) -> 'a list -> bool
val all      : ('a -> bool) -> 'a list -> bool

val collate  : ('a * 'a -> order) -> 'a list * 'a list -> order
val tabulate : int * (int -> 'a) -> 'a list                  Size
val getItem  : 'a list -> ('a * 'a list) option
```

[*'a list*] is the type of lists of elements of type '*a*.

[*null xs*] is true iff *xs* is nil.

[*hd xs*] returns the first element of *xs*. Raises *Empty* if *xs* is nil.

[*tl xs*] returns all but the first element of *xs*.
Raises *Empty* if *xs* is nil.

[*last xs*] returns the last element of *xs*. Raises *Empty* if *xs* is nil.

[*nth(xs, i)*] returns the *i*'th element of *xs*, counting from 0.
Raises *Subscript* if *i*<0 or *i*>=length *xs*.

[*take(xs, i)*] returns the first *i* elements of *xs*. Raises *Subscript*

```

if i<0 or i>length xs.

[drop(xs, i)] returns what is left after dropping the first i
elements of xs. Raises Subscript if i<0 or i>length xs.
It holds that take(xs, i) @ drop(xs, i) = xs when 0 <= i <= length xs.

[length xs] returns the number of elements in xs.

[rev xs] returns the list of xs's elements, reversed.

[xs @ ys] returns the list which is the concatenation of xs and ys.

[concat xss] returns the list which is the concatenation of all the
lists in xss.

[revAppend(xs, ys)] is equivalent to rev xs @ ys, but more efficient.

[app f xs] applies f to the elements of xs, from left to right.

[map f xs] applies f to each element x of xs, from left to
right, and returns the list of f's results.

[mapPartial f xs] applies f to each element x of xs, from left
to right, and returns the list of those y's for which f(x)
evaluated to SOME y.

[find p xs] applies p to each element x of xs, from left to right,
until p(x) evaluates to true; returns SOME x if such an x exists,
otherwise NONE.

[filter p xs] applies p to each element x of xs, from left to
right, and returns the sublist of those x for which p(x) evaluated
to true.

[partition p xs] applies p to each element x of xs, from left
to right, and returns a pair (pos, neg) where pos is the sublist
of those x for which p(x) evaluated to true, and neg is the sublist of
those for which p(x) evaluated to false.

[foldr op% e xs] evaluates x1 % (x2 % ( ... % (x(n-1) % (xn % e)) ... ))
where xs = [x1, x2, ..., x(n-1), xn], and % is taken to be infix.

[foldl op% e xs] evaluates xn % (x(n-1) % ( ... % (x2 % (x1 % e))))
where xs = [x1, x2, ..., x(n-1), xn], and % is taken to be infix.

[exists p xs] applies p to each element x of xs, from left to
right until p(x) evaluates to true; returns true if such an x
exists, otherwise false.

[all p xs] applies p to each element x of xs, from left to
right until p(x) evaluates to false; returns false if such an x
exists, otherwise true.

[collate cmp (xs, ys)] returns LESS, EQUAL or GREATER according as
xs precedes, equals or follows ys in the lexicographic ordering on
lists induced by the ordering cmp on elements.

[tabulate(n, f)] returns a list of length n whose elements are
f(0), f(1), ..., f(n-1), created from left to right. Raises Size
if n<0.

```

[getItem xs] attempts to extract an element from the list xs. It returns NONE if xs is empty, and returns SOME (x, xr) if xs=x::xr. This can be used for scanning booleans, integers, reals, and so on from a list of characters. For instance, to scan a decimal integer from a list cs of characters, compute

```
Int.scan StringCvt.DEC List.getItem cs
```

Module ListPair

ListPair -- SML Basis Library

```

val zip      : 'a list * 'b list -> ('a * 'b) list
val unzip   : ('a * 'b) list -> 'a list * 'b list
val map     : ('a * 'b -> 'c) -> 'a list * 'b list -> 'c list
val app     : ('a * 'b -> unit) -> 'a list * 'b list -> unit
val all     : ('a * 'b -> bool) -> 'a list * 'b list -> bool
val exists : ('a * 'b -> bool) -> 'a list * 'b list -> bool
val foldr   : ('a * 'b * 'c -> 'c) -> 'c -> 'a list * 'b list -> 'c
val foldl   : ('a * 'b * 'c -> 'c) -> 'c -> 'a list * 'b list -> 'c

val allEq    : ('a * 'b -> bool) -> 'a list * 'b list -> bool
exception UnequalLengths

val zipEq    : ('a list * 'b list) -> ('a * 'b) list
val mapEq   : ('a * 'b -> 'c) -> 'a list * 'b list -> 'c list
val appEq   : ('a * 'b -> 'c) -> 'a list * 'b list -> unit
val foldrEq : ('a * 'b * 'c -> 'c) -> 'c -> 'a list * 'b list -> 'c
val foldlEq : ('a * 'b * 'c -> 'c) -> 'c -> 'a list * 'b list -> 'c

```

These functions process pairs (xs, ys) of lists.
There are three groups of functions:

- * zip, map, app, all, exists, foldr and foldl raise no exception when the argument lists are found to be of unequal length; the excess elements from the longer list are simply disregarded.
- * zipEq, mapEq, appEq, foldrEq and foldlEq raise exception UnequalLengths when the argument lists are found to be of unequal length.
- * allEq raises no exception but returns false if the lists are found to have unequal lengths (after traversing the lists).

[zip (xs, ys)] returns the list of pairs of corresponding elements from xs and ys.

[unzip xys] returns a pair (xs, ys), where xs is the list of first components of xys, and ys is the list of second components from xys. Hence zip (unzip xys) has the same result and effect as xys.

[map f (xs, ys)] applies function f to the pairs of corresponding elements of xs and ys from left to right and returns the list of results. Hence map f (xs, ys) has the same result and effect as List.map f (zip (xs, ys)).

[app f (xs, ys)] applies function f to the pairs of corresponding elements of xs and ys from left to right and returns (). Hence app f (xs, ys) has the same result and effect as List.app f (zip (xs, ys)).

[all p (xs, ys)] applies predicate p to the pairs of corresponding elements of xs and ys from left to right until p evaluates to false or one or both lists is exhausted; returns true if p is true of all such pairs; otherwise false. Hence all p (xs, ys) has the same result and effect as List.all p (zip (xs, ys)).

[exists p (xs, ys)] applies predicate p to the pairs of corresponding elements of xs and ys from left to right until p evaluates to true or one or both lists is exhausted; returns true if p is true of any such pair; otherwise false.
Hence exists p (xs, ys) has the same result and effect as List.exists p (zip (xs, ys)). Also, exists p (xs, ys) is equivalent to not(all (not o p) (xs, ys)).

[foldr f e (xs, ys)] evaluates f(x1, y1, f(x2, y2, f(..., f(xn, yn, e))))
where xs = [x1, x2, ..., x(n-1), xn, ...],
ys = [y1, y2, ..., y(n-1), yn, ...],
and n = min(length xs, length ys).
Equivalent to List.foldr (fn ((x, y), r) => f(x, y, r)) e (zip(xs, ys)).

[foldl f e (xs, ys)] evaluates f(xn, yn, f(..., f(x2, y2, f(x1, y1, e))))
where xs = [x1, x2, ..., x(n-1), xn, ...],
ys = [y1, y2, ..., y(n-1), yn, ...],
and n = min(length xs, length ys).
Equivalent to List.foldl (fn ((x, y), r) => f(x, y, r)) e (zip(xs, ys)).

[zipEq (xs, ys)] returns the list of pairs of corresponding elements from xs and ys. Raises UnequalLengths if xs and ys do not have the same length.

[mapEq f (xs, ys)] applies function f to pairs of corresponding elements of xs and ys from left to right, and then returns the list of results if xs and ys have the same length, otherwise raises UnequalLengths. If f has no side effects and terminates, then it is equivalent to List.map f (zipEq (xs, ys)).

[appEq f (xs, ys)] applies function f to pairs of corresponding elements of xs and ys from left to right, and then raises UnequalLengths if xs and ys have the same length.

[foldrEq f e (xs, ys)] raises UnequalLengths if xs and ys do not have the same length. Otherwise evaluates
f(x1, y1, f(x2, y2, f(..., f(xn, yn, e))))
where xs = [x1, x2, ..., x(n-1), xn],
ys = [y1, y2, ..., y(n-1), yn],
and n = length xs = length ys.
Equivalent to List.foldr (fn ((x,y),r) => f(x,y,r)) e (zipEq(xs, ys)).

[foldlEq f e (xs, ys)] evaluates
f(xn, yn, f(..., f(x2, y2, f(x1, y1, e))))
where xs = [x1, x2, ..., x(n-1), xn, ...],
ys = [y1, y2, ..., y(n-1), yn, ...],
and n = min(length xs, length ys).
Then raises UnequalLengths if xs and ys do not have the same length. If f has no side effects and terminates normally, then it is equivalent to List.foldl (fn ((x,y),r) => f(x,y,r)) e (zipEq(xs, ys)).

[allEq p (xs, ys)] works as all p (xs, ys) but returns false if xs and ys do not have the same length. Equivalent to
all p (xs, ys) andalso length xs = length ys.

Module Listsort

Listsort

```
val sort      : ('a * 'a -> order) -> 'a list -> 'a list
val sorted    : ('a * 'a -> order) -> 'a list -> bool
val merge     : ('a * 'a -> order) -> 'a list * 'a list -> 'a list
val mergeUniq : ('a * 'a -> order) -> 'a list * 'a list -> 'a list
val eqclasses : ('a * 'a -> order) -> 'a list -> 'a list list
```

[sort ordr xs] sorts the list xs in nondecreasing order, using the given ordering. Uses Richard O'Keefe's smooth applicative merge sort.

[sorted ordr xs] checks that the list xs is sorted in nondecreasing order, in the given ordering.

[merge ordr (xs, ys)] returns a sorted list of the elements of the sorted lists xs and ys, preserving duplicates. Both xs and ys must be already sorted by ordr, that is, must satisfy
 sorted ordr xs andalso sorted ordr ys
 Then the result satisfies
 sorted ordr (merge ordr (xs, ys))

[mergeUniq ordr (xs, ys)] returns a sorted list of the elements of the sorted lists xs and ys, without duplicates: no elements in the result are EQUAL by ordr. Both xs and ys must be already sorted by ordr.

[eqclasses ordr xs] returns a list [x_{s1}, x_{s2}, ..., x_{sn}] of non-empty equivalence classes of xs, obtained by sorting the list and then grouping consecutive runs of elements that are EQUAL by ordr. If ordr is a total order, then it holds for xi in xsi and xj in xsj:
 ordr(xi, xj) = EQUAL iff i=j and
 ordr(xi, xj) = LESS iff i<j and
 ordr(xi, xj) = GREATER iff i>j
 Thus ordr(xi, xj) = Int.compare(i, j). A list of representatives for the equivalence classes of xs under ordering ordr can be obtained by
 List.map List.hd (eqclasses ordr xs)

Module Location

*Location -- error reporting for mosmllex and mosmlyac
Based on src/compiler/location from the Caml Light 0.6 distribution*

```
datatype Location = Source file positions
  Loc of int      Position of the first character
    * int          Position of the character following the last one

val errLocation : string * BasicIO.instream * Lexing.lexbuf -> Location
val errMsg      : string * BasicIO.instream * Lexing.lexbuf -> Location
val errPrompt    : string -> unit;
val nilLocation : Location
val getCurrentLocation : unit -> Location
val mkLoc : 'a -> Location * 'a
val xLR  : Location * 'a -> Location
val xL   : Location * 'a -> int
val xR   : Location * 'a -> int
val xxLR : Location * 'a -> Location * 'b -> Location
val xxRL : Location * 'a -> Location * 'b -> Location
```

These functions support error reporting in lexers and parsers generated with mosmllex and mosmlyac. The directory mosml/examples/lexyacc/ contains an example of their use.

[errLocation (file, stream, lexbuf) loc] prints the part of the lexer input which is indicated by location loc.

If file <> "" then it is assumed to be the name of the file from which the lexer reads, the stream is assumed to be an open input stream associated with this file, and lexbuf is the lexer buffer used to read from the stream. Under MS DOS (and presumably Windows, OS/2, and MacOS), the stream must have been opened in binary mode (with Nonstdio.open_in_bin), or else the positioning in the file will be wrong (due to the translation of CRLF into newline in text files).

If file = "" then the lexer is assumed to read from some source other than a stream, and the lexbuf (rather than the instream) is used to obtain the location indicated, if possible. In this case the stream is immaterial; it will not be used.

[errMsg (file, stream, lexbuf) loc msg] calls errLocation to print the indicated part of the lexer input, then prints the error message msg and raises exception Fail.

[errPrompt msg] prints "!", the string msg, and a newline on standard output.

[nilLocation] is the undefined location.

[getCurrentLocation ()] can be called within the semantic action part of a grammar rule (only) and returns the location of the string matching the left-hand side of the rule.

[mkLoc a] can be called within the semantic action part of a grammar rule (only), and returns a pair (loc, a) of the current location and the value a. This is typically used to decorate

abstract syntax tree nodes with location information, for use in subsequent error reports.

[xLR loc_a] returns the location of the decorated value loc_a.

[xL loc_a] returns the left end position of loc_a.

[xR loc_a] returns the right end position of loc_a.

[xxLR loc_a loc_b] returns the location extending from the left end of loc_a to the right end of loc_b.

[xxRL loc_a loc_b] returns the location extending from the right end of loc_a to the left end of loc_b.

Module Math

Math -- SML Basis Library

```
type real = real

val pi      : real
val e       : real

val sqrt   : real -> real
val sin    : real -> real
val cos    : real -> real
val tan    : real -> real
val atan   : real -> real
val asin   : real -> real
val acos   : real -> real
val atan2  : real * real -> real
val exp    : real -> real
val pow    : real * real -> real
val ln     : real -> real
val log10  : real -> real
val sinh   : real -> real
val cosh   : real -> real
val tanh   : real -> real
```

[pi] is the circumference of the circle with diameter 1, that is,
3.14159265358979323846.

[e] is the base of the natural logarithm: 2.7182818284590452354.

[sqrt x] is the square root of x. Raises Domain if x < 0.0.

[sin r] is the sine of r, where r is in radians.

[cos r] is the cosine of r, where r is in radians.

[tan r] is the tangent of r, where r is in radians. Raises Domain if
r is a multiple of pi/2.0.

[atan t] is the arc tangent of t, in the open interval] ~pi/2.0, pi/2.0 [.

[asin t] is the arc sine of t, in the closed interval [~pi/2.0, pi/2.0].
Raises Domain if abs x > 1.

[acos t] is the arc cosine of t, in the closed interval [0, pi].
Raises Domain if abs x > 1.

[atan2(y, x)] is the arc tangent of y/x, in the interval] ~pi, pi],
except that atan2(y, 0) = sign y * pi/2.0. The quadrant of the result
is the same as the quadrant of the point (x, y).
Hence sign(cos(atan2(y, x))) = sign x
and sign(sin(atan2(y, x))) = sign y.

[exp x] is e to the x'th power.

[pow (x, y)] is x it the y'th power, defined when
y >= 0 and (y integral or x >= 0)
or y < 0 and ((y integral and x <> 0.0) or x > 0).

We define pow(0, 0) = 1.

[$\ln x$] is the natural logarithm of x (that is, with base e).
Raises Domain if $x \leq 0.0$.

[$\log_{10} x$] is the base-10 logarithm of x . Raises Domain if $x \leq 0.0$.

[$\sinh x$] returns the hyperbolic sine of x , mathematically defined as
 $(\exp x - \exp (-x)) / 2.0$. Raises Overflow if x is too large.

[$\cosh x$] returns the hyperbolic cosine of x , mathematically defined as
 $(\exp x + \exp (-x)) / 2.0$. Raises Overflow if x is too large.

[$\tanh x$] returns the hyperbolic tangent of x , mathematically defined as
 $(\sinh x) / (\cosh x)$. Raises Domain if x is too large.

Module Meta

Meta -- functions available only in interactive Moscow ML sessions

```

val printVal      : 'a -> 'a
val printDepth    : int ref
val printLength   : int ref
val installPP     : (ppstream -> 'a -> unit) -> unit

val liberal       : unit -> unit
val conservative  : unit -> unit
val orthodox      : unit -> unit

val use           : string -> unit
val compile        : string -> unit
val compileToplevel: string list -> string -> unit
val compileStructure: string list -> string -> unit

val load          : string -> unit
val loadOne       : string -> unit
val loaded        : unit -> string list
val loadPath      : string list ref

val quietdec      : bool ref
val verbose        : bool ref

val quotation     : bool ref
val valuepoly     : bool ref

val quit          : unit -> 'a

```

These values and functions are available in the Moscow ML
interactive system only.

[printVal e] prints the value of expression e to standard output
exactly as it would be printed at top-level, and returns the value
of e. Output is flushed immediately. This function is provided as
a simple debugging aid. The effect of printVal is similar to that
of 'print' in Edinburgh ML or Umeaa ML. For string arguments, the
effect of SML/NJ print can be achieved by the function
TextIO.print : string -> unit.

[printDepth] determines the depth (in terms of nested constructors,
records, tuples, lists, and vectors) to which values are printed by
the top-level value printer and the function printVal. The components
of the value whose depth is greater than printDepth are printed as
'#'. The initial value of printDepth is 20. This value can be
changed at any moment, by evaluating, for example,

```
printDepth := 17;
```

[printLength] determines the way in which list values are printed
by the top-level value printer and the function printVal. If the
length of a list is greater than printLength, then only the first
printLength elements are printed, and the remaining elements are
printed as '...'. The initial value of printLength is 200. This
value can be changed at any moment, by evaluating, for example,

```
printLength := 500;
```

[quit ()] quits Moscow ML immediately.

[installPP pp] installs the prettyprinter pp : ppstream -> ty -> unit at type ty. The type ty must be a nullary (parameter-less) type constructor representing a datatype, either built-in (such as bool) or user-defined. Whenever a value of type ty is about to be printed by the interactive system, or function printVal is invoked on an argument of type ty, the pretty-printer pp will be invoked to print it. See library unit PP for more information.

[use "f"] causes ML declarations to be read from file f as if they were entered from the console. A file loaded by use may, in turn, evaluate calls to use. For best results, use 'use' only at top level, or at top level within a use'd file.

[liberal ()] sets liberal mode for the compilation functions: accept (without warnings) all extensions to the SML Modules language. The extensions are: higher-order modules (functors defined within structures and functors); first-order modules (structures can be packed as values, and values can be unpacked as structures); and recursively defined modules (signatures and structures). The liberal, conservative, and orthodox modes affect the functions compile, compileStructure, and compileToplevel. The liberal mode may be set also by the mosml option -liberal.

[conservative ()] sets conservative mode for the compilation functions: accept all extensions to the SML Modules language, but issue a warning for each use. The conservative mode may be set also by the mosml option -conservative. This is the default.

[orthodox ()] sets orthodox mode for the compilation functions: reject all uses of the extensions to the SML Modules language. That is, accept only SML Modules syntax. The orthodox mode may be set also by the mosml option -orthodox.

[compile "U.sig"] will compile and elaborate the specifications in file U.sig in structure mode, producing a compiled signature U in file U.ui. This function is backwards compatible with Moscow ML 1.44 and earlier. Equivalent to compileStructure [] "U.sig".

[compile "U.sml"] will elaborate and compile the declarations in file U.sml in structure mode, producing a compiled structure U in bytecode file U.uo. If there is an explicit signature file U.sig, then file U.ui must exist, and the unit body must match the signature. If there is no U.sig, then an inferred signature file U.ui will be produced also. No evaluation takes place. This function is backwards compatible with Moscow ML 1.44 and earlier. Equivalent to compileStructure [] "U.sml".

The declared identifiers will be reported if verbose is true (see below); otherwise compilation will be silent. In any case, compilation warnings are reported, and compilation errors abort the compilation and raise the exception Fail with a string argument.

```
[compileStructure opnunits "U.sig"] compiles the specifications
in file U.sig as if they form a signature declaration
    signature U = sig ... contents of U.sig ... end
The contents of opnunits is added to the compilation context in
which the specifications in U.sig are compiled. The result is a
compiled signature file U.ui. This
corresponds to invoking the batch compiler as follows:
    mosmlc -c U1.ui ... Un.ui -structure U.sig
where opnunits equals ["U1", ..., "Un"].
```

[compileStructure opnunits "U.sml"] compiles the declarations in file U.sml as if they formed a structure declaration
 structure U = struct ... contents of U.sml ... end
 The contents of opnunits is added to the compilation context in which the declarations in U.sml are compiled. If U.ui exists already and represents a signature called U, then the compiled declarations are matched against it. The result is a bytecode file U.uo. If no file U.ui existed, then also a file U.ui is created, containing the inferred signature of structure U. This corresponds to invoking the batch compiler as follows:
 mosmlc -c U1.ui ... Un.ui -structure U.sml
 where opnunits equals ["U1", ..., "Un"].

[compileToplevel opnunits "U.sig"] compiles the specifications in file U.sig, in a context in which all declarations from opnunits are visible, creating a compiled signature file U.ui. This corresponds to invoking the batch compiler as follows:

mosmlc -c U1.ui ... Un.ui -toplevel U.sig
 where opnunits equals ["U1", ..., "Un"].

[compileToplevel opnunits "U.sml"] compiles the declarations in file U.sml, in a context in which all declarations from opnunits are visible, creating a bytecode file U.uo. If U.ui exists already, then the compiled declarations are matched against it; otherwise the file U.ui is created. This corresponds to invoking the batch compiler as follows

mosmlc -c U1.ui ... Un.ui -toplevel U.sml
 where opnunits equals ["U1", ..., "Un"].

[load "U"] will load and evaluate the compiled unit body from file U.uo. The resulting values are not reported, but exceptions are reported, and cause evaluation and loading to stop. If U is already loaded, then load "U" has no effect. If any other unit is mentioned by U but not yet loaded, then it will be loaded automatically before U.

After loading a unit, it can be opened with 'open U'. Opening it at top-level will list the identifiers declared in the unit.

When loading U, it is checked that the signatures of units mentioned by U agree with the signatures used when compiling U, and it is checked that the signature of U has not been modified since U was compiled; these checks are necessary for type safety. The exception Fail is raised if these signature checks fail, or if the file containing U or a unit mentioned by U does not exist.

[loadOne "U"] is similar to 'load "U"', but raises exception Fail if U is already loaded or if some unit mentioned by U is not yet loaded. That is, it does not automatically load any units mentioned by U. It performs the same signature checks as 'load'.

[loaded ()] returns a list of the names of all compiled units that have been loaded so far. The names appear in some random order.

[loadPath] determines the load path: which directories will be searched for interface files (.ui files), bytecode files (.uo files), and source files (.sml files). This variable affects the load, loadOne, and use functions. The current directory is always searched first, followed by the directories in loadPath, in order. By default, only the standard library directory is in the list, but

if additional directories are specified using option -I, then these directories are prepended to loadPath.

[quietdec] when true, turns off the interactive system's prompt and responses, except warnings and error messages. Useful for writing scripts in SML. The default value is false; can be set to true with the -quietdec command line option.

[verbose] determines whether the signature inferred by a call to compile will be printed. The printed signature follows the syntax of Moscow ML signatures, so the output of compile "U.sml" can be edited to subsequently create file U.sig. The default value is ref false.

[quotation] determines whether quotations and antiquotations are permitted in declarations entered at top-level and in files compiled with compile. A quotation is a piece of text surrounded by backquote characters 'a b c' and is used to embed object language phrases in ML programs; see the Moscow ML Owner's Manual for a brief explanation of quotations. When quotation is false, the backquote character is an ordinary symbol which can be used in ML symbolic identifiers. When quotation is true, the backquote character is illegal in symbolic identifiers, and a quotation 'a b c' will be recognized by the parser and evaluated to an object of type 'a General.frag list. False by default.

[valuepoly] determines whether value polymorphism is used or not in the type checker. With value polymorphism (the default), there is no distinction between imperative ('_a) and applicative ('a) type variables, and type variables are generalized only in bindings to non-expansive expressions. Non-generalized type variables are left free, to be instantiated when the bound identifier is used. An expression is non-expansive if it is a variable, a special constant, a function, a tuple or record of non-expansive expressions, a parenthesized or typed non-expansive expression, or the application of an exception or value constructor (other than ref) to a non-expansive expression. If valuepoly is false, then the type checker will distinguish imperative and applicative type variables, generalize all applicative type variables, and generalize imperative type variables only in non-expansive expressions. True by default.

Module Mosml

Mosml -- some Moscow ML specific functions

```
val argv      : unit -> string list
val time      : ('a -> 'b) -> ('a -> 'b)
val listDir   : string -> string list
val doubleVec : real -> Word8Vector.vector
val vecDouble : Word8Vector.vector -> real
val floatVec  : real -> Word8Vector.vector
val vecFloat  : Word8Vector.vector -> real
val md5sum    : string -> string

datatype runresult =
  Success of string
  | Failure of string

val run : string -> string list -> string -> runresult

val systemInfo: string list -> (string * string) list
```

[`argv ()`] returns the command line strings of the current process. Hence `List.nth(argv (), 0)` is the command used to invoke the SML process, `List.nth(argv (), 1)` is its first argument, and so on. We recommend using the SML Basis Library `CommandLine` structure instead.

[`time f arg`] applies `f` to `arg` and returns the result; as a side effect, it prints the time (cpu, system, and real time) consumed by the evaluation.

[`listDir path`] returns the list of all files and subdirectories of the directory indicated by `path`. Raises `OS.SysErr` in case of failure.

[`doubleVec r`] returns an eight-element vector of `Word8.word`, which contains the real number in the IEEE 754 floating-point ‘double format’ bit layout stored in big-endian (high byte first) order.

[`vecDouble v`] accepts an eight-element vector `v` of `Word8.word`, and returns the real number obtained by taking `v` to be an IEEE 754 floating-point ‘double format’ number stored in big-endian (high byte first) order. Raises `Fail` if `v` is not an eight-element vector.

[`floatVec r`] returns a four-element vector of `Word8.word`, which contains the real number in the IEEE 754 floating-point ‘float format’ bit layout stored in big-endian (high byte first) order. Raises `Fail` if `r` is not representable as a 32-bit float.

[`vecFloat v`] accepts a four-element vector `v` of `Word8.word`, and returns the real obtained by taking `v` to be an IEEE 754 floating-point ‘float format’ number stored in big-endian (high byte first) order. Raises `Fail` if `v` is not a four-element vector.

[`md5sum s`] computes the 128-bit MD5 checksum of string `s` and returns it as a 22 character base64 string.

[`run cmd args inp`] executes the program `cmd` with command-line arguments `args` and standard input `inp`. Returns `Success s` where `s` is the program’s (standard and error) output as a string, if it executed successfully; otherwise returns `Failure s` where `s` is its

(standard and error) output as a string.

Extreme care should be taken when calling this function in web scripts and similar, since the cmd is executed by the shell, so even the args can be abused for attacks.

[systemInfo query] returns a pair (p, v) for each property p in query, where v is the value associated with p. If query is the empty list, then all properties and values are returned. The property "version" is always guaranteed to have a value associated.

Module Mosmlcgi

Mosmlcgi -- support for writing CGI scripts in Moscow ML

1. Accessing the fields or parameters of a CGI call

```
val cgi_fieldnames      : string list
val cgi_field_strings   : string -> string list;
val cgi_field_string    : string -> string option;
val cgi_field_integer   : string * int -> int;
```

2. Accessing parts in multipart/form-data; form-based file upload

```
val cgi_partnames       : string list

type part
val cgi_part           : string -> part option
val cgi_parts          : string -> part list

val part_fieldnames    : part -> string list
val part_type           : part -> string option
val part_data           : part -> string
val part_field_strings : part -> string -> string list
val part_field_string  : part -> string -> string option
val part_field_integer : part -> string * int -> int
```

3. Administrative information

```
val cgi_server_software      : string option
val cgi_server_name          : string option
val cgi_gateway_interface    : string option
val cgi_server_protocol      : string option
val cgi_server_port          : string option
val cgi_request_method       : string option
val cgi_http_accept          : string option
val cgi_http_user_agent      : string option
val cgi_http_referer         : string option
val cgi_path_info             : string option
val cgi_path_translated       : string option
val cgi_script_name           : string option
val cgi_query_string          : string option
val cgi_remote_host           : string option
val cgi_remote_addr           : string option
val cgi_remote_user           : string option
val cgi_remote_ident          : string option
val cgi_auth_type              : string option
val cgi_content_type           : string option
val cgi_content_length         : string option
val cgi_annotation_server     : string option

val cgi_http_cookie           : string option
val cgi_http_forwarded        : string option
val cgi_http_host              : string option
val cgi_http_proxy_connection : string option
val cgi_script_filename        : string option
val cgi_document_root          : string option
val cgi_server_admin            : string option
val cgi_api_version            : string option
val cgi_the_request            : string option
val cgi_request_uri            : string option
val cgi_request_filename       : string option
```

```
val cgi_is_subreq           : string option
```

The Mosmlcgi library is for writing CGI programs in Moscow ML. A CGI program may be installed on a WWW server and is invoked in response to HTTP requests sent to the server from a web browser, typically from an HTML FORM element.

1. Obtaining field values sent from an ordinary HTML form

[cogi_fieldnames] is a list of the names of fields present in the CGI call message. If field name fnm is in cgi_fieldnames, then cgi_field_string fnm <>> NONE.

[cogi_field_strings fnm] is a (possibly empty) list of the strings bound to field fnm.

[cogi_field_string fnm] returns SOME(s) where s is a string bound to field name fnm, if any; otherwise NONE. Equivalent to

```
case cgi_field_strings fnm of
    []          => NONE
    | s :: _   => SOME s
```

[cogi_field_integer (fnm, deflt)] attempts to parse an integer from field fnm. Returns i if cgi_field_string(fnm) = SOME(s) and an integer i can be parsed from a prefix of s; otherwise returns deflt.

2. Obtaining field values sent with ENCTYPE="multipart/form-data"

[cogi_partnames] is a list of the names of the parts of the multipart/form-data message.

The type part is the abstract type of parts of a message. Each part may have several fields. In this implementation, the field of a part cannot be another part itself.

[cogi_parts pnm] is a (possibly empty) list of the parts called pnm.

[cogi_part pnm] is SOME(prt) where prt is a part called pnm, if any; otherwise NONE. Equivalent to

```
case cgi_parts pnm of
    []          => NONE
    | prt :: _  => SOME prt
```

[part_fieldnames prt] is the list of field names in part pnm.

[part_type prt] is SOME(typ) if the part prt contains a specification 'Content-Type: typ'; otherwise NONE.

[part_data prt] is the data contained in part prt; for instance, the contents of a file uploaded via form-based file upload.

[part_field_strings prt fnm] is a (possibly empty) list of the strings bound to field fnm in part prt.

[part_field_string prt fnm] returns SOME(s) where s is a string bound to field name fnm in part prt, if any; otherwise NONE.

```
Equivalent to
  case part_field_strings prt fnm of
    []      => NONE
    | s :: _ => SOME s

[part_field_integer prt (fnm, deflt)] attempts to parse an integer
from field fnm of part prt. Returns i if part_field_string prt fnm
= SOME(s) and an integer i can be parsed from a prefix of s;
otherwise returns deflt.
```

3. Administrative and server information

Each of the following variables has the value SOME(s) if the corresponding CGI environment variable is bound to string s; otherwise NONE:

```
[cgi_server_software] is the value of SERVER_SOFTWARE
[cgi_server_name] is the value of SERVER_NAME
[cgi_gateway_interface] is the value of GATEWAY_INTERFACE
[cgi_server_protocol] is the value of SERVER_PROTOCOL
[cgi_server_port] is the value of SERVER_PORT
[cgi_request_method] is the value of REQUEST_METHOD
[cgi_http_accept] is the value of HTTP_ACCEPT
[cgi_http_user_agent] is the value of HTTP_USER_AGENT
[cgi_http_referer] is the value of HTTP_REFERER
[cgi_path_info] is the value of PATH_INFO
[cgi_path_translated] is the value of PATH_TRANSLATED
[cgi_script_name] is the value of SCRIPT_NAME
[cgi_query_string] is the value of QUERY_STRING
[cgi_remote_host] is the value of REMOTE_HOST
[cgi_remote_addr] is the value of REMOTE_ADDR
[cgi_remote_user] is the value of REMOTE_USER
[cgi_remote_ident] is the value of REMOTE_IDENT
[cgi_auth_type] is the value of AUTH_TYPE
[cgi_content_type] is the value of CONTENT_TYPE
[cgi_content_length] is the value of CONTENT_LENGTH, that is, the
length of the data transmitted in the CGI call.
[cgi_annotation_server] is the value of ANNOTATION_SERVER
```

[cgi_http_cookie] is the value of HTTP_COOKIE
[cgi_http_forwarded] is the value of HTTP_FORWARDED
[cgi_http_host] is the value of HTTP_HOST
[cgi_http_proxy_connection] is the value of HTTP_PROXY_CONNECTION
[cgi_script_filename] is the value of SCRIPT_FILENAME
[cgi_document_root] is the value of DOCUMENT_ROOT
[cgi_server_admin] is the value of SERVER_ADMIN
[cgi_api_version] is the value of API_VERSION
[cgi_the_request] is the value of THE_REQUEST
[cgi_request_uri] is the value of REQUEST_URI
[cgi_request_filename] is the value of REQUEST_FILENAME
[cgi_is_subreq] is the value of IS_SUBREQ

Module Mosmlcookie

```
Mosmlcookie -- getting and setting cookies in CGI scripts

exception CookieError of string

val allCookies      : string list
val getCookieValue : string -> string option
val getCookie      : string -> string option

type cookiedata =
  { name    : string,
    value   : string,
    expiry  : Date.date option,
    domain : string option,
    path   : string option,
    secure  : bool }

val setCookie     : cookiedata -> string
val setCookies   : cookiedata list -> string

val deleteCookie : { name : string, path : string option } -> string
```

These functions may be used in CGI scripts to get and set cookies.
(c) Hans Molin, Computing Science Dept., Uppsala University, 1999.

[getCookieValue ck] returns SOME(v) where v is the value associated
with the cookie ck, if any; otherwise returns NONE.

[getCookie ck] returns SOME(nv) where nv is the ck=value string
for the cookie ck, if any; otherwise returns NONE.

[allCookies] is a list [nv1, nv2, ..., nvm] of all the ck=value
pairs of defined cookies.

[setCookie { name, value, expiry, domain, path, secure }] returns a
string which (when transmitted to a browser as part of the HTTP
response header) sets a cookie with the given name, value, expiry
date, domain, path, and security.

[setCookies ckds] returns a string which (when transmitted to a
browser as part of the HTTP response header) sets the specified cookies.

[deleteCookie { name, path }] returns a string which (when
transmitted to a browser as part of the HTTP response header)
deletes the specified cookie by setting its expiry to some time in
the past.

Module Msp

Msp -- utilities for CGI scripts and ML Server Pages

Efficiently concatenable word sequences

```
datatype wseq =
  Empty                                The empty sequence
  | Nl                                    Newline
  | $ of string                          A string
  | $$ of string list                   A sequence of strings
  | && of wseq * wseq;                  Concatenation of sequences
```

Manipulating wseqs

```
val prmap     : ('a -> wseq) -> 'a list -> wseq
val prsep    : wseq -> ('a -> wseq) -> 'a list -> wseq
val flatten   : wseq -> string
val printseq  : wseq -> unit
val vec2list  : 'a vector -> 'a list
```

Shorthands for accessing CGI parameters

```
exception ParamMissing of string
exception NotInt of string * string
```

```
val %        : string -> string
val %?       : string -> bool
val %#       : string -> int
val %%       : string * string -> string
val %%#      : string * int -> int
```

HTML generic marks

```
val mark0     : string -> wseq
val mark0a    : string -> string -> wseq
val mark1     : string -> wseq -> wseq
val mark1a    : string -> string -> wseq -> wseq
val comment   : wseq -> wseq
```

HTML documents and headers

```
val html      : wseq -> wseq
val head      : wseq -> wseq
val title     : wseq -> wseq
val body      : wseq -> wseq
val bodya     : string -> wseq -> wseq
val htmldoc   : wseq -> wseq -> wseq
```

HTML headings and vertical format

```
val h1        : wseq -> wseq
val h2        : wseq -> wseq
val h3        : wseq -> wseq
val h4        : wseq -> wseq
val h5        : wseq -> wseq
val h6        : wseq -> wseq
val p         : wseq -> wseq
val pa        : string -> wseq -> wseq
```

```

val br      : wseq
val bra     : string -> wseq
val hr      : wseq
val hra     : string -> wseq

val divi    : wseq -> wseq
val divia   : string -> wseq -> wseq
val blockquote : wseq -> wseq
val blockquotea : string -> wseq -> wseq
val center   : wseq -> wseq
val address   : wseq -> wseq
val pre      : wseq -> wseq

```

HTML anchors and hyperlinks

```

val ahref    : string -> wseq -> wseq
val ahrefa   : string -> string -> wseq -> wseq
val fname    : string -> wseq -> wseq

```

HTML text formats and style

```

val em       : wseq -> wseq
val strong   : wseq -> wseq
val tt       : wseq -> wseq
val sub      : wseq -> wseq
val sup      : wseq -> wseq
val fonta    : string -> wseq -> wseq

```

HTML lists

```

val ul       : wseq -> wseq
val ula     : string -> wseq -> wseq
val ol       : wseq -> wseq
val ola     : string -> wseq -> wseq
val li       : wseq -> wseq
val dl       : wseq -> wseq
val dla     : string -> wseq -> wseq
val dt       : wseq -> wseq
val dd       : wseq -> wseq

```

HTML tables

```

val table   : wseq -> wseq
val tablea  : string -> wseq -> wseq
val tr      : wseq -> wseq
val tra     : string -> wseq -> wseq
val td      : wseq -> wseq
val tda    : string -> wseq -> wseq
val th      : wseq -> wseq
val tha    : string -> wseq -> wseq
val caption : wseq -> wseq
val captiona : string -> wseq -> wseq

```

HTML images and image maps

```

val img     : string -> wseq
val imga   : string -> string -> wseq
val map    : string -> wseq -> wseq
val mapa   : string -> string -> wseq -> wseq
val area   : { alt : string option, coords : string,
               href : string option, shape : string} -> wseq

```

HTML forms etc

```

val form      : string -> wseq -> wseq
val forma     : string -> string -> wseq -> wseq
val input     : string -> wseq
val inputa    : string -> string -> wseq
val intext   : string -> string -> wseq
val inpassword : string -> string -> wseq
val incheckbox : {name : string, value : string} -> string -> wseq
val inradio   : {name : string, value : string} -> string -> wseq
val inreset   : string -> string -> wseq
val insubmit  : string -> string -> wseq
val inhiddenn : {name : string, value : string} -> wseq
val textarea  : string -> wseq -> wseq
val textareaaa: string -> string -> wseq -> wseq
val select    : string -> string -> wseq -> wseq
val option    : string -> wseq

```

HTML frames and framesets

```

val frameset  : string -> wseq -> wseq
val frame     : { src : string, name : string } -> wseq
val framea   : { src : string, name : string } -> string -> wseq

```

HTML encoding

```

val urlencode : string -> string
val htmlencode: string -> string

```

This module provides support functions for writing CGI scripts and ML Server Page scripts.

[wseq] is the type of efficiently concatenable word sequences. Building an HTML page (functionally) as a wseq is more efficient than building it (functionally) as a string, and more convenient and modular than building it (imperatively) by calling print.

[Empty] represents the empty string "".

[Nl] represents the string "\n" consisting of a single newline character.

[\$ s] represents the string s.

[\$\$ ss] represents the string String.concat(ss).

[&&(ws1, ws2)] represents the concatenation of the strings represented by ws1 and ws2. The function && should be declared infix &&

[prmap f xs] is f x1 && ... && f xn evaluated from left to right, when xs is [x1, ..., xn].

[prsep sep f xs] is f x1 && sep && ... && sep && f xn, evaluated from left to right, when xs is [x1, ..., xn].

[flatten ws] is the string represented by ws.

[printseq ws] is equivalent to print(flatten ws), but avoids

building any new strings.

[vec2list vec] is a list of the elements of vector vec. Use it to convert e.g. the results of a database query into a list, for processing with prmap or prsep.

Shorthands for accessing CGI parameters:

[%? fnm] returns true if there is a string associated with CGI parameter fnm; otherwise returns false.

[% fnm] returns a string associated with CGI parameter fnm if there is any; raises ParamMissing(fnm) if no strings are associated with fnm. Equivalent to

```
case Mosmlcgi.cgi_field_string fnm of
    NONE => raise ParamMissing "fnm"
    | SOME v => v
```

In general, multiple strings may be associated with a CGI parameter; use Mosmlcgi.cgi_field_strings if you need to access all of them.

[%# fnm] returns the integer i if there is a string associated with CGI parameter fnm, and that string is parseable as ML integer i. Raises ParamMissing(fnm) if no string is associated with fnm. Raises NotInt(fnm, s) if there is a string but it is not parseable as an ML int.

[%%(fnm, dflt)] returns a string associated with CGI parameter fnm if there is any; otherwise returns the string dflt.

[%%#(fnm, dflt)] returns the integer i if there is a string associated with CGI parameter fnm, and that string is parseable as an ML int; otherwise returns the string dflt.

HTML generic marks:

[mark0 t] generates the HTML tag <t> as a wseq.

[mark0a attr t] generates the attributed HTML tag <t attr> as a wseq.

[mark1 t ws] generates <t>ws</t> as a wseq.

[mark1a attr t ws] generates <t attr>ws</t> as a wseq.

[comment ws] generates <!--ws--> as a wseq.

HTML documents and headers:

[html ws] generates <HTML>ws</HTML>.

[head ws] generates <HEAD>ws</HEAD>.

[title ws] generates <TITLE>ws</TITLE>.

[body ws] generates <BODY>ws</BODY>.

[bodya attr ws] generates <BODY attr>ws</BODY>.

[htmldoc titl ws] generates

```
<HTML><HEAD><TITLE>titl</TITLE></HEAD><BODY>ws</BODY></HTML>.
```

HTML headings and vertical format:

[h1 ws] generates <H1>ws</H1>.

[p ws] generates <P>ws</P>.

[pa attr ws] generates <P attr>ws</P>.

[br] generates
.

[bra attr] generates <BR attr>.

[hr] generates <HR>.

[hra attr] generates <HR attr>.

[divi ws] generates <DIV>ws</DIV>.

[divia attr ws] generates <DIV attr>ws</DIV>.

[blockquote ws] generates <BLOCKQUOTE>ws</BLOCKQUOTE>.

[blockquotea attr ws] generates <BLOCKQUOTE attr>ws</BLOCKQUOTE>

[center ws] generates <CENTER>ws</CENTER>.

[address ws] generates <ADDRESS>ws</ADDRESS>.

[pre ws] generates <PRE>ws</PRE>.

HTML anchors and hyperlinks:

[ahref link ws] generates ws.

[ahrefa link attr ws] generates ws.

[aname nam ws] generates ws.

HTML text formats and style:

[em ws] generates ws.

[strong ws] generates ws.

[tt ws] generates <TT>ws</TT>.

[sub ws] generates _{ws}.

[sup ws] generates ^{ws}.

[fonta attr ws] generates ws.

HTML lists:

[ul ws] generates ws.

```
[ula attr ws] generates <UL attr>ws</UL>.
[ol ws] generates <OL>ws</OL>.
[ola attr ws] generates <OL attr>ws</OL>.
[li ws] generates <LI>ws</LI>.
[dl ws] generates <DL>ws</DL>.
[dla attr ws] generates <DL attr>ws</DL>.
[dt ws] generates <DT>ws</DT>.
[dd ws] generates <DD>ws</DD>.
```

HTML tables:

```
[table ws] generates <TABLE>ws</TABLE>.
[tablea attr ws] generates <TABLE attr>ws</TABLE>.
[tr ws] generates <TR>ws</TR>.
[tra attr ws] generates <TR attr>ws</TR>.
[td ws] generates <TD>ws</TD>.
[tda attr ws] generates <TD attr>ws</TD>.
[th ws] generates <TH>ws</TH>.
[tha attr ws] generates <TH attr>ws</TH>.
[caption ws] generates <CAPTION>ws</CAPTION>.
[captiona attr ws] generates <CAPTION attr>ws</CAPTION>.
```

HTML images and image maps:

```
[img s] generates <IMG SRC="s">.
[imga s attr] generates <IMG SRC="s" attr>.
[map nam ws] generates <MAP NAME="name">ws</MAP>.
[mapa nam attr ws] generates <MAP NAME="name" attr>ws</MAP>.
[area { alt, coords, href, shape}] generates
    <AREA SHAPE="shape" COORDS="coords" HREF="link" ALT="desc">
when href is SOME link (where HREF is replaced by NOHREF otherwise)
and alt is SOME desc (where ALT is omitted otherwise).
```

HTML forms etc:

```
[form act ws] generates <FORM ACTION="act">ws</FORM>.
```

```
[forma act attr ws] generates <FORM ACTION="act" attr>ws</FORM>.

[input typ] generates <INPUT TYPE=typ>.

[inputa typ attr] generates <INPUT TYPE=typ attr>.

[intext name attr] generates <INPUT TYPE=TEXT NAME="name" attr>.

[inpassword name attr] generates <INPUT TYPE=PASSWORD NAME="name" attr>.

[incheckbox {name, value} attr] generates
<INPUT TYPE=CHECKBOX NAME="name" VALUE="value" attr>.

[inradio {name, value} attr] generates
<INPUT TYPE=RADIO NAME="name" VALUE="value" attr>.

[inreset value attr] generates <INPUT TYPE=RESET VALUE="value" attr>.

[insubmit value attr] generates <INPUT TYPE=SUBMIT VALUE="value" attr>.

[inhidden {name, value}] generates
<INPUT TYPE=HIDDEN NAME="name" VALUE="value">.

[textarea name ws] generates <TEXTAREA NAME="name">ws</TEXTAREA>.

[textareaa name attr ws] generates
<TEXTAREA NAME="name" attr>ws</TEXTAREA>.

[select name attr ws] generates <SELECT NAME="name" attr>ws</SELECT>.

[option value] generates <OPTION VALUE="value">.
```

HTML frames and framesets:

```
[frameset attr ws] generates <FRAMESET attr>ws</FRAMESET>.

[frame { src, name }] generates <FRAME SRC="src" NAME="name">.

[framea { src, name } attr] generates <FRAME SRC="src" NAME="name" attr>.
```

HTML encoding functions:

[urlencode s] returns the url-encoding of s. That is, space (ASCII 32) is replaced by '+' and every non-alphanumeric character c except the three characters hyphen (-), underscore (_) and full stop (.) is replaced by %hh, where hh is the hexadecimal representation of the ASCII code of c.

[htmlencode s] returns the html-encoding of s. That is, < and > are replaced by < and >, respectively, and & is replaced by &;

Module Mysql

Mysql -- interface to the MySQL database server -- requires Dynlib

type dbconn	<i>Connection to server</i>
type dbresult	<i>Result of a query</i>
eotype oid	<i>(not used by Mysql)</i>
exception Closed	<i>Connection is closed</i>
exception Null	<i>Field value is NULL</i>

Opening, closing, and maintaining database connections

```
val openbase : { dbhost    : string option,   database server host
                 dbname    : string option,   database name
                 dboptions: string option,  (not used by Mysql)
                 dbport    : string option,  database server port
                 dbpwd    : string option,  user passwd
                 dbtty    : string option,  (not used by Mysql)
                 dbuser    : string option, database user
               } -> dbconn

val closebase   : dbconn -> unit
val db          : dbconn -> string
val host        : dbconn -> string option
val options     : dbconn -> string
val port        : dbconn -> string
val tty         : dbconn -> string

val status      : dbconn -> bool
val reset       : dbconn -> unit
val errormessage: dbconn -> string option
```

Query execution and result set information

```
datatype dbresultstatus =
  | Bad_response           | (not used by Mysql)
  | Command_ok              | The query was a command
  | Copy_in                 | (not used by Mysql)
  | Copy_out                 | (not used by Mysql)
  | Empty_query              | (not used by Mysql)
  | Fatal_error              | (not used by Mysql)
  | Nonfatal_error           |
  | Tuples_ok                | The query successfully returned tuples

val execute      : dbconn -> string -> dbresult
val resultstatus : dbresult -> dbresultstatus
val ntuples      : dbresult -> int
val cmdtuples    : dbresult -> int
val nfields      : dbresult -> int
val fname        : dbresult -> int -> string
val fnames       : dbresult -> string vector
val fnumber      : dbresult -> string -> int option
```

Accessing the fields of a resultset

```
val getint       : dbresult -> int -> int -> int
val getreal      : dbresult -> int -> int -> real
val getstring    : dbresult -> int -> int -> string
val getdate      : dbresult -> int -> int -> int * int * int    Y M D
```

```

val gettime      : dbresult -> int -> int -> int * int * int   H M S
val getdatetime : dbresult -> int -> int -> Date.date
val getbool     : dbresult -> int -> int -> bool
val isnull      : dbresult -> int -> int -> bool

datatype dynval =
  Bool of bool                                (not used by MySQL)
  | Int of int                                 MySQL int4
  | Real of real                               MySQL float8 (float4)
  | String of string                          MySQL text (varchar)
  | Date of int * int * int                  MySQL date yyyy-mm-dd
  | Time of int * int * int                  MySQL time hh:mm:ss
  | DateTime of Date.date                    MySQL datetime
  | Oid of oid                                (not used by MySQL)
  | Bytea of Word8Array.array                (not used by MySQL)
  | NullVal                                    MySQL NULL value

val getdynfield  : dbresult -> int -> int -> dynval
val getdyntup    : dbresult -> int -> dynval vector
val getdyntups   : dbresult -> dynval vector vector
val dynval2s     : dynval -> string

```

Bulk copying to or from a table

```

val copytableto  : dbconn * string * (string -> unit) -> unit
val copytablefrom : dbconn * string * ((string -> unit) -> unit) -> unit

```

Some standard ML and MySQL types:

```

datatype dyntype =
  BoolTy          ML bool           (not used by MySQL)
  | IntTy          ML int            MySQL int4
  | RealTy         ML real           MySQL float8, float4
  | StringTy       ML string          MySQL text, varchar
  | DateTy         ML (yyyy, mth, day) MySQL date
  | TimeTy         ML (hh, mm, ss)    MySQL time
  | DateTimeTy    ML Date.date      MySQL datetime, abstime
  | OidTy          ML oid             (not used by MySQL)
  | ByteArrTy     ML Word8Array.array (not used by MySQL)
  | UnknownTy of oid

val fromtag : dyntype -> string
val ftype   : dbresult -> int -> dyntype
val ftypes  : dbresult -> dyntype Vector.vector

val applyto : 'a -> ('a -> 'b) -> 'b

```

Formatting the result of a database query as an HTML table

```

val formattable : dbresult -> Msp.wseq
val showquery   : dbconn -> string -> Msp.wseq

```

[dbconn] is the type of connections to a MySQL database.

[dbresult] is the type of result sets from MySQL queries.

[openbase { dbhost, dbport, dboptions, dbtty, dbname, dbuser, dbpwd }]
opens a connection to a MySQL database server on the given host

(default the local one) on the given port (default ?), to the given database (defaults to the user's login name), for the given user name (defaults to the current user's login name), and the given password (default none). The result is a connection which may be used in subsequent queries. In MySQL, unlike PostgreSQL, the dboptions and dbtty fields are not used.

[closebase dbconn] closes the database connection. No further queries can be executed.

[db dbconn] returns the name of the database.

[host dbconn] returns SOME h, where h is the database server host name, if the connection uses the Internet; returns NONE if the connection is to a socket on the local server.

[options dbconn] returns the options given when opening the database.

[port dbconn] returns the port number of the connection.

[tty dbconn] returns the name of the tty used for logging.

[status dbconn] returns true if the connection is usable, false otherwise.

[reset dbconn] attempts to close and then reopen the connection to the database server.

[errormessage dbconn] returns NONE if no error occurred, and SOME msg if an error occurred, where msg describes the error.

[execute dbconn query] sends an SQL query to the database server for execution, and returns a resultset dbres.

[resultstatus dbres] returns the status of the result set dbres. After a select query that succeeded, it will be Tuples_ok.

[ntuples dbres] returns the number of tuples in the result set after a query.

[cmdtuples dbres] returns the number of tuples affected by an insert, update, or delete SQL command.

[nfields dbres] returns the number of fields in each tuple after a query.

[fname dbres fno] returns the name of field number fno (in the result set after a query). The fields are numbered 0, 1, ...

[fnames dbres] returns a vector of the field names (in the result set after a query).

[fnumber dbres fname] returns SOME i where i is the number (0, 1, ...) of the field called fname (in the result set after a query), if the result set contains such a field name; returns NONE otherwise.

[ftype dbres fno] returns the dyntype of field number fno (in the result set after a query).

[ftypes dbres] returns a vector of the dyntypes (in the result set after a query).

[fromtag dt] returns the name of the preferred MySQL type used to represent values of the dyntype dt. This may be used when building 'create table' statements.

[getint dbres fno tupno] returns the integer value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[getreal dbres fno tupno] returns the floating-point value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[getstring dbres fno tupno] returns the string value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[getdate dbres fno tupno] returns the date (yyyy, mth, day) value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a date.

[gettime dbres fno tupno] returns the time-of-day (hh, mm, ss) value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a time.

[getdatetime dbres fno tupno] returns the Date.date value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a date.

[getbool dbres fno tupno] returns the boolean value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[isnull dbres fno tupno] returns true if the value of field number fno in tuple tupno of result set dbres is NULL; false otherwise.

[getdynfield dbres fno tupno] returns the value of field number fno in tuple tupno of result set dbres as a dynval (a wrapped value). A NULL value is returned as NullVal. Note that the partial application (getdynfield dbres fno) precomputes the type of the field fno. Hence it is far more efficient to compute

```
let val getfno = getdynfield dbres fno
  in tabulate(ntuples dbres, getfno) end
than to compute
let fun getfno tupno = getdynfield dbres fno tupno
  in tabulate(ntuples dbres, getfno) end
because the latter repeatedly computes the type of the field.
```

[getdyntup dbres tupno] returns the fields of tuple tupno in result set dbres as a vector of dynvals.

[getdyntups dbres] returns all tuples of result set dbres as a vector of vectors of dynvals.

[dynval2s dv] returns a string representing the dynval dv.

[applyto x f] computes f(x). This is convenient for applying several functions (given in a list or vector) to the same value:

```
    map (applyto 5) (tabulate(3, getdynfield dbres))
equals
[getdynfield dbres 0 5, getdynfield dbres 1 5, getdynfield dbres 2 5]

[copytableto(dbconn, tablename, put)] simulates a PostgreSQL "COPY
TABLE TO" statement, applies the function put to every tuple of the
table, represented as a line of text (not terminated by newline
\n), and cleans up at the end. For instance, to copy the contents
of a table t to a text stream s (one tuple on each line), define
  fun put line =
    (TextIO.output(s, line); TextIO.output(s, "\n"))
and execute
  copytableto(dbconn, "t", put).

[copytablefrom(dbconn, tablename, useput)] simulates a PostgreSQL
"COPY TABLE FROM" statement, creates a put function for copying
lines to the table, passes the put function to useput, and cleans
up at the end. The put function may be called multiple times for
each line (tuple); the end of each line is indicated by the
newline character "\n" as usual. For instance, to copy the
contents of a text stream s to a table t, define
  fun useput put =
    while not (TextIO.endOfStream s) do put(TextIO.inputLine s);
and execute
  copytablefrom(dbconn, "t", useput).
Note that TextIO.inputLine preserves the newline at the end of each
line.

[formattable dbresult] returns a wseq representing an HTML table.
The HTML table has a column for every field in the dbresult. The
first row is a table header giving the names of the fields in the
dbresult. The remaining rows correspond to the tuples in the
dbresult, in the order they are provided by the database server.
Null fields are shown as NULL.

[showquery dbconn query] sends the SQL query to the database
server, then uses formattable to format the result of the query.
```

Module NJ93

NJ93 -- compatibility SML/NJ 0.93 top-level environment

val print : string -> unit

NJ93 Integer

val max : int * int -> int
 val min : int * int -> int

NJ93 List

exception Hd and Tl and Nth and NthTail

val hd : 'a list -> 'a *Hd*
 val tl : 'a list -> 'a list *Tl*
 val nth : 'a list * int -> 'a *Nth*
 val nthtail : 'a list * int -> 'a list *NthTail*
 val app : ('a -> 'b) -> 'a list -> unit
 val revapp : ('a -> 'b) -> 'a list -> unit
 val fold : ('a * 'b -> 'b) -> 'a list -> 'b -> 'b
 val revfold : ('a * 'b -> 'b) -> 'a list -> 'b -> 'b

NJ93 Real

val ceiling : real -> int
 val truncate : real -> int

NJ93 Ref

val inc : int ref -> unit
 val dec : int ref -> unit

NJ93 String

exception Substring

val ordof : string * int -> int
 val ord : string -> int *Ord*
 val chr : int -> string *Chr*
 val substring : string * int * int -> string *Substring*
 val explode : string -> string list
 val implode : string list -> string

NJ93 top-level math functions

val sqrt : real -> real
 val sin : real -> real
 val cos : real -> real
 val arctan : real -> real
 val exp : real -> real
 val ln : real -> real

NJ93 top-level input/output, standard

type instream and outstream

val std_in : instream
 val open_in : string -> instream
 val input : instream * int -> string

```
val lookahead      : instream -> string
val close_in       : instream -> unit
val end_of_stream : instream -> bool

val std_out        : outstream
val open_out        : string -> outstream
val output         : outstream * string -> unit
val close_out       : outstream -> unit
```

NJ93 top-level input/output, non-standard

```
val open_in_bin   : string -> instream
val open_out_bin  : string -> outstream
val inputc        : instream -> int -> string
val std_err        : outstream
val outputc       : outstream -> string -> unit
val flush_out     : outstream -> unit
val input_line    : instream -> string
val can_input     : instream * int -> bool
val open_append   : string -> outstream
```

Module Nonstdio

Nonstdio -- non-standard I/O -- use BinIO and TextIO instead

```
local open BasicIO in

  val open_in_bin      : string -> instream
  val buff_input       : instream -> CharArray.array -> int -> int -> int
  val input_char        : instream -> char Raises Size
  val input_binary_int : instream -> int
  val input_value       : instream -> 'a
  val seek_in           : instream -> int -> unit
  val pos_in            : instream -> int
  val in_stream_length : instream -> int
  val fast_really_input: instream -> string -> int -> int -> unit

  val open_out_bin     : string -> outstream
  val open_out_exe     : string -> outstream
  val output_char       : outstream -> Char.char -> unit
  val output_byte       : outstream -> int -> unit
  val buff_output       : outstream -> CharArray.array -> int -> int -> unit
  val output_binary_int: outstream -> int -> unit
  val output_value      : outstream -> 'a -> unit
  val seek_out          : outstream -> int -> unit
  val pos_out           : outstream -> int

  val file_exists      : string -> bool

end
```

Module OS

```
OS -- SML Basis Library
signature OS = sig
  type syserror = syserror
  exception SysErr of string * syserror option
  val errorMsg      : syserror -> string
  structure FileSys : FileSys
  structure Path    : Path
  structure Process : Process
end
```

[errorMsg err] returns a string explaining the error message system error code err, as found in a SysErr exception. The precise form of the string depends on the operating system.

Module Option

Option -- SML Basis Library

exception Option

datatype option = datatype option

```
val getOpt      : 'a option * 'a -> 'a
val isSome     : 'a option -> bool
val valOf      : 'a option -> 'a
val filter     : ('a -> bool) -> 'a -> 'a option
val map        : ('a -> 'b) -> 'a option -> 'b option
val app        : ('a -> unit) -> 'a option -> unit
val join       : 'a option option -> 'a option
val compose    : ('a -> 'b) * ('c -> 'a option) -> ('c -> 'b option)
val mapPartial : ('a -> 'b option) -> ('a option -> 'b option)
val composePartial : ('a -> 'b option) * ('c -> 'a option) -> ('c -> 'b option)
```

[getOpt (xopt, d)] returns x if xopt is SOME x; returns d otherwise.

[isSome vopt] returns true if xopt is SOME x; returns false otherwise.

[valOf vopt] returns x if xopt is SOME x; raises Option otherwise.

[filter p x] returns SOME x if p x is true; returns NONE otherwise.

[map f xopt] returns SOME (f x) if xopt is SOME x; returns NONE otherwise.

[app f xopt] applies f to x if xopt is SOME x; does nothing otherwise.

[join xopt] returns x if xopt is SOME x; returns NONE otherwise.

[compose (f, g) x] returns SOME (f y) if g x is SOME y; returns NONE otherwise. It holds that compose (f, g) = map f o g.

[mapPartial f xopt] returns f x if xopt is SOME x; returns NONE otherwise. It holds that mapPartial f = join o map f.

[composePartial (f, g) x] returns f y if g x is SOME y; returns NONE otherwise. It holds that composePartial (f, g) = mapPartial f o g.

The operators (map, join, SOME) form a monad.

Module PP

```
PP -- pretty-printing -- from the SML/NJ library

type ppconsumer = { consumer : string -> unit,
                     linewidth : int,
                     flush      : unit -> unit }

datatype break_style =
  CONSISTENT
 | INCONSISTENT

val mk_ppstream    : ppconsumer -> ppstream
val dest_ppstream : ppstream -> ppconsumer
val add_break     : ppstream -> int * int -> unit
val add_newline   : ppstream -> unit
val add_string    : ppstream -> string -> unit
val begin_block   : ppstream -> break_style -> int -> unit
val end_block     : ppstream -> unit
val clear_ppstream: ppstream -> unit
val flush_ppstream: ppstream -> unit
val with_pp       : ppconsumer -> (ppstream -> unit) -> unit
val pp_to_string  : int -> (ppstream -> 'a -> unit) -> 'a -> string
```

This structure provides tools for creating customized Oppen-style pretty-printers, based on the type ppstream. A ppstream is an output stream that contains prettyprinting commands. The commands are placed in the stream by various function calls listed below.

The following primitives add commands to the stream:
begin_block, end_block, add_string, add_break, and add_newline.
All calls to add_string, add_break, and add_newline must happen between a pair of calls to begin_block and end_block must be properly nested dynamically. All calls to begin_block and end_block must be properly nested (dynamically).

[ppconsumer] is the type of sinks for pretty-printing. A value of type ppconsumer is a record
{ consumer : string -> unit,
 linewidth : int,
 flush : unit -> unit }
of a string consumer, a specified linewidth, and a flush function which is called whenever flush_ppstream is called.

A prettyprinter can be called outright to print a value. In addition, a prettyprinter for a base type or nullary datatype ty can be installed in the top-level system. Then the installed prettyprinter will be invoked automatically whenever a value of type ty is to be printed.

[break_style] is the type of line break styles for blocks:

[CONSISTENT] specifies that if any line break occurs inside the block, then all indicated line breaks occur.

[INCONSISTENT] specifies that breaks will be inserted to only to avoid overfull lines.

[mk_ppstream {consumer, linewidth, flush}] creates a new ppstream which invokes the consumer to output text, putting at most

linewidth characters on each line.

[dest_ppstream ppstrm] extracts the linewidth, flush function, and consumer from a ppstream.

[add_break ppstrm (size, offset)] notifies the pretty-printer that a line break is possible at this point.

* When the current block style is CONSISTENT:

- ** if the entire block fits on the remainder of the line, then output size spaces; else
- ** increase the current indentation by the block offset; further indent every item of the block by offset, and add one newline at every add_break in the block.

* When the current block style is INCONSISTENT:

- ** if the next component of the block fits on the remainder of the line, then output size spaces; else
- ** issue a newline and indent to the current indentation level plus the block offset plus the offset.

[add_newline ppstrm] issues a newline.

[add_string ppstrm str] outputs the string str to the ppstream.

[begin_block ppstrm style blockoffset] begins a new block and level of indentation, with the given style and block offset.

[end_block ppstrm] closes the current block.

[clear_ppstream ppstrm] restarts the stream, without affecting the underlying consumer.

[flush_ppstream ppstrm] executes any remaining commands in the ppstream (that is, flushes currently accumulated output to the consumer associated with ppstrm); executes the flush function associated with the consumer; and calls clear_ppstream.

[with_pp consumer f] makes a new ppstream from the consumer and applies f (which can be thought of as a producer) to that ppstream, then flushes the ppstream and returns the value of f.

[pp_to_string linewidth printit x] constructs a new ppstream ppstrm whose consumer accumulates the output in a string s. Then it evaluates (printit ppstrm x) and finally returns the string s.

Example 1: A simple prettyprinter for Booleans:

```
load "PP";
fun ppbool pps d =
  let open PP
  in
    begin_block pps INCONSISTENT 6;
    add_string pps (if d then "right" else "wrong");
    end_block pps
  end;
```

Now one may define a ppstream to print to, and exercise it:

```
val ppstrm = PP.mk_ppstream {consumer =
  fn s => TextIO.output(TextIO.stdOut, s),
  linewidth = 72,
```

```

flush      =
fn () => TextIO.flushOut TextIO.stdOut};

fun ppb b = (ppbool ppstrm b; PP.flush_ppstream ppstrm);

- ppb false;
wrong> val it = () : unit

```

The prettyprinter may also be installed in the toplevel system;
then it will be used to print all expressions of type bool
subsequently computed:

```

- installPP ppbool;
> val it = () : unit
- l=0;
> val it = wrong : bool
- l=1;
> val it = right : bool

```

See library Meta for a description of installPP.

Example 2: Prettyprinting simple expressions (examples/pretty/ppexpr.sml):

```

datatype expr =
  Cst of int
  | Neg of expr
  | Plus of expr * expr

fun ppexpr pps e0 =
  let open PP
    fun ppe (Cst i)      = add_string pps (Int.toString i)
    | ppe (Neg e)        = (add_string pps "~"; ppe e)
    | ppe (Plus(e1, e2)) = (begin_block pps CONSISTENT 0;
                             add_string pps "(";
                             ppe e1;
                             add_string pps " + ";
                             add_break pps (0, 1);
                             ppe e2;
                             add_string pps ")");
                             end_block pps)
  in
    begin_block pps INCONSISTENT 0;
    ppe e0;
    end_block pps
  end

val _ = installPP ppexpr;

```

Some example values:

```

val e1 = Cst 1;
val e2 = Cst 2;
val e3 = Plus(e1, Neg e2);
val e4 = Plus(Neg e3, e3);
val e5 = Plus(Neg e4, e4);
val e6 = Plus(e5, e5);
val e7 = Plus(e6, e6);
val e8 =
  Plus(e3, Plus(e3, Plus(e3, Plus(e3, Plus(e3, Plus(e3, e7))))));

```

Module Parsing

*Parsing -- runtime library for parsers generated by mosmlyac
Based on the runtime library for camlyacc; copyright 1993 INRIA, France*

```
local open Vector Obj Lexing in
```

```
val symbolStart : unit -> int
val symbolEnd   : unit -> int
val itemStart   : int -> int
val itemEnd    : int -> int
val clearParser : unit -> unit
```

For internal use in generated parsers:

```
type parseTables =
  actions      (unit -> obj) vector *
  transl       int vector *
  lhs          string *
  len          string *
  defred       string *
  dgoto        string *
  sindex       string *
  rindex       string *
  gindex       string *
  tablesizer  int *
  table        string *
  check        string

exception yyexit of obj
exception ParseError of (obj -> bool)

val yyparse : parseTables -> int -> (lexbuf -> 'a) -> lexbuf -> 'b
val peekVal : int -> 'a

end
```

These functions are for use in mosmlyac-generated parsers. For further information, see the Moscow ML Owner's Manual. For examples, see mosml/examples/lexyacc and mosml/examples/calc.

A grammar definition (input to mosmlyac) consists of fragments of this form

```
nonterm :
  grsyms1 { action1 }
  | grsyms2 { action2 }
  | grsyms3 { action3 }
  | ...
```

where the grsyms are sequences of grammar symbols, matching some string of characters, and the actions are corresponding semantic actions, written in ML. The following functions can be used in the semantic actions:

[symbolStart ()] returns the start position of the string that matches the sequence of grammar symbols. The first character in the input stream has position 0. May be called in a semantic action only.

[symbolEnd ()] returns the end position, plus one, of the string that matches the sequence of grammar symbols. The first character in the input stream has position 0. May be called in a semantic action only.

[itemStart i] returns the start position of the string that matches the i'th grammar symbol in the sequence. The first grammar symbol has number 1. The first character in the input stream has position 0. May be called in a semantic action only.

[itemEnd i] returns the end position, plus one, of the string that matches the i'th grammar symbol in the sequence. The first grammar symbols has number 1. The first character in the input stream has position 0. May be called in a semantic action only.

[clearParser ()] clears the parser stack. It may be called after a parsing function has returned, to remove all pointers from the parser stack to structures that were built by semantic actions during parsing. This is not strict necessary, but reduces the memory requirements of the program.

Module Path

```
OS.Path -- SML Basis Library

exception Path

val parentArc    : string
val currentArc   : string

val fromString   : string -> {isAbs : bool, vol : string, arcs : string list}
val toString     : {isAbs : bool, vol : string, arcs : string list} -> string

val getVolume    : string -> string
val validVolume  : {isAbs : bool, vol : string} -> bool
val getParent    : string -> string

val isAbsolute   : string -> bool
val isRelative   : string -> bool
val isRoot       : string -> bool
val mkAbsolute   : {path : string, relativeTo : string} -> string
val mkRelative   : {path : string, relativeTo : string} -> string

val concat       : string * string -> string

val mkCanonical : string -> string
val isCanonical : string -> bool

val splitDirFile: string -> {dir : string, file : string}
val joinDirFile : {dir : string, file : string} -> string
val dir         : string -> string
val file        : string -> string

val splitBaseExt: string -> {base : string, ext : string option}
val joinBaseExt : {base : string, ext: string option} -> string
val base        : string -> string
val ext         : string -> string

exception InvalidArc
val fromUnixPath: string -> string
val toUnixPath  : string -> string
```

This module provides OS-independent functions for manipulating strings that represent file names and paths in a directory structure. None of these functions accesses the actual filesystem.

Definitions:

- * An arc denotes a directory or file. Under Unix or DOS, an arc may have form "...", ".", "", or "abc", or similar.
- * An absolute path has a root: Unix examples include "/", "/a/b"; DOS examples include "\", "\a\b", "A:\a\b".
- * A relative path is one without a root: Unix examples include "...", "a/b"; DOS examples include "...", "a\b", "A:a\b".
- * A path has an associated volume. Under Unix, there is only one volume, whose name is "". Under DOS, the volume names are "", "A:", "C:", and similar.

* A canonical path contains no occurrences of the empty arc "" or the current arc ".", and contains or the parent arc ".." only at the beginning and only if the path is relative.

* All functions (except concat) preserve canonical paths. That is, if all arguments are canonical, then so will the result be.

* All functions are defined so that they work sensibly on canonical paths.

* There are three groups of functions, corresponding to three ways to look at paths, exemplified by the following paths:

Unix: d/e/f/a.b.c	and	/d/e/f/a.b.c
DOS: A:d\ e\f\ a.b.c	and	A:\d\ e\f\ a.b.c

- (1) A path consists of a sequence of arcs, possibly preceded by a volume and a root:

vol [--- arcs ---]	vol root [--- arcs ---]
-----	-----
Unix examples: d e f a.b.c	/ d e f a.b.c
DOS examples: A: d e f a.b	A: \ d e f a.b

- (2) A path consists of a directory part and a (last) file name part:

directory file	directory file
-----	-----
Unix examples: d/e/f a.b.c	/d/e/f a.b.c
DOS examples: A:d\ e\f a.b	A:\d\ e\f a.b

- (3) A path consists of a base and an extension:

base extension	base extension
-----	-----
Unix examples: d/e/f/a.b c	/d/e/f/a.b c
DOS examples: A:d\ e\f\ a b	A:\d\ e\f\ a b

GROUP 0: General functions on paths:

[parentArc] is the arc denoting a parent directory: ".." under DOS and Unix.

[currentArc] is the arc denoting the current directory: "." under DOS and Unix.

[isRelative p] returns true if p is a relative path.

[isAbsolute p] returns true if p is an absolute path.
Equals not (isRelative p).

[isRoot p] returns true if p is a canonical specification of a root directory. That is, if p is an absolute path with no arcs.

[validVolume {isAbs, vol}] returns true if vol is a valid volume name for an absolute path (if isAbs=true) resp. for a relative path (if isAbs=false). Under Unix, the only valid volume name is ""; under MS DOS and MS Windows the valid volume names are "", "a:", "b:", ..., and "A:", "B:", ...

[getParent p] returns a string denoting the parent directory of p. It holds that getParent p = p if and only if p is a root.

[concat (p1, p2)] returns the path consisting of p1 followed by p2. Does not preserve canonical paths: concat("a/b", "../c") equals "a/b/../c". This is because "a/b/../c" and "a/c" may not be equivalent in the presence of symbolic links. Raises Path if p2 is not a relative path.

[mkAbsolute { path=p1, relativeTo=p2 }] returns the absolute path made by taking path p2, then p1. That is, returns p1 if p1 is absolute; otherwise returns the canonicalized concatenation of p2 and p1. Raises Path if p2 is not absolute (even if p1 is absolute).

[mkRelative { path=p1, relativeTo=p2 }] returns p1 relative to p2. That is, returns p1 if p1 is already relative; otherwise returns the relative path leading from p2 to p1. Raises Path if p2 is not absolute (and even if p1 is relative), or if p1 and p2 are both absolute but have different roots.

[mkCanonical p] returns a canonical path which is equivalent to p. Redundant occurrences of the parent arc, the current arc, and the empty arc are removed. The canonical path will never be the empty string; the empty path is converted to the current directory path ("." under Unix and DOS).

[isCanonical p] is equal to (p = mkCanonical p).

GROUP 1: Manipulating volumes and arcs:

[fromString p] returns {isAbs=false, vol, arcs} if the path p is relative, and {isAbs=true, vol, arcs} if the path p is absolute. In both cases vol is the volume name and arcs is the list of (possibly empty) arcs of the path. Under Unix, the volume name is always the empty string ""; under DOS it will have form "A:", "C:", or similar.

[toString path] reconstitutes a path from its root (if any) and arcs. Raises Path if applied to a relative path whose first arc is empty. It holds that toString(fromString p) = p, except that in MS DOS, slashes "/" in p will be replaced by backslashes "\". It holds that fromString (toString p) = p when no exception is raised. It holds that isRelative(toString {isAbs=false, vol, arcs}) = true when no exception is raised.

[getVolume p] returns the volume name of the path p, if given. Under Unix and MacOS, this is always the empty string "", and under MS DOS and MS Windows, it may have form "A:", "B:", ...

GROUP 2: Manipulating directory paths and file names:

[splitDirFile p] returns {dir, file} where file is the last arc in p, and dir is the path preceding that arc. A typical use is to split a path into the directory part (dir) and the filename (file).

[joinDirFile {dir, file}] returns the path p obtained by extending the path dir with the arc file.

```
[dir p] equals #dir (splitDirFile p).  
[file p] equals #file (splitDirFile p).
```

GROUP 3: Manipulating file names and extensions:

[splitBaseExt s] returns {base, ext} where ext = NONE if s has no extension, and ext = SOME e if s has extension e; base is the part of s preceding the extension. A path s is considered having no extension if its last arc contains no extension separator (typically ".") or contains an extension separator only as its leftmost character, or contains an extension separator as its right-most character. Hence none of "a.b/cd", "a/.login", "a.", "..", ".", and "." has an extension.

[joinBaseExt {base, ext}] returns an arc composed of the base name and the extension (if different from NONE). It is a left inverse of splitBaseExt, so joinBaseExt (splitBaseExt s) = s, but the opposite does not hold (since the extension may be empty, or may contain extension separators).

```
[ext s] equals #ext (splitBaseExt s).  
[base s] equals #base (splitBaseExt s).
```

GROUP 4: Convenience functions for manipulating Unix-style paths.

[fromUnixPath s] returns a path in the style of the host OS from the Unix-style path s. Slash characters are translated to the directory separators of the local system, as are parent arcs and current arcs. Raises InvalidArc if any arc in s is invalid in the host OS's path syntax.

[toUnixPath s] returns a Unix-style path from the path s in the style of the host OS. If the path s has a non-empty volume name, then the Path exception is raised. Raises InvalidArc if any arc contains a slash character.

Module Polygdbm

```
Polygdbm -- GNU gdbm persistent polymorphic hashtables -- requires Dynlib
type ('key, 'data) table

exception NotFound
exception AlreadyThere
exception NotWriter
exception Closed
exception GdbmError of string

val withtable : string * Gdbm.openmode -> (('key, 'data) table -> 'a) -> 'a
val add      : ('key, 'data) table -> 'key * 'data -> unit
val insert   : ('key, 'data) table -> 'key * 'data -> unit
val find     : ('key, 'data) table -> 'key -> 'data
val peek     : ('key, 'data) table -> 'key -> 'data option
val hasKey   : ('key, 'data) table -> 'key -> bool
val remove   : ('key, 'data) table -> 'key -> unit
val listKeys : ('key, 'data) table -> 'key list
val numItems : ('key, 'data) table -> int
val listItems: ('key, 'data) table -> ('key * 'data) list
val app      : ('key * 'data -> unit) -> ('key, 'data) table -> unit
val map      : ('key * 'data -> 'a) -> ('key, 'data) table -> 'a list
val fold     : ('key * 'data * 'a -> 'a) -> 'a -> ('key, 'data) table -> 'a
val fastwrite: bool ref
val reorganize: ('key, 'data) table -> unit
```

[('key, 'data) table] is the type of an opened table with keys of type 'key and associated values of type 'data. The actual values of type 'key and 'data cannot contain function closures or abstract values. Values involving references (even circular values) can be stored, but the identity of references is preserved only with every single key or value stored, not across several different values.

The Polygdbm table files are not portable across platforms, because word size and endianness affects the lay-out of values.

A value of type table can be used only in the argument f to the withtable function. This makes sure that the table is closed after use.

[withtable (nam, mod) f] first opens the table db in file nam with mode mod, then applies f to db, then closes db. Makes sure to close db even if an exception is raised during the evaluation of f(db). Raises GdbmError with an informative message in case the table cannot be opened. E.g. the table cannot be opened for reading if already opened for writing, and cannot be opened for writing if already opened for reading.

[add db (k,v)] adds the pair (k, v) to db. Raises AlreadyThere if there is a pair (k, _) in db already. Raises NotWriter if db is not opened in write mode.

[insert db (k, v)] adds the pair (k, v) to db, replacing any pair (k, _) at k if present. Raises NotWriter if db is not opened in write mode.

[find(db, k)] returns v if the pair (k, v) is in db; otherwise raises NotFound.

[peek db k] returns SOME v if the pair (k, v) is in db; otherwise returns NONE.

[hasKey(db, k)] returns true if there is a pair (k, _) in db; otherwise returns false.

[remove db k] deletes the pair (k, _) from the table if present; otherwise raises NotFound. Raises NotWriter if db is not opened in write mode.

[listKeys db] returns a list of all keys in db in an unspecified order.

[numItems db] is the number of (key, value) pairs in db.
Equivalent to length(listKeys db).

[listItems db] returns a list of all (key, value) pairs in db in some order. Equivalent to

```
List.map (fn key => (key, find(db, key))) (listKeys db)
```

[app f db] is equivalent to List.app f (listItems db), provided the function f does not change the set of keys in the table.
Otherwise the effect is unpredictable.

[map f db] is equivalent to List.map f (listItems db), provided the function f does not change the set of keys in the table.
Otherwise the result and effect are unpredictable.

[fold f a db] is equivalent to
List.foldr (fn ((k, v), r) => f(k, v, r)) a (listItems db)
provided the function f does not change the set of keys in the table. Otherwise the result and effect are unpredictable.

[fastwrite] can be set to speed up writes to a table. By default, !fastwrite is false and every write to a table will be followed by file system synchronization. This is safe, but slow if you perform thousands of writes. However, if !fastwrite is true when calling withtable, then writes may not be followed by synchronization, which may speed up writes considerably. In any case, the file system is synchronized before withtable returns.

[reorganize db] has no visible effect, but may be called after a lot of deletions to shrink the size of the table file.

Module Polyhash

Polyhash -- polymorphic hashtables as in the SML/NJ Library

```
type ('key, 'data) hash_table

val mkTable      : ('_key -> int) * ('_key * '_key -> bool) -> int * exn
                  -> ('_key, '_data) hash_table
val numItems    : ('key, 'data) hash_table -> int
val insert      : ('_key, '_data) hash_table -> '_key * '_data -> unit
val peekInsert  : ('_key, '_data) hash_table -> '_key * '_data
                  -> '_data option
val find        : ('key, 'data) hash_table -> 'key -> 'data
val peek        : ('key, 'data) hash_table -> 'key -> 'data option
val remove      : ('key, 'data) hash_table -> 'key -> 'data
val listItems   : ('key, 'data) hash_table -> ('key * 'data) list
val apply       : ('key * 'data -> unit) -> ('key, 'data) hash_table -> unit
val map         : ('_key * 'data -> '_res) -> ('_key, '_data) hash_table
                  -> ('_key, '_res) hash_table
val filter      : ('key * 'data -> bool) -> ('key, 'data) hash_table -> unit
val transform   : ('data -> '_res) -> ('_key, '_data) hash_table
                  -> ('_key, '_res) hash_table
val copy        : ('_key, '_data) hash_table -> ('_key, '_data) hash_table
val bucketSizes : ('key, 'data) hash_table -> int list
```

Polymorphic hash primitives from Caml Light

```
val hash        : 'key -> int
val hash_param : int -> int -> 'key -> int
val mkPolyTable : int * exn -> ("_key, '_data) hash_table
```

[('key, 'data) hash_table] is the type of hashtables with keys of type '`'key` and data values of type '`'data`.

[`mkTable (hashVal, sameKey) (sz, exc)`] returns a new hashtable, using hash function `hashVal` and equality predicate `sameKey`. The `sz` is a size hint, and `exc` is the exception raised by function `find`. It must be the case that `sameKey(k1, k2)` implies `hashVal(k1) = hashVal(k2)` for all `k1, k2`.

[`numItems htbl`] is the number of items in the hash table.

[`insert htbl (k, d)`] inserts data `d` for key `k`. If `k` already had an item associated with it, then the old item is overwritten.

[`find htbl k`] returns `d`, where `d` is the data item associated with key `k`, or raises the exception (given at creation of `htbl`) if there is no such `d`.

[`peek htbl k`] returns `SOME d`, where `d` is the data item associated with key `k`, or `NONE` if there is no such `d`.

[`peekInsert htbl (k, d)`] inserts data `d` for key `k`, if `k` is not already in the table, returning `NONE`. If `k` is already in the table, and the associated data value is `d'`, then returns `SOME d'` and leaves the table unmodified.

[`remove htbl k`] returns `d`, where `d` is the data item associated with key `k`, removing `d` from the table; or raises the exception if there is no such `d`.

[`listItems htbl`] returns a list of the (key, data) pairs in the hashtable.

[apply f htbl] applies function f to all (key, data) pairs in the hashtable, in some order.

[map f htbl] returns a new hashtable, whose data items have been obtained by applying f to the (key, data) pairs in htbl. The new tables have the same keys, hash function, equality predicate, and exception, as htbl.

[filter p htbl] deletes from htbl all data items which do not satisfy predicate p.

[transform f htbl] as map, but only the (old) data values are used when computing the new data values.

[copy htbl] returns a complete copy of htbl.

[bucketSizes htbl] returns a list of the sizes of the buckets. This is to allow users to gauge the quality of their hashing function.

[hash k] returns the hash value of k, as a positive integer. If k1=k2 then hash(k1) = hash(k2), so this function can be used when creating hashtables. The application hash(k) always terminates, even on cyclic structures. (From the Caml Light implementation).

[hash_param n m k] computes a hash value for k with the same properties as for hash. The parameters n and m give more precise control over hashing. Hashing performs a depth-first, right-to-left traversal of the structure k, stopping after n meaningful nodes were encountered, or m nodes, meaningful or not, were encountered. Meaningful nodes are: integers, floating-point numbers, strings, characters, booleans, references, and constant constructors.

[mkPolyTable (sz, exc)] creates a new hashtable using the polymorphic hash function (hash) and ML equality (op =); the integer sz is a size hint and the exception exc is to be raised by find.

Module Postgres

Postgres -- interface to PostgreSQL database server -- requires Dynlib

```
type dbconn                      Connection to server
type dbresult                     Result of a query
eqtype oid                        Internal object id
```

```
exception Closed                  Connection is closed
exception Null                   Field value is NULL
```

Opening, closing, and maintaining database connections

```
val openbase : { dbhost      : string option,   database server host
                 dbname      : string option,   database name
                 dboptions   : string option,   options
                 dbport       : string option,   database server port
                 dbpwd        : string option,   user passwd
                 dbtty        : string option,   tty for error log
                 dbuser       : string option,   database user
               } -> dbconn
```

```
val closebase    : dbconn -> unit
val db           : dbconn -> string
val host         : dbconn -> string option
val options      : dbconn -> string
val port         : dbconn -> string
val tty          : dbconn -> string
```

```
val status        : dbconn -> bool
val reset         : dbconn -> unit
val errormessage : dbconn -> string option
```

Query execution and result set information

```
datatype dbresultstatus =
  | Bad_response           An unexpected response was received
  | Command_ok              The query was a command
  | Copy_in                 The query was "copy <table> from ..."
  | Copy_out                The query was "copy <table> to ..."
  | Empty_query
  | Fatal_error
  | Nonfatal_error
  | Tuples_ok               The query successfully returned tuples
```

```
val execute      : dbconn -> string -> dbresult
val resultstatus : dbresult -> dbresultstatus
val ntuples      : dbresult -> int
val cmdntuples   : dbresult -> int
val nfields      : dbresult -> int
val fname        : dbresult -> int -> string
val fnames       : dbresult -> string vector
val fnumber      : dbresult -> string -> int option
```

Accessing the fields of a resultset

```
val getint        : dbresult -> int -> int -> int
val getreal       : dbresult -> int -> int -> real
val getstring     : dbresult -> int -> int -> string
val getdate       : dbresult -> int -> int -> int * int * int    Y M D
```

```

val gettime      : dbresult -> int -> int -> int * int * int   H M S
val getdatetime : dbresult -> int -> int -> Date.date
val getbool     : dbresult -> int -> int -> bool
val isnull      : dbresult -> int -> int -> bool

datatype dynval =
  Bool of bool                                psql bool
  | Int of int                                 psql int4
  | Real of real                             psql float8, float4
  | String of string                         psql text, varchar
  | Date of int * int * int                 psql date yyyy-mm-dd
  | Time of int * int * int                 psql time hh:mm:ss
  | DateTime of Date.date                   psql datetime
  | Oid of oid                               psql oid
  | Bytea of Word8Array.array               psql bytea
  | NullVal                                  psql NULL

val getdynfield : dbresult -> int -> int -> dynval
val getdyntup  : dbresult -> int -> dynval vector
val getdyntups : dbresult -> dynval vector vector
val dynval2s   : dynval -> string

```

Bulk copying to or from a table

```

val copytableto  : dbconn * string * (string -> unit) -> unit
val copytablefrom : dbconn * string * ((string -> unit) -> unit) -> unit

```

Some standard ML and Postgres types:

```

datatype dyntype =
  BoolTy          ML bool           psql bool
  | IntTy          ML int            psql int4
  | RealTy         ML real           psql float8, float4
  | StringTy       ML string         psql text, varchar
  | DateTy         ML (yyyy, mth, day) psql date
  | TimeTy         ML (hh, mm, ss)    psql time
  | DateTimeTy    ML Date.date      psql datetime, abstime
  | OidTy          ML oid             psql oid
  | ByteArrTy     ML Word8Array.array psql bytea
  | UnknownTy of oid

val fromtag : dyntype -> string
val ftype   : dbresult -> int -> dyntype
val ftypes  : dbresult -> dyntype Vector.vector

val applyto : 'a -> ('a -> 'b) -> 'b

```

Formatting the result of a database query as an HTML table

```

val formattable : dbresult -> Msp.wseq
val showquery   : dbconn -> string -> Msp.wseq

```

(Technical warning: This expects the PostgreSQL server to use ISO date format, such as 2002-07-25. Also, if the PostgreSQL server was compiled with support for multibyte-encodings (Unicode), the database must be created with
 createdb -E LATIN1 <dbname>

or you should set the environment variable PGCLIENTENCODING to LATIN1 in the SML program's environment.)

[dbconn] is the type of connections to a PostgreSQL database.

[dbresult] is the type of result sets from SQL queries.

[oid] is the type of PostgreSQL internal object identifiers.

[openbase { dbhost, dbport, dboptions, dbtty, dbname, dbuser, dbpwd }] opens a connection to a PostgreSQL database server on the given host (default the local one) on the given port (default 5432), with the given options (default the empty string), with error logging on the given tty (default?), to the given database (defaults to the user's login name), for the given user name (defaults to the current user's login name), and the given password (default none). The result is a connection which may be used in subsequent queries.

[closebase dbconn] closes the database connection. No further queries can be executed.

[db dbconn] returns the name of the database.

[host dbconn] returns SOME h, where h is the database server host name, if the connection uses the Internet; returns NONE if the connection is to a socket on the local server.

[options dbconn] returns the options given when opening the database.

[port dbconn] returns the port number of the connection.

[tty dbconn] returns the name of the tty used for logging.

[status dbconn] returns true if the connection is usable, false otherwise.

[reset dbconn] attempts to close and then reopen the connection to the database server.

[errormessage dbconn] returns NONE if no error occurred, and SOME msg if an error occurred, where msg describes the error.

[execute dbconn query] sends an SQL query to the database server for execution, and returns a resultset dbres.

[resultstatus dbres] returns the status of the result set dbres. After a select query that succeeded, it will be Tuples_ok.

[ntuples dbres] returns the number of tuples in the result set after a query.

[cmdtuples dbres] returns the number of tuples affected by an insert, update, or delete SQL command.

[nfields dbres] returns the number of fields in each tuple after a query.

[fname dbres fno] returns the name of field number fno (in the result set after a query). The fields are numbered 0, 1, ...

[fnames dbres] returns a vector of the field names (in the result

set after a query).

[fnumber dbres fname] returns SOME i where i is the number (0, 1, ...) of the field called fname (in the result set after a query), if the result set contains such a field name; returns NONE otherwise.

[ftype dbres fno] returns the dyntype of field number fno (in the result set after a query).

[ftypes dbres] returns a vector of the dyntypes (in the result set after a query).

[fromtag dt] returns the name of the preferred PostgreSQL type used to represent values of the dyntype dt. This may be used when building 'create table' statements.

[getint dbres fno tupno] returns the integer value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[getreal dbres fno tupno] returns the floating-point value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[getstring dbres fno tupno] returns the string value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[getdate dbres fno tupno] returns the date (yyyy, mth, day) value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a date.

[gettime dbres fno tupno] returns the time-of-day (hh, mm, ss) value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a time.

[getdatetime dbres fno tupno] returns the Date.date value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL. Raises Fail if the field cannot be scanned as a date.

[getbool dbres fno tupno] returns the boolean value of field number fno in tuple tupno of result set dbres. Raises Null if the value is NULL.

[isnull dbres fno tupno] returns true if the value of field number fno in tuple tupno of result set dbres is NULL; false otherwise.

[getdynfield dbres fno tupno] returns the value of field number fno in tuple tupno of result set dbres as a dynval (a wrapped value). A NULL value is returned as NullVal. Note that the partial application (getdynfield dbres fno) precomputes the type of the field fno. Hence it is far more efficient to compute

```
let val getfno = getdynfield dbres fno
  in tabulate(ntuples dbres, getfno) end
```

than to compute

```
let fun getfno tupno = getdynfield dbres fno tupno
  in tabulate(ntuples dbres, getfno) end
```

because the latter repeatedly computes the type of the field.

[getdyntup dbres tupno] returns the fields of tuple tupno in result set dbres as a vector of dynvals.

[getdyntups dbres] returns all tuples of result set dbres as a vector of vectors of dynvals.

[dynval2s dv] returns a string representing the dynval dv.

[applyto x f] computes f(x). This is convenient for applying several functions (given in a list or vector) to the same value:

map (applyto 5) (tabulate(3, getdynfield dbres))
equals

[getdynfield dbres 0 5, getdynfield dbres 1 5, getdynfield dbres 2 5]

[copytableto(dbconn, tablename, put)] executes a "COPY TABLE TO" statement, applies the function put to every tuple of the table, represented as a line of text (not terminated by newline \n), and cleans up at the end. For instance, to copy the contents of a table t to a text stream s (one tuple on each line), define

fun put line =
 (TextIO.output(s, line); TextIO.output(s, "\n"))

and execute

copytableto(dbconn, "t", put).

[copytablefrom(dbconn, tablename, useput)] executes a "COPY TABLE FROM" statement, creates a put function for copying lines to the table, passes the put function to useput, and cleans up at the end. The put function may be called multiple times for each line (tuple); the end of each line is indicated with the newline character "\n" as usual. For instance, to copy the contents of a text stream s to a table t, define

fun useput put =
 while not (TextIO.endOfStream s) do put(TextIO.inputLine s);
and execute

copytablefrom(dbconn, "t", useput).

Note that TextIO.inputLine preserves the newline at the end of each line.

[formattable dbresult] returns a wseq representing an HTML table. The HTML table has a column for every field in the dbresult. The first row is a table header giving the names of the fields in the dbresult. The remaining rows correspond to the tuples in the dbresult, in the order they are provided by the database server. Null fields are shown as NULL.

[showquery dbconn query] sends the SQL query to the database server, then uses formattable to format the result of the query.

Module Process

```
OS.Process -- SML Basis Library

type status

val success    : status
val failure    : status

val isSuccess : status -> bool

val system     : string -> status

val atExit     : (unit -> unit) -> unit
val exit       : status -> 'a
val terminate : status -> 'a
val sleep      : Time.time -> unit

val getEnv     : string -> string option
```

Portable functions for manipulating processes.

[success] is the unique status value that signifies successful termination of a process. Note: MS DOS (sometimes) believes that all processes are successful.

[failure] is a status value that signifies an error during execution of a process. Note that in contrast to the success value, there may be several distinct failure values. Use function isSuccess to reliably test for success.

[isSuccess sv] returns true if the status value sv represents a successful execution, false otherwise. It holds that isSuccess success = true and isSuccess failure = false.

[system cmd] asks the operating system to execute command cmd, and returns a status value.

[atExit act] registers the action act to be executed when the current SML program calls Process.exit. Actions will be executed in reverse order of registration.

[exit i] executes all registered actions, then terminates the SML process with completion code i.

[terminate i] terminates the SML process with completion code i (but without executing the registered actions).

[sleep t] suspends this process for approximately the time indicated by t. The actual time slept depends on the capabilities of the underlying system and the system load. Does not sleep at all if t <= Time.zeroTime.

[getEnv evar] returns SOME s if the environment variable evar is defined and is associated with the string s; otherwise NONE.

Module Random

Random -- random number generator

type generator

```
val newgenseed : real -> generator
val newgen      : unit -> generator
val random     : generator -> real
val randomlist : int * generator -> real list
val range      : int * int -> generator -> int
val rangelist  : int * int -> int * generator -> int list
```

[generator] is the type of random number generators, here the linear congruential generators from Paulson 1991, 1996.

[newgenseed seed] returns a random number generator with the given seed. Throws exception Fail on seed 0.0 (which would give rise to a degenerate sequence of random numbers).

[newgen ()] returns a random number generator, taking the seed from the system clock.

[random gen] returns a random number in the interval [0..1].

[randomlist (n, gen)] returns a list of n random numbers in the interval [0,1].

[range (min, max) gen] returns an integral random number in the range [min, max). Raises Fail if min >= max.

[rangelist (min, max) (n, gen)] returns a list of n integral random numbers in the range [min, max). Raises Fail if min >= max.

Module Rbset

*Rbset -- ordered sets implemented by red-black trees
 Intention: should resemble SML/NJs ORD_SET signature*

```

signature Rbset = sig
type 'item set

exception NotFound
exception NonMonotonic

val empty      : ('item * 'item -> order) -> 'item set
val singleton  : ('item * 'item -> order) -> 'item -> 'item set
val add        : 'item set * 'item -> 'item set
val add'       : 'item * 'item set -> 'item set
val addList    : 'item set * 'item list -> 'item set
val isEmpty    : 'item set -> bool
val isSubset   : 'item set * 'item set -> bool
val member     : 'item set * 'item -> bool
val delete     : 'item set * 'item -> 'item set
val numItems   : 'item set -> int
val getOrder   : 'item set -> ('item * 'item -> order)
val union      : 'item set * 'item set -> 'item set
val intersection : 'item set * 'item set -> 'item set
val difference  : 'item set * 'item set -> 'item set
val listItems   : 'item set -> 'item list
val app         : ('item -> unit) -> 'item set -> unit
val revapp     : ('item -> unit) -> 'item set -> unit
val foldr      : ('item * 'b -> 'b) -> 'b -> 'item set -> 'b
val foldl      : ('item * 'b -> 'b) -> 'b -> 'item set -> 'b
val map         : ('item -> 'newitem) * ('newitem * 'newitem -> order)
               -> 'item set -> 'newitem set
val mapMono    : ('item -> 'newitem) * ('newitem * 'newitem -> order)
               -> 'item set -> 'newitem set
val find        : ('item -> bool) -> 'item set -> 'item option
val min         : 'item set -> 'item option
val max         : 'item set -> 'item option
val hash        : ('item -> word) -> 'item set -> word
val equal       : 'item set * 'item set -> bool
val compare     : 'item set * 'item set -> order

val depth       : 'item set -> int

datatype 'item intv =
  All
  | From of 'item
  | To   of 'item
  | FromTo of 'item * 'item

val subset   : 'item set * 'item intv -> 'item set
val sublist : 'item set * 'item intv -> 'item list
end

```

[*'item set*] is the type of sets of ordered elements of type '*item*.
 The ordering relation on the elements is used in the representation
 of the set. The result of combining or comparing two sets with
 different underlying ordering relations is undefined. The
 implementation uses Okasaki-style red-black trees.

[empty ordr] creates a new empty set with the given ordering relation.

[singleton ordr i] creates the singleton set containing i, with the given ordering relation.

[add(s, i)] adds item i to set s.

[addList(s, xs)] adds all items from the list xs to the set s.

[isEmpty s] returns true if and only if the set is empty.

[equal(s1, s2)] returns true if and only if the two sets have the same elements, as determined by the ordering relation given when the sets were created.

[isSubset(s1, s2)] returns true if and only if s1 is a subset of s2.

[member(s, i)] returns true if and only if i is in s.

[delete(s, i)] removes item i from s. Raises NotFound if i is not in s.

[numItems s] returns the number of items in set s.

[union(s1, s2)] returns the union of s1 and s2.

[intersection(s1, s2)] returns the intersection of s1 and s2.

[difference(s1, s2)] returns the difference between s1 and s2 (that is, the set of elements in s1 but not in s2).

[listItems s] returns a list of the items in set s, in increasing order.

[app f s] applies function f to the elements of s, in increasing order.

[revapp f s] applies function f to the elements of s, in decreasing order.

[foldl f e s] applies the folding function f to the entries of the set in increasing order.

[foldr f e s] applies the folding function f to the entries of the set in decreasing order.

[map (f, ordr) s] creates a new set with underlying ordering ordr by applying function f to all elements of the set s.

[mapMono (f, ordr) s] creates a new set by applying the strictly monotonically increasing function f to all elements of s. The new set will have ordering ordr. This is faster than map (f, ordr) s by a logarithmic factor, but the function must satisfy

ordr(f x, f y) = ordr'(x, y)
for all elements x, y in s, where ordr' is the ordering relation on s; otherwise exception NonMonotonic is thrown.

[find p s] returns SOME i, where i is an item in s which satisfies p, if one exists; otherwise returns NONE. Traverses the entries of the set in increasing order.

[min s] returns SOME i, where i is the least item in the set s, if s is non-empty; returns NONE if s is empty.

[max s] returns SOME i, where i is the greatest item in the set s, if s is non-empty; returns NONE if s is empty.

[hashCode h s] returns the hashCode of the set, which is the sum of the hashcodes of its elements, as computed by the function h.

[compare (s1, s2)] returns LESS, EQUAL or GREATER according as s1 precedes, equals or follows s2 in the lexicographic ordering that would be obtained by comparing the sorted lists of elements of the two sets. It holds that

equal(s1, s2) if and only if compare(s1, s2) = EQUAL
 isSubset(s1, s2) implies compare(s1, s2) = LESS
 isSubset(s2, s1) implies compare(s1, s2) = GREATER

[subset(s, intv)] returns a set of those elements of s that belong to the interval intv. The intervals have the following meaning:

All	denotes all elements
From e1	denotes elements e for which $\text{cmp}(e1, e) \leftrightarrow \text{GREATER}$
To e2	denotes elements e for which $\text{cmp}(e, e2) = \text{LESS}$
FromTo(e1, e2)	denotes elements e for which $\text{cmp}(e1, e) \leftrightarrow \text{GREATER}$ and $\text{cmp}(e, e2) = \text{LESS}$

[sublist(s, intv)] returns a list, in order, of those elements of s that belong to the interval intv. Thus sublist(s, All) is equivalent to listItems s.

Module Real

```
Real -- SML Basis Library

type real = real

exception Div
and Overflow

val ~          : real -> real
val +          : real * real -> real
val -          : real * real -> real
val *          : real * real -> real
val /          : real * real -> real
val abs        : real -> real
val min        : real * real -> real
val max        : real * real -> real
val sign       : real -> int
val compare    : real * real -> order

val sameSign   : real * real -> bool
val toDefault  : real -> real
val fromDefault: real -> real
val fromInt   : int -> real

val floor      : real -> int
val ceil       : real -> int
val trunc      : real -> int
val round      : real -> int

val >          : real * real -> bool
val >=         : real * real -> bool
val <          : real * real -> bool
val <=         : real * real -> bool
val ==         : real * real -> bool
val !=         : real * real -> bool
val ?=         : real * real -> bool

val toString   : real -> string
val fromString : string -> real option
val scan       : (char, 'a) StringCvt.reader -> (real, 'a) StringCvt.reader
val fmt        : StringCvt.realfmt -> real -> string
```

```
[~]
[*]
[/]
[+]
[-]
[>]
[>=]
[<]
[<=] are the usual operations on defined reals (excluding NaN and Inf).
```

[abs x] is x if $x \geq 0$, and $-x$ if $x < 0$, that is, the absolute value of x .

[min(x, y)] is the smaller of x and y .

[max(x, y)] is the larger of x and y .

[sign x] is -1 , 0 , or 1 , according as x is negative, zero, or positive.

[compare(x, y)] returns LESS, EQUAL, or GREATER, according as x is less than, equal to, or greater than y.

[sameSign(x, y)] is true iff sign x = sign y.

[toDefault x] is x.

[fromDefault x] is x.

[fromInt i] is the floating-point number representing integer i.

[floor r] is the largest integer $\leq r$ (rounds towards minus infinity). May raise Overflow.

[ceil r] is the smallest integer $\geq r$ (rounds towards plus infinity). May raise Overflow.

[trunc r] is the numerically largest integer between r and zero (rounds towards zero). May raise Overflow.

[round r] is the integer nearest to r, using the default rounding mode. May raise Overflow.

[==(x, y)] is equivalent to x=y in Moscow ML (because of the absence of NaNs and Infs).

[!= (x, y)] is equivalent to x<>y in Moscow ML (because of the absence of NaNs and Infs).

[?=(x, y)] is false in Moscow ML (because of the absence of NaNs and Infs).

[fmt spec r] returns a string representing r, in the format specified by spec (see below). The requested number of digits must be ≥ 0 in the SCI and FIX formats and > 0 in the GEN format; otherwise Size is raised, even in a partial application fmt(spec).

spec	description	C printf
SCI NONE	scientific, 6 digits after point	%e
SCI (SOME n)	scientific, n digits after point	%.ne
FIX NONE	fixed-point, 6 digits after point	%f
FIX (SOME n)	fixed-point, n digits after point	%.nf
GEN NONE	auto choice, 12 significant digits	%.12g
GEN (SOME n)	auto choice, n significant digits	%.ng

[toString r] returns a string representing r, with automatic choice of format according to the magnitude of r.
Equivalent to (fmt (GEN NONE) r).

[fromString s] returns SOME(r) if a floating-point numeral can be scanned from a prefix of string s, ignoring any initial whitespace; returns NONE otherwise. The valid forms of floating-point numerals are described by:

[+~-]?(([0-9]+(\.[0-9]+)?))|((\.[0-9]+))([eE][+~-]?[0-9]+)?

[scan getc charsrc] attempts to scan a floating-point number from the character source charsrc, using the accessor getc, and ignoring any initial whitespace. If successful, it returns SOME(r, rest) where r is the number scanned, and rest is the unused part of the

character source. The valid forms of floating-point numerals are described by:

```
[+~-]?(([0-9]+(\.[0-9]+)?)(\.[0-9]+))([eE][+~-]?[0-9]+)?
```

Module Redblackmap

```
Redblackmap -- applicative maps as Red-black trees
signature Redblackmap =
sig
type ('key, 'a) dict

exception NotFound

val mkDict    : ('key * 'key -> order) -> ('key, 'a) dict
val insert   : ('key, 'a) dict * 'key * 'a -> ('key, 'a) dict
val find     : ('key, 'a) dict * 'key -> 'a
val peek     : ('key, 'a) dict * 'key -> 'a option
val remove   : ('key, 'a) dict * 'key -> ('key, 'a) dict * 'a
val numItems : ('key, 'a) dict -> int
val listItems: ('key, 'a) dict -> ('key * 'a) list
val app      : ('key * 'a -> unit) -> ('key, 'a) dict -> unit
val revapp   : ('key * 'a -> unit) -> ('key, 'a) dict -> unit
val foldr    : ('key * 'a * 'b -> 'b) -> 'b -> ('key, 'a) dict -> 'b
val foldl    : ('key * 'a * 'b -> 'b) -> 'b -> ('key, 'a) dict -> 'b
val map      : ('key * 'a -> 'b) -> ('key, 'a) dict -> ('key, 'b) dict
val transform: ('a -> 'b) -> ('key, 'a) dict -> ('key, 'b) dict
end
```

[('key, 'a) dict] is the type of applicative maps from domain type 'key to range type 'a, or equivalently, applicative dictionaries with keys of type 'key and values of type 'a. They are implemented as Okasaki-style red-black trees.

[mkDict ordr] returns a new, empty map whose keys have ordering ordr.

[insert(m, i, v)] extends (or modifies) map m to map i to v.

[find (m, k)] returns v if m maps k to v; otherwise raises NotFound.

[peek(m, k)] returns SOME v if m maps k to v; otherwise returns NONE.

[remove(m, k)] removes k from the domain of m and returns the modified map and the element v corresponding to k. Raises NotFound if k is not in the domain of m.

[numItems m] returns the number of entries in m (that is, the size of the domain of m).

[listItems m] returns a list of the entries (k, v) of keys k and the corresponding values v in m, in order of increasing key values.

[app f m] applies function f to the entries (k, v) in m, in increasing order of k (according to the ordering ordr used to create the map or dictionary).

[revapp f m] applies function f to the entries (k, v) in m, in decreasing order of k.

[foldl f e m] applies the folding function f to the entries (k, v) in m, in increasing order of k.

[foldr f e m] applies the folding function f to the entries (k, v) in m, in decreasing order of k.

[map f m] returns a new map whose entries have form (k, f(k,v)), where (k, v) is an entry in m.

[transform f m] returns a new map whose entries have form (k, f v), where (k, v) is an entry in m.

Module Regex

```

Regex -- regular expressions a la POSIX 1003.2 -- requires Dynlib

exception Regex of string

type regex           A compiled regular expression

datatype cflag =
  Extended          Compile POSIX extended REs
  | Icase            Compile case-insensitive match
  | Newline          Treat \n in target string as new line

datatype eflag =
  Notbol            Do not match ^ at beginning of string
  | Noteol           Do not match $ at end of string

val regcomp      : string -> cflag list -> regex
val regexec      : regex -> eflag list -> string -> substring vector option
val regexecBool : regex -> eflag list -> string -> bool
val regexec      : regex -> eflag list -> substring
                   -> substring vector option
val regexecBool : regex -> eflag list -> substring -> bool

val regmatch     : { pat : string, tgt : string } -> cflag list
                   -> eflag list -> substring vector option
val regmatchBool : { pat : string, tgt : string } -> cflag list
                   -> eflag list -> bool

datatype replacer =
  Str of string           A literal string
  | Sus of int             The i'th parenthesized group
  | Tr of (string -> string) * int   Transformation of i'th group
  | Trs of substring vector -> string Transformation of all groups

val replace1    : regex -> replacer list -> string -> string
val replace     : regex -> replacer list -> string -> string

val substitute1 : regex -> (string -> string) -> string -> string
val substitute  : regex -> (string -> string) -> string -> string

val tokens      : regex -> string -> substring list
val fields       : regex -> string -> substring list

val map          : regex -> (substring vector -> 'a) -> string -> 'a list
val app          : regex -> (substring vector -> unit) -> string -> unit
val fold         : regex
                   -> (substring * 'a -> 'a) * (substring vector * 'a -> 'a)
                   -> 'a -> string -> 'a

```

This structure provides pattern matching with POSIX 1003.2 regular expressions.

The form and meaning of Extended and Basic regular expressions are described below. Here R and S denote regular expressions; m and n denote natural numbers; L denotes a character list; and d denotes a decimal digit:

Extended	Basic	Meaning
c	c	Match the character c
.	.	Match any character
R*	R*	Match R zero or more times
R+	R\+	Match R one or more times
R S	R\ S	Match R or S
R?	R\?	Match R or the empty string
R{m}	R\{m\}	Match R exactly m times
R{m,}	R\{m,\}	Match R at least m times
R{m,n}	R\{m,n\}	Match R at least m and at most n times
[L]	[L]	Match any character in L
[^L]	[^L]	Match any character not in L
^	^	Match at string's beginning
\$	\$	Match at string's end
(R)	\(R\)	Match R as a group; save the match
\d	\d	Match the same as previous group d
\\	\\	Match \ --- similarly for *.[]^\$
\+	+	Match + --- similarly for ?{}()

Some example character lists L:

[aeiou]	Match vowel: a or e or i or o or u
[0-9]	Match digit: 0 or 1 or 2 or ... or 9
[^0-9]	Match non-digit
[-*/*^]	Match - or + or * or / or ^
[-a-z]	Match lowercase letter or hyphen (-)
[0-9a-fA-F]	Match hexadecimal digit
[[:alnum:]]	Match letter or digit
[[:alpha:]]	Match letter
[[:cntrl:]]	Match ASCII control character
[[:digit:]]	Match decimal digit; same as [0-9]
[[:graph:]]	Same as [:print:] but not [:space:]
[[:lower:]]	Match lowercase letter
[[:print:]]	Match printable character
[[:punct:]]	Match punctuation character
[[:space:]]	Match SML #", #"\r", #"\n", #"\t", #"\v", #"\f"
[[:upper:]]	Match uppercase letter
[[:xdigit:]]	Match hexadecimal digit; same as [0-9a-fA-F]
[[:lower:]\æøå]	Match lowercase Danish letters (ISO Latin 1)

Remember that backslash (\) must be escaped as "\\" in SML strings.

[regcomp pat cflags] returns a compiled representation of the regular expression pat. Raises Regex in case of failure.

[cflag] is the type of compilation flags with the following meanings:

- [Extended] : compile as POSIX extended regular expression.
- [Icase] : compile case-insensitive match.
- [Newline] : make the newline character \n significant, so ^ matches just after newline (\n), and \$ matches just before \n.

Example: Match SML integer constant:
regcomp "^~?[0-9]+\$" [Extended]

Example: Match SML alphanumeric identifier:
regcomp "^[a-zA-Z0-9][a-zA-Z0-9'_]*\$" [Extended]

Example: Match SML floating-point constant:
regcomp "^[+~]?[0-9]+(\.\[0-9\]+|\.\[0-9\]+\?)?[eE][+~]?[0-9]+\\$" [Extended]

Example: Match any HTML start tag; make the tag's name into a group:
`regcomp "<(:alnum:)+[^>]*>" [Extended]`

[`regexec regex eflags s`] returns `SOME(vec)` if some substring of `s` matches `regex`, `NONE` otherwise. In case of success, `vec` is the match vector, a vector of substrings such that `vec[0]` is the (longest leftmost) substring of `s` matching `regex`, and `vec[1], vec[2], ...` are substrings matching the parenthesized groups in `pat` (numbered 1, 2, ...) from left to right in the order of their opening parentheses). For a group that does not take part in the match, such as `(ab)` in `"(ab)|(cd)"` when matched against the string `"xcdy"`, the corresponding substring is the empty substring at the beginning of the underlying string. For a group that takes part in the match repeatedly, such as the group `(b+)` in `"(a(b+))+"` when matched against `"babbbbbb"`, the corresponding substring is the last (rightmost) one matched.

[`eflag`] is the type of end flags with the following meaning:

[`Notbol`] : do not match `^` at beginning of string.
[`Noteol`] : do not match `$` at end of string.

[`regexecBool regex eflags s`] returns true if some substring of `s` matches `regex`, false otherwise. Equivalent to, but faster than, `Option.isSome(regexexec regexec eflags s)`.

[`regnexec regex eflags sus`] returns `SOME(vec)` if some substring of `sus` matches `regex`, `NONE` otherwise. The substrings returned in the vector `vec` will have the same base string as `sus`. Useful e.g. for splitting a string into fragments separated by substrings matching some regular expression.

[`regnexecBool regex eflags sus`] returns true if some substring of `sus` matches `regex`, false otherwise. Equivalent to, but faster than, `Option.isSome(regnexec regexec eflags sus)`.

[`regmatch { pat, tgt } cflags eflags`] is equivalent to
`regexec (regcomp pat cflags) eflags tgt`
but more efficient when the compiled regex is used only once.

[`regmatchBool { pat, tgt } cflags eflags`] is equivalent to
`regexecBool (regcomp pat cflags) eflags tgt`
but more efficient when the compiled regex is used only once.

[`replace regex repl s`] finds the (disjoint) substrings of `s` matching `regex` from left to right, and returns the string obtained from `s` by applying the replacer list `repl` to every such substring (see below). Raises `Regex` if it fails to make progress in decomposing `s`, that is, if `regex` matches an empty string at the head of `s` or immediately after a previous regex match.

Example use: delete all HTML tags from `s`:
`replace (regcomp "<[^>]+>" [Extended]) [] s`

[`replacel regex repl s`] finds the leftmost substring `b1` of `s` matching `regex`, and returns the string resulting from `s` by applying the replacer list `repl` to the match vector `vec1` (see below).

Let `x0` be a substring matching the entire `regex` and `xi` be the substring matching the `i`'th parenthesized group in `regex`; thus `xi = vec[i]` where `vec` is the match vector (see `regexec` above). Then a

single replacer evaluates to a string as follows:

```
[Str s]      gives the string s
[Sus i]      gives the string xi
[Tr (f, i)]  gives the string f(xi)
[Trs f]      gives the string f(vec)
```

A replacer list repl evaluates to the concatenation of the results of the replacers. The replacers are applied from left to right.

[substitute regex f s] finds the (disjoint) substrings b₁, ..., b_n of s matching regex from left to right, and returns the string obtained from s by replacing every b_i by f(b_i). Function f is applied to the matching substrings from left to right. Raises Regex if it fails to make progress in decomposing s. Equivalent to replace regex [Tr (f, 0)] s

[substitutel regex f s] finds the leftmost substring b of s matching regex, and returns the string obtained from s by replacing that substring by f(b). Equivalent to replace1 regex [Tr (f, 0)] s

[map regex f s] finds the (disjoint) substrings of s matching regex from left to right, applies f to the match vectors vec₁, ..., vec_n, and returns the list [f(vec₁), ..., f(vec_n)]. Raises Regex if it fails to make progress in decomposing s.

[app regex f s] finds the (disjoint) substrings of s matching regex from left to right, and applies f to the match vectors vec₁, ..., vec_n. Raises Regex if the regex fails to make progress in decomposing s.

[fields regex s] returns the list of fields in s, from left to right. A field is a (possibly empty) maximal substring of s not containing any delimiter. A delimiter is a maximal substring that matches regex. The eflags Notbol and Noteol are set. Raises Regex if it fails to make progress in decomposing s.

Example use:

```
fields (regcomp " *; *" []) "56; 23 ; 22;; 89; 99"
```

[tokens regex s] returns the list of tokens in s, from left to right. A token is a non-empty maximal substring of s not containing any delimiter. A delimiter is a maximal substring that matches regex. The eflags Notbol and Noteol are set. Raises Regex if it fails to make progress in decomposing s. Equivalent to List.filter (not o Substring.isEmpty) (fields regex s)

Two tokens may be separated by more than one delimiter, whereas two fields are separated by exactly one delimiter. If the only delimiter is the character #"\|", then

"abc||def" contains three fields: "abc" and "" and "def"

"abc||def" contains two tokens: "abc" and "def"

[fold regex (fa, fb) e s] finds the (disjoint) substrings b₁, ..., b_n of s matching regex from left to right, and splits s into the substrings

a₀, b₁, a₁, b₂, a₂, ..., b_n, a_n

where n >= 0 and where a₀ is the (possibly empty) substring of s preceding the first match, and a_i is the (possibly empty) substring between the matches b_i and b_(i+1). Then it computes and returns

fa(a_n, fb(vec_n, ..., fa(a₁, fb(vec₁, fa(a₀, e)))) ...))

where `veci` is the match vector corresponding to `bi`. Raises `Regex` if it fails to make progress in decomposing `s`.

If we define the auxiliary functions

```
fun fapp f (x, r) = f x :: r
fun get i vec = Substring.string(Vector.sub(vec, i))
```

then

```
map regex f s = List.rev (fold regex (#2, fapp f) [] s)
app regex f s = fold regex (ignore, f o #1) () s
fields regex s = List.rev (fold regex (op ::, #2) [] s)
substitute regex f s =
  Substring.concat(List.rev
    (fold regex (op ::, fapp (Substring.all o f o get 0)) [] s))
```

Module SML90

SML90 -- part of the initial basis of the 1990 Definition

Math

```
val sqrt    : real -> real
val sin     : real -> real
val cos     : real -> real
val arctan   : real -> real
val exp     : real -> real
val ln      : real -> real
```

Strings

```
val chr     : int -> string
val ord     : string -> int

val explode : string -> string list
val implode : string list -> string
```

```
exception Abs
  and Diff
  and Exp
  and Floor
  and Neg
  and Prod
  and Sum
  and Mod
  and Quot
```

Input/output

```
type instream and outstream

val std_in       : instream
val open_in      : string -> instream
val input        : instream * int -> string
val lookahead    : instream -> string
val close_in     : instream -> unit
val end_of_stream : instream -> bool

val std_out      : outstream
val open_out     : string -> outstream
val output       : outstream * string -> unit
val close_out    : outstream -> unit
```

Module Signal

Signal -- SML Basis Library

```
eqtype signal

val abrt : signal
val alarm : signal
val bus  : signal
val fpe   : signal
val hup   : signal
val ill   : signal
val int   : signal
val kill  : signal
val pipe  : signal
val quit  : signal
val segv  : signal
val term  : signal
val usrl  : signal
val usr2  : signal
val chld  : signal
val cont  : signal
val stop  : signal
val tstop : signal
val ttin  : signal
val ttou  : signal

val toWord   : signal -> Word.word
val fromWord : Word.word -> signal
```

[signal] is the type of Unix/Posix-style signals, which can be sent to another process.

[toWord sig] returns the signal number as an unsigned word.

[fromWord w] returns the signal whose number is w.

[abrt] is SIGABRT, the abort signal from abort(3).

[alarm] is SIGALRM, a timer signal from alarm(1).

[bus] is SIGBUS, a bus error.

[fpe] is SIGFPE, a floating point exception.

[hup] is SIGHUP, a hangup.

[ill] is SIGILL, an illegal instruction.

[int] is SIGINT, an interrupt.

[kill] is SIGKILL, the kill signal.

[pipe] is SIGPIPE, a broken pipe.

[quit] is SIGQUIT, a quit from keyboard.

[segv] is SIGSEGV, a segmentation violation.

[term] is SIGTERM, the termination signal.

[usr1] is SIGUSR1, the first user signal.
[usr2] is SIGUSR2, the second user signal.
[chld] is SIGCHLD, child process stopped or terminated.
[cont] is SIGCONT, continue if stopped.
[stop] is SIGSTOP, signal to stop process.
[tstp] is SIGTSTP, a stop signal typed at the tty.
[ttin] is SIGTTIN, tty input for background process.
[ttou] is SIGTTOU, tty output for background process.

Module Socket

```

Socket -- SML Basis Library -- requires Dynlib

type ('addressfam, 'socktype) sock
type 'addressfam sock_addr

Socket types
type dgram                                A datagram socket
type 'a stream                             A stream socket
type passive                             A passive stream
type active                               An active, connected, stream

Socket protocol families
type pf_file                                The Unix file protocol family
type pf_inet                                The Internet protocol family

Address constructors
val fileAddr    : string -> pf_file sock_addr
val inetAddr   : string -> int -> pf_inet sock_addr

Socket constructors
val fileStream : unit -> (pf_file, 'a stream) sock
val fileDgram  : unit -> (pf_file, dgram) sock
val inetStream : unit -> (pf_inet, 'a stream) sock
val inetDgram  : unit -> (pf_inet, dgram) sock

val accept     : ('a, passive stream) sock
                 -> ('a, active stream) sock * 'a sock_addr
val bind       : ('a, 'b) sock * 'a sock_addr -> unit
val connect    : ('a, 'b) sock * 'a sock_addr -> unit
val listen     : ('a, passive stream) sock * int -> unit
val close      : ('a, 'b) sock -> unit

Socket management
datatype shutdown_mode =
  NO_RECVS                                No further receives
  | NO_SENDS                                 No further sends
  | NO_RECVS_OR_SENDS                         No receives nor sends

val shutdown   : ('a, 'b stream) sock * shutdown_mode -> unit

type sock_desc

val sockDesc   : ('a, 'b) sock -> sock_desc
val sameDesc   : sock_desc * sock_desc -> bool
val compare    : sock_desc * sock_desc -> order
val select     :
  { rds : sock_desc list, wrs : sock_desc list, exs : sock_desc list,
    timeout : Time.time option }
  -> { rds : sock_desc list, wrs : sock_desc list, exs : sock_desc list }

val getinetaddr : pf_inet sock_addr -> string

Sock I/O option types
type out_flags = { don't_route : bool, oob : bool }
type in_flags  = { peek : bool, oob : bool }

type 'a buf = { buf : 'a, ofs : int, size : int option }

```

```

Socket output operations
val sendVec    : ('a, active stream) sock * Word8Vector.vector buf -> int
val sendArr    : ('a, active stream) sock * Word8Array.array buf -> int
val sendVec'   : ('a, active stream) sock * Word8Vector.vector buf
                * out_flags -> int
val sendArr'   : ('a, active stream) sock * Word8Array.array buf
                * out_flags -> int
val sendVecTo  : ('a, dgram) sock * 'a sock_addr * Word8Vector.vector buf
                -> int
val sendArrTo  : ('a, dgram) sock * 'a sock_addr * Word8Array.array buf
                -> int
val sendVecTo' : ('a, dgram) sock * 'a sock_addr * Word8Vector.vector buf
                * out_flags -> int
val sendArrTo' : ('a, dgram) sock * 'a sock_addr * Word8Array.array buf
                * out_flags -> int

Socket input operations
val recvVec    : ('a, active stream) sock * int -> Word8Vector.vector
val recvArr    : ('a, active stream) sock * Word8Array.array buf -> int
val recvVec'   : ('a, active stream) sock * int * in_flags
                -> Word8Vector.vector
val recvArr'   : ('a, active stream) sock * Word8Array.array buf * in_flags
                -> int
val recvVecFrom : ('a, dgram) sock * int
                -> Word8Vector.vector * 'a sock_addr
val recvArrFrom : ('a, dgram) sock * Word8Array.array buf
                -> int * 'a sock_addr
val recvVecFrom' : ('a, dgram) sock * int * in_flags
                -> Word8Vector.vector * 'a sock_addr
val recvArrFrom' : ('a, dgram) sock * Word8Array.array buf * in_flags
                -> int * 'a sock_addr

```

Structure `Socket` defines functions for creating and using sockets, a means for communication between SML processes on the same machine or via a network.

`[('addressfam, 'socktype) sock]` is the type of sockets with address family `'addressfam` and having type `'socktype`.

`['addressfam sock_addr]` is the type of sockets addresses.

The possible address (protocol) families are

type pf_file	The Unix address family (file)
type pf_inet	The Internet address family

The possible socket types are

type dgram	datagram sockets
type 'a stream	stream sockets
type passive	passive stream sockets
type active	active, or connected, stream sockets

`[fileAddr fname]` returns a socket address for the Unix protocol family, created from the given file name `fname`.

`[inetAddr inetaddr portno]` returns a socket address for the Internet protocol family, created from the given Internet number (e.g. "130.225.40.253") and port number (e.g. 8080).

`[fileStream ()]` returns a new stream socket for the Unix protocol

family.

[fileDgram ()] returns a new datagram socket for the Unix protocol family.

[inetStream ()] returns a new stream socket for the Internet protocol family.

[inetDgram ()] returns a new datagram socket for the Internet protocol family.

[accept sock] extracts the first connection on the queue of pending connections to sock. Returns (sock', addr) where sock' is a copy of the socket sock, bound to that connection, and addr is the address of the communications counterpart (the other end of the connection). Blocks if no connections are pending. The stream socket sock must have been assigned a name (with bind) and must be listening for connections (following a call to listen).

[bind sock addr] binds the socket sock to the address addr, that is, assigns the name addr to the socket. Binding a name in the Unix protocol family creates a socket in the file system that must be deleted when it is no longer needed

[connect (sock, addr)] attempts to connect socket sock to the communications peer at address addr. If sock is a datagram socket, then addr is the address to which datagrams are to be sent, and the only address from which datagrams will be accepted. If sock is a stream socket, then addr specifies another socket to which to connect.

[listen (sock, queueLen)] enables the passive stream socket sock to accept incoming connections. The parameter queueLen specifies the maximal number of pending connections. Further connections from clients may be refused when this limit is reached.

[close sock] closes the socket.

[shutdown sock shutdown_mode] shuts down socket sock for further communication, as specified by the shutdown_mode parameter:

[NO_RECVS] no further receives are allowed;

[NO_SENDS] no further sends are allowed;

[NO_RECVS_OR_SENDS] no further receives or sends are allowed.

[getinetaddr addr] returns the Internet number (e.g. "130.225.40.253") of the Internet socket address addr.

['buf'] is the type of records { buf, ofs, size } which represent subvectors or subarrays:
if size = SOME s it represents buf[ofs..ofs+s-1];
if size = NONE it represents buf[ofs..len-1] where len is buf's length.
When the subbuffer is used in a call, exception Subscript will be raised
if ofs < 0 or size < 0 or ofs+size > len.

[sendVec (sock, vecbuf)] transmits the bytes from buffer vecbuf on the active stream socket sock. Returns the number of bytes sent. Blocks until sufficient space is available at the socket.

[sendArr (sock, arrbuf)] is analogous til sendVec.

[sendVec' (sock, vecbuf, out_flags)] transmits the bytes from buffer vecbuf on the active stream socket sock, observing the out_flags. Returns the number of bytes sent. Blocks until sufficient space is available at the socket.

[out_flags] is the type of records { don't_route, oob } in which the field don't_route specifies whether routing should be bypassed, and the field oob specifies whether data should be sent out-of-band.

[sendArr' (sock, arrbuf, out_flags)] is analogous til sendVec'.

[sendVecTo (sock, addr, vecbuf)] transmits the bytes from buffer vecbuf on the datagram socket sock to the target address addr. Returns the number of bytes sent. Blocks until sufficient space is available at the socket.

[sendArrTo (sock, addr, arrbuf)] is analogous til sendVecTo.

[sendVecTo' (sock, addr, vecbuf, out_flags)] transmits the bytes from buffer vecbuf on the datagram socket sock to the target address addr, observing the out_flags. Returns the number of bytes sent. Blocks until sufficient space is available at the socket. See above for a description of vecbuf and out_flags.

[sendArrTo' (sock, addr, arrbuf, out_flags)] is analogous til sendVecTo'.

[recvVec (sock, n)] receives up to n bytes from the active stream socket sock. Returns a byte vector containing the bytes actually received. Blocks until some data become available at the socket, then returns any available data, up to n bytes. Excess data are not lost; they are available for subsequent receive calls.

[recvArr (sock, arrbuf)] receives bytes from the active stream socket sock into the subarray arrbuf, up to the available space. If #size(arrbuf) = SOME(s) the available space is s bytes; if #size(arrbuf) = NONE the available space is len - #ofs(arrbuf) bytes. Returns the number of bytes actually received. Blocks until some data become available at the socket. Excess data are not lost; they are available for subsequent receive calls.

[recvVec' (sock, n, in_flags)] receives up to n bytes from the active stream socket sock, observing the in_flags. Returns a byte vector containing the bytes actually received. Blocks until some data become available at the socket, then returns any available data, up to n bytes. Data in excess of n bytes are not lost; they are available for subsequent receive calls.

[in_flags] is the type of records { peek, oob } in which the field peek specifies that the data read should not be removed from the receive queue, and the field oob specifies that data may be received out-of-band.

[recvArr' (sock, arrbuf, in_flags)] receives bytes from the active stream socket sock into the subarray arrbuf, observing the in_flags, up to the available space.. Returns the number of bytes actually received. Blocks until some data become available at the socket. Excess data are not lost; they are available for subsequent receive calls.

[recvVecFrom (sock, n)] receives up to n bytes from the datagram socket sock. Returns a byte vector containing the bytes actually received. Blocks until some data become available at the socket, then returns any available data, up to n bytes.

[recvArrFrom (sock, arrbuf)] receives bytes from the datagram socket sock into the subarray arrbuf. Returns the number of bytes actually received. Blocks until some data become available at the socket.

[recvVecFrom' (sock, n, in_flags)] receives up to n bytes from the datagram socket sock, observing the in_flags (see above). Returns (vec, addr) where vec is a byte vector containing the bytes actually received, and addr is the source address of the message. Blocks until some data become available at the socket, then returns any available data, up to n bytes.

[recvArrFrom' (sock, arrbuf, in_flags)] receives bytes from the datagram socket sock into the array buffer arrbuf, observing the in_flags (see above). Returns (n, addr) where n is the number of bytes actually received, and addr is the source address of the message. Blocks until some data become available at the socket.

[sockDesc sock] returns a descriptor for the socket sock, to be used in a call to select.

[compare (sd1, sd2)] compares sd1 and sd2 according to an unspecified total ordering, and returns LESS if sd1 precedes sd2, returns GREATER if sd1 precedes sd2, and returns EQUAL otherwise.

[sameDesc (sd1, sd2)] returns true if sd1 and sd2 describe the same socket. Equivalent to compare(sd1, sd2) = EQUAL.

[select { rds, wrs, exs, timeout }] blocks the calling process until some input/output operations become possible on some sockets. The call will check the sockets described in rds for reading, those in wrs for writing, and those in exs for exceptional conditions. Returns { rds, wrs, exs } where rds now is a list of descriptors of sockets ready for reading, wrs are ready for writing, and exs have exceptional conditions. The order of the socket descriptors in the results is the same as their order in the corresponding arguments. If timeout is NONE then the call blocks until some input/output operations become possible; if timeout is SOME(t) then the call blocks for at most time t.

A server socket is considered ready for reading if there is a pending connection which can be accepted with 'accept'. A client socket is ready for writing when its connection is fully established.

Module Splaymap

*Splaymap -- applicative maps implemented by splay-trees
From SML/NJ lib 0.2, copyright 1993 by AT&T Bell Laboratories*

```
type ('key, 'a) dict

exception NotFound

val mkDict      : ('_key * '_key -> order) -> ('_key, '_a) dict
val insert     : ('_key, '_a) dict * '_key * '_a -> ('_key, '_a) dict
val find       : ('key, 'a) dict * 'key -> 'a
val peek       : ('key, 'a) dict * 'key -> 'a option
val remove     : ('_key, '_a) dict * '_key -> ('_key, '_a) dict * '_a
val numItems   : ('key, 'a) dict -> int
val listItems  : ('key, 'a) dict -> ('key * 'a) list
val app        : ('key * 'a -> unit) -> ('key, 'a) dict -> unit
val revapp    : ('key * 'a -> 'b) -> ('key, 'a) dict -> unit
val foldr      : ('key * 'a * 'b -> 'b) -> 'b -> ('key, 'a) dict -> 'b
val foldl      : ('key * 'a * 'b -> 'b) -> 'b -> ('key, 'a) dict -> 'b
val map        : ('_key * 'a -> '_b) -> ('_key, 'a) dict -> ('_key, '_b) dict
val transform  : ('a -> '_b) -> ('_key, 'a) dict -> ('_key, '_b) dict
```

[('key, 'a) dict] is the type of applicative maps from domain type '`'key` to range type '`'a`, or equivalently, applicative dictionaries with keys of type '`'key` and values of type '`'a`. They are implemented as ordered splay-trees (Sleator and Tarjan).

[`mkDict` `ordr`] returns a new, empty map whose keys have ordering `ordr`.

[`insert(m, i, v)`] extends (or modifies) map `m` to map `i` to `v`.

[`find (m, k)`] returns `v` if `m` maps `k` to `v`; otherwise raises `NotFound`.

[`peek(m, k)`] returns SOME `v` if `m` maps `k` to `v`; otherwise returns NONE.

[`remove(m, k)`] removes `k` from the domain of `m` and returns the modified map and the element `v` corresponding to `k`. Raises `NotFound` if `k` is not in the domain of `m`.

[`numItems m`] returns the number of entries in `m` (that is, the size of the domain of `m`).

[`listItems m`] returns a list of the entries `(k, v)` of keys `k` and the corresponding values `v` in `m`, in increasing order of `k`.

[`app f m`] applies function `f` to the entries `(k, v)` in `m`, in increasing order of `k` (according to the ordering `ordr` used to create the map or dictionary).

[`revapp f m`] applies function `f` to the entries `(k, v)` in `m`, in decreasing order of `k`.

[`foldl f e m`] applies the folding function `f` to the entries `(k, v)` in `m`, in increasing order of `k`.

[`foldr f e m`] applies the folding function `f` to the entries `(k, v)` in `m`, in decreasing order of `k`.

[map f m] returns a new map whose entries have form (k, f(k,v)), where (k, v) is an entry in m.

[transform f m] returns a new map whose entries have form (k, f v), where (k, v) is an entry in m.

Module Splayset

*Splayset -- applicative sets implemented by splay-trees
From SML/NJ lib 0.2, copyright 1993 by AT&T Bell Laboratories*

```
type 'item set

exception NotFound

val empty      : ('_item * '_item -> order) -> '_item set
val singleton   : ('_item * '_item -> order) -> '_item -> '_item set
val add         : '_item set * '_item -> '_item set
val addList     : '_item set * '_item list -> '_item set
val retrieve    : '_item set * 'item -> 'item
val peek        : '_item set * 'item -> 'item option
val isEmpty     : '_item set -> bool
val equal       : '_item set * '_item set -> bool
val isSubset    : '_item set * '_item set -> bool
val member      : '_item set * 'item -> bool
val delete      : '_item set * '_item -> '_item set
val numItems    : '_item set -> int
val union       : '_item set * '_item set -> '_item set
val intersection: '_item set * '_item set -> '_item set
val difference  : '_item set * '_item set -> '_item set
val listItems   : '_item set -> 'item list
val app         : ('item -> unit) -> '_item set -> unit
val revapp     : ('item -> unit) -> '_item set -> unit
val foldr       : ('item * 'b -> 'b) -> 'b -> '_item set -> 'b
val foldl       : ('item * 'b -> 'b) -> 'b -> '_item set -> 'b
val find        : ('item -> bool) -> '_item set -> 'item option
```

[`item set] is the type of sets of ordered elements of type 'item.
The ordering relation on the elements is used in the representation
of the set. The result of combining two sets with different
underlying ordering relations is undefined. The implementation
uses splay-trees (Sleator and Tarjan).

[empty ordr] creates a new empty set with the given ordering
relation.

[singleton ordr i] creates the singleton set containing i, with the
given ordering relation.

[add(s, i)] adds item i to set s.

[addList(s, xs)] adds all items from the list xs to the set s.

[retrieve(s, i)] returns i if it is in s; raises NotFound otherwise.

[peek(s, i)] returns SOME i if i is in s; returns NONE otherwise.

[isEmpty s] returns true if and only if the set is empty.

[equal(s1, s2)] returns true if and only if the two sets have the
same elements.

[isSubset(s1, s2)] returns true if and only if s1 is a subset of s2.

[member(s, i)] returns true if and only if i is in s.

[delete(s, i)] removes item i from s. Raises NotFound if i is not in s.

[numItems s] returns the number of items in set s.

[union(s1, s2)] returns the union of s1 and s2.

[intersection(s1, s2)] returns the intersection of s1 and s2.

[difference(s1, s2)] returns the difference between s1 and s2 (that is, the set of elements in s1 but not in s2).

[listItems s] returns a list of the items in set s, in increasing order.

[app f s] applies function f to the elements of s, in increasing order.

[revapp f s] applies function f to the elements of s, in decreasing order.

[foldl f e s] applies the folding function f to the entries of the set in increasing order.

[foldr f e s] applies the folding function f to the entries of the set in decreasing order.

[find p s] returns SOME i, where i is an item in s which satisfies p, if one exists; otherwise returns NONE.

Module String

String -- SML Basis Library

```

local
  type char = Char.char
in
  type string = string
  val maxSize    : int
  val size       : string -> int
  val sub        : string * int -> char
  val substring  : string * int * int -> string
  val extract    : string * int * int option -> string
  val ^          : string * string -> string
  val concat    : string list -> string
  val concatWith : string -> string list -> string
  val str        : char -> string
  val implode   : char list -> string
  val explode   : string -> char list

  val map        : (char -> char) -> string -> string
  val translate  : (char -> string) -> string -> string
  val tokens    : (char -> bool) -> string -> string list
  val fields    : (char -> bool) -> string -> string list

  val compare   : string * string -> order
  val collate   : (char * char -> order) -> string * string -> order

  val isPrefix   : string -> string -> bool
  val isSuffix  : string -> string -> bool
  val isSubstring : string -> string -> bool

  val fromString : string -> string option      ML escape sequences
  val toString   : string -> string              ML escape sequences
  val fromCString: string -> string option      C escape sequences
  val toCString  : string -> string              C escape sequences

  val <  : string * string -> bool
  val <= : string * string -> bool
  val >  : string * string -> bool
  val >= : string * string -> bool
end

```

[string] is the type of immutable strings of characters, with constant-time indexing.

[maxSize] is the maximal number of characters in a string.

[size s] is the number of characters in string s.

[sub(s, i)] is the i'th character of s, counting from zero.
Raises Subscript if i<0 or i>=size s.

[substring(s, i, n)] is the string s[i..i+n-1]. Raises Subscript if i<0 or n<0 or i+n>size s. Equivalent to extract(s, i, SOME n).

[extract (s, i, NONE)] is the string s[i..size s-1].
Raises Subscript if i<0 or i>size s.

[extract (s, i, SOME n)] is the string s[i..i+n-1].

`Raises Subscript if $i < 0$ or $n < 0$ or $i + n > \text{size } s$.`

`[$s_1 \wedge s_2$] is the concatenation of strings s_1 and s_2 .`

`[concat ss] is the concatenation of all the strings in ss .
Raises Size if the sum of their sizes is greater than maxSize.`

`[concatWith sep ss] is the concatenation of all the strings in ss ,
using sep as a separator. Thus`

<code>concatWith sep ss</code>	is the empty string ""
<code>concatWith sep [s]</code>	is s
<code>concatWith sep [s₁, ..., s_n]</code>	is <code>concat[s₁, sep, ..., sep, s_n]</code> .

`Raises Size if the resulting string would have more than maxSize
characters.`

`[str c] is the string of size one which contains the character c .`

`[implode cs] is the string containing the characters in the list cs .
Equivalent to concat (List.map str cs).`

`[explode s] is the list of characters in the string s .`

`[map f s] applies f to every character of s , from left to right,
and returns the string consisting of the resulting characters.
Equivalent to CharVector.map f s
and to implode (List.map f (explode s)).`

`[translate f s] applies f to every character of s , from left to right,
right, and returns the concatenation of the resulting strings.
Raises Size if the sum of their sizes is greater than maxSize.
Equivalent to concat (List.map f (explode s)).`

`[tokens p s] returns the list of tokens in s , from left to right,
where a token is a non-empty maximal substring of s not containing
any delimiter, and a delimiter is a character satisfying p .`

`[fields p s] returns the list of fields in s , from left to right,
where a field is a (possibly empty) maximal substring of s not
containing any delimiter, and a delimiter is a character satisfying p .`

Two tokens may be separated by more than one delimiter, whereas two
fields are separated by exactly one delimiter. If the only delimiter
is the character `"|"`, then

`"abc||def" contains two tokens: "abc" and "def"
"abc||def" contains three fields: "abc" and "" and "def"`

`[isPrefix s1 s2] is true if s_1 is a prefix of s_2 .
That is, if there exists a string u such that $s_1 \wedge u = s_2$.`

`[isSuffix s1 s2] is true if s_1 is a suffix of s_2 .
That is, if there exists a string t such that $t \wedge s_1 = s_2$.`

`[isSubstring s1 s2] is true if s_1 is a substring of s_2 .
That is, if there exist strings t and u such that $t \wedge s_1 \wedge u = s_2$.`

`[fromString s] scans the string s as an ML source program string,
converting escape sequences into the appropriate characters. Does
not skip leading whitespace.`

`[toString s] returns a string corresponding to s , with
non-printable characters replaced by ML escape sequences.`

Equivalent to `String.translate Char.toString.`

`[fromCString s]` scans the string `s` as a C source program string, converting escape sequences into the appropriate characters. Does not skip leading whitespace.

`[toCString s]` returns a string corresponding to `s`, with non-printable characters replaced by C escape sequences. Equivalent to `String.translate Char.toIntString.`

`[compare (s1, s2)]` does lexicographic comparison, using the standard ordering `Char.compare` on the characters. Returns `LESS`, `EQUAL`, or `GREATER`, according as `s1` is less than, equal to, or greater than `s2`.

`[collate cmp (s1, s2)]` performs lexicographic comparison, using the given ordering `cmp` on characters.

`[<]`
`[<=]`
`[>]`
`[>=]` compare strings lexicographically, using the representation ordering on characters.

Module StringCvt

StringCvt -- SML Basis Library

```

datatype radix = BIN | OCT | DEC | HEX

datatype realfmt =
  SCI of int option      scientific, arg = # dec. digits, dflt=6
  | FIX of int option    fixed-point, arg = # dec. digits, dflt=6
  | GEN of int option    auto choice of the above,
                        arg = # significant digits, dflt=12

type cs                  character source state

type ('a, 'b) reader = 'b -> ('a * 'b) option

val scanString : ((char, cs) reader -> ('a, cs) reader) -> string -> 'a option

val splitl    : (char -> bool) -> (char, 'a) reader -> 'a -> string * 'a
val takel    : (char -> bool) -> (char, 'a) reader -> 'a -> string
val dropl    : (char -> bool) -> (char, 'a) reader -> 'a -> 'a
val skipWS   : (char, 'a) reader -> 'a -> 'a

val padLeft   : char -> int -> string -> string
val padRight  : char -> int -> string -> string

```

This structure presents tools for scanning strings and values from functional character streams, and for simple formatting.

[('elm, 'src) reader] is the type of source readers for reading a sequence of 'elm values from a source of type 'src. For instance, a character source reader
`getc : (char, cs) reader`
is used for obtaining characters from a functional character source src of type cs, one at a time. It should hold that

```

getc src = SOME(c, src')           if the next character in src
                                    is c, and src' is the rest of src;
= NONE                            if src contains no characters

```

A character source scanner takes a character source reader getc as argument and uses it to scan a data value from the character source.

[scanString scan s] turns the string s into a character source and applies the scanner 'scan' to that source.

[splitl p getc src] returns (pref, suff) where pref is the longest prefix (left substring) of src all of whose characters satisfy p, and suff is the remainder of src. That is, the first character retrievable from suff, if any, is the leftmost character not satisfying p. Does not skip leading whitespace.

[takel p getc src] returns the longest prefix (left substring) of src all of whose characters satisfy predicate p. That is, if the left-most character does not satisfy p, the result is the empty string. Does not skip leading whitespace. It holds that
`takel p getc src = #1 (splitl p getc src)`

[dropl p getc src] drops the longest prefix (left substring) of

src all of whose characters satisfy predicate p. If all characters do, it returns the empty source. It holds that
dropl p getc src = #2 (splitl p getc src)

[skipWS getc src] drops any leading whitespace from src.
Equivalent to dropl Char.isSpace.

[padLeft c n s] returns the string s if size s >= n, otherwise pads s with (n - size s) copies of the character c on the left.
In other words, right-justifies s in a field n characters wide.

[padRight c n s] returns the string s if size s >= n, otherwise pads s with (n - size s) copies of the character c on the right.
In other words, left-justifies s in a field n characters wide.

Module Substring

Substring -- SML Basis Library

```

type substring

val substring    : string * int * int -> substring
val extract      : string * int * int option -> substring
val full         : string -> substring
val all          : string -> substring
val string       : substring -> string
val base         : substring -> (string * int * int)

val isEmpty      : substring -> bool
val getc         : substring -> (char * substring) option
val first        : substring -> char option
val triml        : int -> substring -> substring
val trimr        : int -> substring -> substring
val sub          : substring * int -> char
val size         : substring -> int
val slice         : substring * int * int option -> substring
val concat        : substring list -> string
val concatWith   : string -> substring list -> string
val explode       : substring -> char list
val compare       : substring * substring -> order
val collate      : (char * char -> order) -> substring * substring -> order

val dropl         : (char -> bool) -> substring -> substring
val dropr        : (char -> bool) -> substring -> substring
val takel        : (char -> bool) -> substring -> substring
val taker         : (char -> bool) -> substring -> substring
val splitl        : (char -> bool) -> substring -> substring * substring
val splitr        : (char -> bool) -> substring -> substring * substring
val splitAt       : substring * int -> substring * substring

val position      : string -> substring -> substring * substring
val isPrefix      : string -> substring -> bool
val isSuffix      : string -> substring -> bool
val isSubstring   : string -> substring -> bool

exception Span
val span          : substring * substring -> substring

val translate     : (char -> string) -> substring -> string
val tokens         : (char -> bool) -> substring -> substring list
val fields         : (char -> bool) -> substring -> substring list

val foldl         : (char * 'a -> 'a) -> 'a -> substring -> 'a
val foldr         : (char * 'a -> 'a) -> 'a -> substring -> 'a
val app           : (char -> unit) -> substring -> unit

```

[substring] is the type of substrings of a basestring, an efficient representation of a piece of a string.

A substring (s,i,n) is valid if $0 \leq i \leq i+n \leq \text{size } s$,
or equivalently, $0 \leq i$ and $0 \leq n$ and $i+n \leq \text{size } s$.

A valid substring (s, i, n) represents the string $s[i\dots i+n-1]$.
Invariant in the implementation: Any value of type substring is valid.

A substring is the same as a CharVectorSlice.slice, so substrings

may be processed using the functions declared in CharVectorSlice.

[substring(s, i, n)] creates the substring (s, i, n), consisting of the substring of s with length n starting at i. Raises Subscript if i<0 or n<0 or i+n > size s. Equivalent to extract(s, i, SOME n).

[extract(s, i, NONE)] creates the substring (s, i, size s-i) consisting of the tail of s starting at i. Raises Subscript if i<0 or i > size s.

[extract(s, i, SOME n)] creates the substring (s, i, n), consisting of the substring of s with length n starting at i. Raises Subscript if i<0 or n<0 or i+n > size s.

[full s] is the substring (s, 0, size s).

[all s] is the same as full(s). Its use is deprecated.

[string sus] is the string s[i..i+n-1] represented by sus = (s, i, n).

[base sus] is the concrete triple (s, i, n), where sus = (s, i, n).

[isEmpty (s, i, n)] true if the substring is empty (that is, n = 0).

[getc sus] returns SOME(c, rst) where c is the first character and rst the remainder of sus, if sus is non-empty; otherwise returns NONE. Note that

```
#1 o valOf o scanFn Substring.getc  
is equivalent to, but more efficient than,  
valOf o StringCvt.scanString scanFn o Substring.string
```

[first sus] returns SOME c where c is the first character in sus, if sus is non-empty; otherwise returns NONE.

[triml k sus] returns sus less its leftmost k characters; or the empty string at the end of sus if it has less than k characters. Raises Subscript if k < 0, even in the partial application triml(k).

[trimr k sus] returns sus less its rightmost k characters; or the empty string at the beginning of sus if it has less than k characters. Raises Subscript if k < 0, even in the partial application triml(k).

[sub (sus, k)] returns the k'th character of the substring; that is, s(i+k) where sus = (s, i, n). Raises Subscript if k<0 or k>=n.

[size sus] returns the size n of the substring sus = (s, i, n).

[slice (sus, i', NONE)] returns the substring (s, i+i', n-i'), where sus = (s, i, n). Raises Subscript if i' < 0 or i' > n.

[slice (sus, i', SOME n')] returns the substring (s, i+i', n'), where sus = (s, i, n). Raises Subscript if i' < 0 or n' < 0 or i'+n' > n.

[concat suss] returns a string consisting of the concatenation of the substrings. Equivalent to String.concat (List.map string suss). Raises Size if the resulting string would be longer than String.maxSize.

[concatWith sep suss] returns a string consisting of the concatenation of the substrings in suss, using sep as a separator. Equivalent to String.concatWith sep (List.map string suss). Raises Size if the resulting string would be longer than String.maxSize.

[explode sus] returns the list of characters of sus, that is,
 [s(i), s(i+1), ..., s(i+n-1)]
 where sus = (s, i, n). Equivalent to String=explode(string ss).

[compare (sus1, sus2)] performs lexicographic comparison, using the standard ordering Char.compare on the characters. Returns LESS, EQUAL, or GREATER, according as sus1 is less than, equal to, or greater than sus2. Equivalent to, but more efficient than,
 String.compare(string sus1, string sus2).

[collate cmp (sus1, sus2)] performs lexicographic comparison, using the given ordering cmp on characters. Equivalent to, but more efficient than, String.collate cmp (string sus1, string sus2).

[drop1 p sus] drops the longest prefix (left substring) of sus all of whose characters satisfy predicate p. If all characters do, it returns the empty substring (s, i+n, 0) where sus = (s, i, n).

[dropr p sus] drops the longest suffix (right substring) of sus all of whose characters satisfy predicate p. If all characters do, it returns the empty substring (s, i, 0) where sus = (s, i, n).

[takel p sus] returns the longest prefix (left substring) of sus all of whose characters satisfy predicate p. That is, if the left-most character does not satisfy p, returns the empty (s, i, 0) where sus = (s, i, n).

[taker p sus] returns the longest suffix (right substring) of sus all of whose characters satisfy predicate p. That is, if the right-most character satisfies p, returns the empty (s, i+n, 0) where sus = (s, i, n).

Let p be a predicate and xxxxfyfffffz a string where all characters in xxxx and zzzz satisfy p, and f a is character not satisfying p. Then

sus = xxxxfyfffffz	sus = xxxxzzzz	
<hr/>		
drop1 p sus =	fyfffffz	
dropr p sus =	xxxxfyfffff	
takel p sus =	xxxx	xxxxzzzz
taker p sus =	z	xxxxzzzz

It also holds that

concat[takel p sus, drop1 p sus] = string sus
 concat[dropr p sus, taker p sus] = string sus

[splitl p sus] splits sus into a pair (sus1, sus2) of substrings where sus1 is the longest prefix (left substring) all of whose characters satisfy p, and sus2 is the rest. That is, sus2 begins with the leftmost character not satisfying p. Disregarding sideeffects, we have:

splitl p sus = (takel p sus, drop1 p sus).

[splitr p sus] splits sus into a pair (sus1, sus2) of substrings where sus2 is the longest suffix (right substring) all of whose characters satisfy p, and sus1 is the rest. That is, sus1 ends with the rightmost character not satisfying p. Disregarding sideeffects, we have:

splitr p sus = (dropr p sus, taker p sus)

[splitAt (sus, k)] returns the pair (sus1, sus2) of substrings, where sus1 contains the first k characters of sus, and sus2 contains the rest. Raises Subscript if k < 0 or k > size sus.

[isPrefix s1 s2] is true if s1 is a prefix of s2. That is, if there exists a string u such that $s1 \wedge u = \text{string } s2$.

[isSuffix s1 s2] is true if s1 is a suffix of s2. That is, if there exists a string t such that $t \wedge s1 = \text{string } s2$.

[isSubstring s1 s2] is true if s1 is a substring of s2. That is, if there exist strings t and u such that $t \wedge s1 \wedge u = \text{string } s2$.

[position s (s', i, n)] splits the substring into a pair (pref, suff) of substrings, where suff is the longest suffix of (s', i, n) which has s as a prefix. More precisely, let m = size s. If there is a least index k in i..i+n-m for which $s = s'[k..k+m-1]$, then the result is pref = (s', i, k-i) and suff = (s', k, n-(k-i)); otherwise the result is pref = (s', i, n) and suff = (s', i+n, 0).

[span (sus1, sus2)] returns a substring spanning from the start of sus1 to the end of sus2, provided this is well-defined: sus1 and sus2 must have the same underlying string, and the start of sus1 must not be to the right of the end of sus2; otherwise raises Span.

More precisely, if base(sus1) = (s, i, n) and base(sus2) = (s', i', n') and s = s' and i <= i'+n', then base(join(sus1, sus2)) = (s, i, i'+n'-i). This may be used to compute 'span', 'union', and 'intersection'.

[translate f sus] applies f to every character of sus, from left to right, and returns the concatenation of the results. Raises Size if the sum of their sizes is greater than String.maxSize. Equivalent to String.concat(List.map f (explode sus)).

[tokens p sus] returns the list of tokens in sus, from left to right, where a token is a non-empty maximal substring of sus not containing any delimiter, and a delimiter is a character satisfying p.

[fields p sus] returns the list of fields in sus, from left to right, where a field is a (possibly empty) maximal substring of sus not containing any delimiter, and a delimiter is a character satisfying p.

Two tokens may be separated by more than one delimiter, whereas two fields are separated by exactly one delimiter. If the only delimiter is the character "#|", then

"abc||def" contains two tokens: "abc" and "def"

"abc||def" contains three fields: "abc" and "" and "def"

[foldl f e sus] folds f over sus from left to right. That is, evaluates f(s[i+n-1], f(... f(s[i+1], f(s[i] % e)) ...)) tail-recursively, where sus = (s, i, n). Equivalent to List.foldl f e (explode sus).

[foldr f e sus] folds f over sus from right to left. That is, evaluates f(s[i], f(s[i+1], f(... f(s[i+n-1] % e) ...))) tail-recursively, where sus = (s, i, n). Equivalent to List.foldr f e (explode sus).

[app f sus] applies f to all characters of sus, from left to right. Equivalent to List.app f (explode sus).

Module Susp

Susp -- support for lazy evaluation

```
type 'a susp

val delay : (unit -> 'a) -> 'a susp
val force : 'a susp -> 'a
```

[*'a susp*] is the type of lazily evaluated expressions with result type '*a*.

[*delay (fn () => e)*] creates a suspension for the expression *e*. The first time the suspension is forced, the expression *e* will be evaluated, and the result stored in the suspension. All subsequent forcing of the suspension will just return this result, so *e* is evaluated at most once. If the suspension is never forced, then *e* is never evaluated.

[*force su*] forces the suspension *su* and returns the result of the expression *e* stored in the suspension.

Module TextIO

TextIO -- SML Basis Library

```

type elem    = Char.char
type vector = string

Text input

type instream

val openIn      : string -> instream
val closeIn     : instream -> unit
val input       : instream -> vector
val inputAll    : instream -> vector
val inputNoBlock: instream -> vector option
val input1      : instream -> elem option
val inputN      : instream * int -> vector
val inputLine   : instream -> string option
val endOfStream: instream -> bool
val lookahead   : instream -> elem option

type cs character source state

val scanStream  : ((char, cs) StringCvt.reader -> ('a, cs) StringCvt.reader)
                  -> instream -> 'a option

val stdIn       : instream

Text output

type outstream

val openOut     : string -> outstream
val openAppend  : string -> outstream
val closeOut    : outstream -> unit
val output      : outstream * vector -> unit
val output1     : outstream * elem -> unit
val outputSubstr: outstream * substring -> unit
val flushOut    : outstream -> unit

val stdOut      : outstream
val stdErr      : outstream

val print       : string -> unit

```

This structure provides input/output functions on text streams. The functions are state-based: reading from or writing to a stream changes the state of the stream. The streams are buffered: output to a stream may not immediately affect the underlying file or device.

Note that under DOS, Windows, OS/2, and MacOS, text streams will be 'translated' by converting (e.g.) the double newline CRLF to a single newline character '\n'.

[instream] is the type of state-based character input streams.

[outstream] is the type of state-based character output streams.

[elem] is the type char of characters.

[vector] is the type of character vectors, that is, strings.

TEXT INPUT:

[openIn s] creates a new instream associated with the file named s. Raises Io.Io is file s does not exist or is not accessible.

[closeIn istr] closes stream istr. Has no effect if istr is closed already. Further operations on istr will behave as if istr is at end of stream (that is, will return "" or NONE or true).

[input istr] reads some elements from istr, returning a vector v of those elements. The vector will be empty (size v = 0) if and only if istr is at end of stream or is closed. May block (not return until data are available in the external world).

[inputAll istr] reads and returns the string v of all characters remaining in istr up to end of stream.

[inputNoBlock istr] returns SOME(v) if some elements v can be read without blocking; returns SOME("") if it can be determined without blocking that istr is at end of stream; returns NONE otherwise. If istr does not support non-blocking input, raises Io.NonblockingNotSupported.

[input1 istr] returns SOME(e) if at least one element e of istr is available; returns NONE if istr is at end of stream or is closed; blocks if necessary until one of these conditions holds.

[inputN(istr, n)] returns the next n characters from istr as a string, if that many are available; returns all remaining characters if end of stream is reached before n characters are available; blocks if necessary until one of these conditions holds. (This is the behaviour of the 'input' function prescribed in the 1990 Definition of Standard ML).

[inputLine istr] returns SOME ln, where ln is one line of text, including the terminating newline character. If end of stream is reached before a newline character, then the remaining part of the stream is returned, with a newline character added. If istr is at end of stream or is closed, then NONE is returned.

[endOfStream istr] returns false if any elements are available in istr; returns true if istr is at end of stream or closed; blocks if necessary until one of these conditions holds.

[lookahead istr] returns SOME(e) where e is the next element in the stream; returns NONE if istr is at end of stream or is closed; blocks if necessary until one of these conditions holds. Does not advance the stream.

[stdIn] is the buffered state-based standard input stream.

[scanStream scan istr] turns the instream istr into a character source and applies the scanner 'scan' to that source. See StringCvt for more on character sources and scanners. The Moscow ML implementation currently can backtrack only 512 characters, and raises Fail if the scanner backtracks further than that.

TEXT OUTPUT:

[openOut s] creates a new outstream associated with the file named s. If file s does not exist, and the directory exists and is writable, then a new file is created. If file s exists, it is truncated (any existing contents are lost).

[openAppend s] creates a new outstream associated with the file named s. If file s does not exist, and the directory exists and is writable, then a new file is created. If file s exists, any existing contents are retained, and output goes at the end of the file.

[closeOut ostr] closes stream ostr; further operations on ostr (except for additional close operations) will raise exception Io.Io.

[output(ostr, v)] writes the string v on outstream ostr.

[output1(ostr, e)] writes the character e on outstream ostr.

[flushOut ostr] flushes the outstream ostr, so that all data written to ostr becomes available to the underlying file or device.

[stdOut] is the buffered state-based standard output stream.

[stdErr] is the unbuffered state-based standard error stream. That is, it is always kept flushed, so flushOut(stdErr) is redundant.

[print s] outputs s to stdOut and flushes immediately.

The functions below are not yet implemented:

[setPosIn(istr, i)] sets istr to the (untranslated) position i. Raises Io.Io if not supported on istr.

[getPosIn istr] returns the (untranslated) current position of istr. Raises Io.Io if not supported on istr.

[endPosIn istr] returns the (untranslated) last position of istr. Because of translation, one cannot expect to read
 endPosIn istr - getPosIn istr
from the current position.

[getPosOut ostr] returns the current position in stream ostr. Raises Io.Io if not supported on ostr.

[endPosOut ostr] returns the ending position in stream ostr. Raises Io.Io if not supported on ostr.

[setPosOut(ostr, i)] sets the current position in stream to ostr to i. Raises Io.Io if not supported on ostr.

[mkInstream sistr] creates a state-based instream from the functional instream sistr.

[getInstream istr] returns the functional instream underlying the state-based instream istr.

[setInstream(istr, sistr)] redirects istr, so that subsequent input is taken from the functional instream sistr.

[mkOutstream sostr] creates a state-based outstream from the outstream sostr.

[getOutstream ostr] returns the outstream underlying the state-based outstream ostr.

[setOutstream(ostr, sostr)] redirects the outstream ostr so that subsequent output goes to sostr.

Module Time

```
Time -- SML Basis Library

eqtype time

exception Time

val zeroTime      : time
val now           : unit -> time

val toSeconds     : time -> int
val toMilliseconds : time -> int
val toMicroseconds: time -> int
val fromSeconds   : int -> time
val fromMilliseconds: int -> time
val fromMicroseconds: int -> time

val fromReal      : real -> time
val toReal         : time -> real

val toString       : time -> string rounded to millisecond precision
val fmt            : int -> time -> string
val fromString    : string -> time option
val scan           : (char, 'a) StringCvt.reader
                     -> (time, 'a) StringCvt.reader

val +              : time * time -> time
val -              : time * time -> time
val <              : time * time -> bool
val <=             : time * time -> bool
val >              : time * time -> bool
val >=             : time * time -> bool

val compare : time * time -> order
```

[time] is a type for representing durations as well as absolute points in time (which can be thought of as durations since some fixed time zero). Times can be negative, zero, or positive.

[zeroTime] represents the 0-second duration, and the origin of time, so zeroTime + t = t + zeroTime = t for all t.

[now ()] returns the point in time at which the application occurs.

[fromSeconds s] returns the time value corresponding to s seconds.

[fromMilliseconds ms] returns the time value corresponding to ms milliseconds.

[fromMicroseconds us] returns the time value corresponding to us microseconds.

[toSeconds t] returns the number of seconds represented by t, truncated (towards zero). Raises Overflow if that number is not representable as an int.

[toMilliseconds t] returns the number of milliseconds represented by t, truncated (towards zero). Raises Overflow if that number is not representable as an int.

[toMicroseconds t] returns the number of microseconds represented by t, truncated (towards zero). Raises Overflow if t is not representable as an int.

[fromReal r] converts a real to a time value representing that many seconds. It holds that fromReal 0.0 = zeroTime.

[toReal t] converts a time to the number of seconds it represents; hence fromReal and toReal are inverses of each other.

[fmt n t] returns as a string the number of seconds represented by t, rounded to n decimal digits. If n <= 0, then no decimal digits are reported.

[toString t] returns as a string the number of seconds represented by t, rounded to 3 decimal digits. Equivalent to (fmt 3 t).

[fromString s] returns SOME t where t is the time value represented by the string s of form [\n\t]*[+~-]?(([0-9]+(\.[0-9]+)?))|(\.[0-9]+)); or returns NONE if s cannot be parsed as a time value.

[scan getc src], where getc is a character accessor, returns SOME (t, rest) where t is a time and rest is rest of the input, or NONE if s cannot be parsed as a time value.

[+] adds two time values. For reals r1, r2 >= 0.0, it holds that fromReal r1 + fromReal r2 = fromReal(Real.+ (r1, r2)). Raises Overflow if the result is not representable as a time value.

[-] subtracts a time value from another. That is, t1 - t2 is the duration from t2 to t1 (which may be negative). It holds that t - zeroTime = t.

[<]
[<=]
[>]

[>=] compares time values. For instance, for reals r1, r2 >= 0.0 it holds that fromReal r1 < fromReal r2 iff Real.<(r1, r2)

[compare(t1, t2)] returns LESS, EQUAL, or GREATER, according as t1 precedes, equals, or follows t2 in time.

Module Timer

Timer -- SML Basis Library

```
type cpu_timer
type real_timer

val startCPUTimer : unit -> cpu_timer
val totalCPUTimer : unit -> cpu_timer
val checkCPUTimer : cpu_timer -> { usr : Time.time, sys : Time.time }
val checkGCTime : cpu_timer -> Time.time
val checkCPUTimes : cpu_timer -> { nongc : {usr : Time.time, sys : Time.time},
                                    gc      : {usr : Time.time, sys : Time.time}
                                   }

val startRealTimer : unit -> real_timer
val totalRealTimer : unit -> real_timer
val checkRealTimer : real_timer -> Time.time
```

[cpu_timer] is the type of timers for measuring CPU time consumption (user time, garbage collection time, and system time).

[real_timer] is the type of timers for measuring the passing of real time (wall-clock time).

[startCPUTimer ()] returns a cpu_timer started at the moment of the call.

[totalCPUTimer ()] returns a cpu_timer started at the moment the library was loaded.

[checkCPUTimer tmr] returns {usr, sys} where usr is the amount of user CPU time consumed since tmr was started and sys is the amount of system CPU time consumed since tmr was started. Note that garbage collection time is included in the usr time. Under MS DOS and MS Windows, usr time is measured as real time.

[checkGCTime tmr] returns the amount of user CPU time spent on garbage collection since tmr was started. Under MS DOS and MS Windows, gc time is measured in real time.

[checkCPUTimes tmr] returns the amount of CPU time consumed since tmr was started spilt into time spent in the program (nongc) and on garbage collecttion (gc). For both nongc and gc a record {usr, sys} is returned where usr is the amount of user CPU time consumed since tmr was started and sys is the amount of system CPU time consumed since tmr was started. Note that Moscow ML will allways attribute all the system CPU time to the program (nongc). That is, #sys(#gc(checkCPUTimes tmr)) is always 0.

[startRealTimer ()] returns a real_timer started at the moment of the call.

[totalRealTimer ()] returns a real_timer started at the moment the library was loaded.

[checkRealTimer tmr] returns the amount of real time that has passed since tmr was started.

Module Unix

```
Unix -- SML Basis Library
signature Unix = sig
  type ('a, 'b) proc
  type signal = Signal.signal

  val executeInEnv    : string * string list * string list -> ('a, 'b) proc
  val execute        : string * string list -> ('a, 'b) proc

  val streamsOf      : (TextIO.instream, TextIO.outstream) proc
                        -> TextIO.instream * TextIO.outstream
  val textInstreamOf : (TextIO.instream, 'a) proc -> TextIO.instream
  val textOutstreamOf: ('a, TextIO.outstream) proc -> TextIO.outstream
  val binInstreamOf  : (BinIO.instream, 'a) proc -> BinIO.instream
  val binOutstreamOf: ('a, BinIO.outstream) proc -> BinIO.outstream
  val kill           : ('a, 'b) proc * signal -> unit
  val reap           : ('a, 'b) proc -> OS.Process.status
end
```

This structure allows Moscow ML programs to start other processes and to communicate with them.

Child processes are not automatically terminated when the parent (ML) process terminates. To forcibly terminate a child process *pr*, use *Unix.kill(pr, Signal.term)*. Then, to remove the terminated process from the operating system tables, call *Unix.reap(pr)*.

The protocol for communication between the ML program and its child process must be designed with some care, typically using non-blocking input for reading from the child process.

[*proc*] is the type of processes started by the ML program.

[*signal*] is the type of Unix-style signals, which can be sent to another process. Signal values must be obtained from the *Signal* structure.

[*execute (cmd, args)*] asks the operating system to execute the command *cmd* with the argument list *args*, as a separate process. Two pipes connected to the standard input and standard output of the new process are created; these may be obtained using *streamsOf*. A *proc* value representing the new process is returned. The new process executes using the same environment as the calling process. Raises *Fail* in case of failure, e.g. if the process or the pipes cannot be created.

Typically, the *cmd* argument will be the full pathname of an executable. On Unix systems, simple command searching as done by the shell, allowing *cmd* to be a relative pathname, can be achieved by using

```
execute("/bin/sh", "-c" :: concat (cmd :: " " :: args))
```

[*executeInEnv (cmd, args, env)*] asks the operating system to execute the command *cmd* with the argument list *args* in the environment *env*, as a separate process. Returns a *proc* value representing the new process. Typically, a string in the *env* list has the form "NAME=VALUE". See also *Process.getEnv*.

[*streamsOf pr*] returns a pair (*ins, outs*) of input and output streams associated with process *pr*. The standard output of *pr* is

the source for the input stream ins, and the standard input of pr is the sink for the output stream outs.

[textInstreamOf pr] returns the text input stream associated with process pr. That is, the standard output of pr.

[textOutstreamOf pr] returns the text output stream associated with process pr. That is, the standard input of pr.

[binInstreamOf pr] returns the binary input stream associated with process pr. That is, the standard output of pr.

[binOutstreamOf pr] returns the binary output stream associated with process pr. That is, the standard input of pr.

[reap pr] closes the input and output streams associated with pr, and then suspends the current (ML) process until the process corresponding to pr terminates. Returns the exit status given by pr when it terminated. Raises Fail in case of failure, e.g. if pr has already been reaped.

Under Unix, information about a terminated process remains in the system tables until the process is reaped. Thus, an ML program using execute or executeInEnv must make sure to reap any process it has created, or else the system tables will fill up.

[kill (pr, s)] sends the signal s to the process pr. Raises Fail in case of failure, e.g. if pr has already been killed.

Module Vector

Vector -- SML Basis Library

```
type 'a vector = 'a vector
val maxLen    : int
val fromList  : 'a list -> 'a vector
val tabulate  : int * (int -> 'a) -> 'a vector
val length    : 'a vector -> int
val sub       : 'a vector * int -> 'a
val update   : 'a vector * int * 'a -> 'a vector
val concat   : 'a vector list -> 'a vector
val find      : ('a -> bool) -> 'a vector -> 'a option
val exists   : ('a -> bool) -> 'a vector -> bool
val all       : ('a -> bool) -> 'a vector -> bool
val app       : ('a -> unit) -> 'a vector -> unit
val map       : ('a -> 'b) -> 'a vector -> 'b vector
val foldl    : ('a * 'b -> 'b) -> 'b -> 'a vector -> 'b
val foldr    : ('a * 'b -> 'b) -> 'b -> 'a vector -> 'b
val findi    : (int * 'a -> bool) -> 'a vector -> (int * 'a) option
val appi     : (int * 'a -> unit) -> 'a vector -> unit
val mapi     : (int * 'a -> 'b) -> 'a vector -> 'b vector
val foldli   : (int * 'a * 'b -> 'b) -> 'b -> 'a vector -> 'b
val foldri   : (int * 'a * 'b -> 'b) -> 'b -> 'a vector -> 'b
val collate  : ('a * 'a -> order) -> 'a vector * 'a vector -> order
```

[*'ty vector*] is the type of one-dimensional, immutable, zero-based constant-time-access vectors with elements of type '*ty*.

Type '*'ty vector*' admits equality if '*'ty*' does. Vectors *v1* and *v2* are equal if they have the same length and their elements are equal.

[*maxLen*] is the maximal number of elements in a vector.

[*fromList xs*] returns a vector whose elements are those of *xs*. Raises *Size* if *length xs > maxLen*.

[*tabulate(n, f)*] returns a vector of length *n* whose elements are *f 0, f 1, ..., f (n-1)*, created from left to right. Raises *Size* if *n<0* or *n>maxLen*.

[*length v*] returns the number of elements in *v*.

[*sub(v, i)*] returns the *i*'th element of *v*, counting from 0. Raises *Subscript* if *i<0* or *i>=length v*.

[*update(v, i, x)*] creates a copy of *v*, sets position *i* to *x*, and returns the new vector. In contrast to *Array.update*, this is not a constant-time operation, because it must copy the entire vector. Raises *Subscript* if *i<0* or *i>=length v*.

[*concat vs*] returns a vector which is the concatenation from left to right of the vectors in *vs*. Raises *Size* if the sum of the sizes of the vectors in *vs* is larger than *maxLen*.

[find p v] applies p to each element x of v, from left to right, until p(x) evaluates to true; returns SOME x if such an x exists, otherwise NONE.

[exists p v] applies p to each element x of v, from left to right, until p(x) evaluates to true; returns true if such an x exists, otherwise false.

[all p v] applies p to each element x of v, from left to right, until p(x) evaluates to false; returns false if such an x exists, otherwise true.

[foldl f e v] folds function f over v from left to right. That is, computes f(v[len-1], f(v[len-2], ..., f(v[1], f(v[0], e)) ...)), where len is the length of v.

[foldr f e v] folds function f over v from right to left. That is, computes f(v[0], f(v[1], ..., f(v[len-2], f(v[len-1], e)) ...)), where len is the length of v.

[app f v] applies f to v[j] for j=0,1,...,length v-1.

[map f v] applies f to v[j] for j=0,1,...,length v-1 and returns a new vector containing the results.

The following iterators generalize the above ones by passing also the vector element index j to the function being iterated.

[findi p a] applies f to successive pairs (j, a[j]) for j=0,1,...,n-1, until p(j, a[j]) evaluates to true; returns SOME (j, a[j]) if such a pair exists, otherwise NONE.

[foldli f e v] folds function f over the vector from left to right. That is, computes f(n-1, v[n-1], f(..., f(1, v[1], f(0, v[0], e)) ...)) where n = length v.

[foldri f e v] folds function f over the vector from right to left. That is, computes f(0, v[0], f(1, v[1], ..., f(n-1, v[n-1], e) ...)) where n = length v.

[appi f v] applies f to successive pairs (j, v[j]) for j=0,1,...,n-1 where n = length v.

[mapi f v] applies f to successive pairs (j, v[j]) for j=0,1,...,n-1 where n = length v and returns a new vector containing the results.

[collate cmp (xs, ys)] returns LESS, EQUAL or GREATER according as xs precedes, equals or follows ys in the lexicographic ordering on vectors induced by the ordering cmp on elements.

Module VectorSlice

VectorSlice -- SML Basis Library

```
type 'a slice

val length    : 'a slice -> int
val sub       : 'a slice * int -> 'a
val slice     : 'a Vector.vector * int * int option -> 'a slice
val full      : 'a Vector.vector -> 'a slice
val subslice  : 'a slice * int * int option -> 'a slice
val base      : 'a slice -> 'a Vector.vector * int * int
val vector    : 'a slice -> 'a Vector.vector
val concat    : 'a slice list -> 'a Vector.vector
val isEmpty   : 'a slice -> bool
val getItem   : 'a slice -> ('a * 'a slice) option

val find      : ('a -> bool) -> 'a slice -> 'a option
val exists   : ('a -> bool) -> 'a slice -> bool
val all       : ('a -> bool) -> 'a slice -> bool

val app       : ('a -> unit) -> 'a slice -> unit
val map       : ('a -> 'b) -> 'a slice -> 'b Vector.vector
val foldl    : ('a * 'b -> 'b) -> 'b -> 'a slice -> 'b
val foldr    : ('a * 'b -> 'b) -> 'b -> 'a slice -> 'b

val findi    : (int * 'a -> bool) -> 'a slice -> (int * 'a) option
val appi     : (int * 'a -> unit) -> 'a slice -> unit
val mapi     : (int * 'a -> 'b) -> 'a slice -> 'b Vector.vector
val foldli   : (int * 'a * 'b -> 'b) -> 'b -> 'a slice -> 'b
val foldri   : (int * 'a * 'b -> 'b) -> 'b -> 'a slice -> 'b

val collate  : ('a * 'a -> order) -> 'a slice * 'a slice -> order
```

[*'ty slice*] is the type of vector slices, that is, sub-vectors.
The slice (a, i, n) is valid if $0 \leq i \leq i+n \leq \text{size } s$,
or equivalently, $0 \leq i$ and $0 \leq n$ and $i+n \leq \text{size } s$.
A valid slice $sli = (a, i, n)$ represents the sub-vector $a[i \dots i+n-1]$,
so the elements of sli are $a[i], a[i+1], \dots, a[i+n-1]$, and n is
the length of the slice. Only valid slices can be constructed by
the functions below.

[length *sli*] returns the number n of elements in $sli = (s, i, n)$.

[sub (*sli*, *k*)] returns the k 'th element of the slice, that is,
 $a(i+k)$ where $sli = (a, i, n)$. Raises Subscript if $k < 0$ or $k \geq n$.

[slice (*a*, *i*, NONE)] creates the slice $(a, i, \text{length } a-i)$,
consisting of the tail of *a* starting at *i*.
Raises Subscript if $i < 0$ or $i > \text{Vector.length } a$.
Equivalent to slice (*a*, *i*, SOME(Vector.length *a* - *i*)).

[slice (*a*, *i*, SOME *n*)] creates the slice (a, i, n) , consisting of
the sub-vector of *a* with length *n* starting at *i*. Raises Subscript
if $i < 0$ or $n < 0$ or $i+n > \text{Vector.length } a$.

slice	meaning	
<i>(a, 0, NONE)</i>	the whole vector	$a[0..len-1]$
<i>(a, 0, SOME n)</i>	a left sub-vector (prefix)	$a[0..n-1]$

```

(a, i, NONE)      a right sub-vector (suffix)    a[i..len-1]
(a, i, SOME n)   a general slice                a[i..i+n-1]

[full a] creates the slice (a, 0, Vector.length a).
Equivalent to slice(a,0,NONE)

[subslice (sli, i', NONE)] returns the slice (a, i+i', n-i') when
sli = (a,i,n). Raises Subscript if i' < 0 or i' > n.

[subslice (sli, i', SOME n')] returns the slice (a, i+i', n') when
sli = (a,i,n). Raises Subscript if i' < 0 or n' < 0 or i'+n' > n.

[base sli] is the concrete triple (a, i, n) when sli = (a, i, n).

[vector sli] creates and returns a vector consisting of the
elements of the slice, that is, a[i..i+n-1] when sli = (a,i,n).

[concat slis] creates a vector containing the concatenation of the
slices in slis.

[isEmpty sli] returns true if the slice sli = (a,i,n) is empty,
that is, if n=0.

[getItem sli] returns SOME(x, rst) where x is the first element and
rst the remainder of sli, if sli is non-empty; otherwise returns
NONE.

[find p sli] applies p to each element x of sli, from left to
right, until p(x) evaluates to true; returns SOME x if such an x
exists, otherwise NONE.

[exists p sli] applies p to each element x of sli, from left to right,
until p(x) evaluates to true; returns true if such an x exists,
otherwise false.

[all p sli] applies p to each element x of sli, from left to right,
until p(x) evaluates to false; returns false if such an x exists,
otherwise true.

[app f sli] applies f to all elements of sli = (a,i,n), from
left to right. That is, applies f to a[j+i] for j=0,1,...,n.

[map f sli] applies f to all elements of sli = (a,i,n), from left
to right, and returns a vector of the results.

[foldl f e sli] folds function f over sli = (a,i,n) from left to right.
That is, computes f(a[i+n-1], f(a[i+n-2],..., f(a[i+1], f(a[i], e))....)).

[foldr f e sli] folds function f over sli = (a,i,n) from right to left.
That is, computes f(a[i], f(a[i+1],..., f(a[i+n-2], f(a[i+n-1], e))....)).

The following iterators generalize the above ones by also passing
the index into the vector a underlying the slice to the function
being iterated.

[findi p sli] applies p to the elements of sli = (a,i,n) and the
underlying vector indices, and returns the least (j, a[j]) for
which p(j, a[j]) evaluates to true, if any; otherwise returns NONE.
That is, evaluates p(j, a[j]) for j=i,..i+n-1 until it evaluates to
true for some j, then returns SOME(j, a[j]); otherwise returns NONE.

```

[appi f sli] applies f to the slice sli = (a,i,n) and the underlying vector indices. That is, applies f to successive pairs (j, a[j]) for j=i,i+1,...,i+n-1.

[mapi f sli] applies f to the slice sli = (a,i,n) and the underlying vector indices, and returns a vector of the results. That is, applies f to successive pairs (j, a[j]) for j=i,i+1,...,i+n-1, and returns #[f(i,a[i]), ..., f(i+n-1,a[i+n-1])].

[foldli f e sli] folds function f over the slice sli = (a,i,n) and the underlying vector indices from left to right. That is, computes f(i+n-1, a[i+n-1], f(..., f(i+1, a[i+1], f(i, a[i], e)) ...)).

[foldri f e sli] folds function f over the slice sli = (a,i,n) and the underlying vector indices from right to left. That is, computes f(i, a[i], f(i+1, a[i+1], ..., f(i+n-1, a[i+n-1], e) ...)).

[collate cmp (sli1, sli2)] returns LESS, EQUAL or GREATER according as sli1 precedes, equals or follows sli2 in the lexicographic ordering on slices induced by the ordering cmp on elements.

Module Weak

Weak --- weak pointers and arrays of weak pointers

Single weak pointers

```
type 'a weak
val weak    : 'a -> 'a weak
val set     : 'a weak * 'a -> unit
val get     : 'a weak -> 'a
val isweak  : 'a weak -> bool
```

Raises Fail

Arrays of weak pointers

prim_EQtype 'a array

```
val maxlen : int
val array   : int -> '_a array
val sub     : 'a array * int -> 'a
val update  : 'a array * int * 'a -> unit
val isdead  : 'a array * int -> bool
val length  : 'a array -> int
```

Raises Size

Raises Fail and Subscript

Raises Subscript

Raises Subscript

```
val app     : ('a -> unit) -> 'a array -> unit
val foldl   : ('a * 'b -> 'b) -> 'b -> 'a array -> 'b
val foldr   : ('a * 'b -> 'b) -> 'b -> 'a array -> 'b
val modify  : ('a -> 'a) -> 'a array -> unit

val appi    : (int * 'a -> unit) -> 'a array * int * int option -> unit
val foldli  : (int * 'a * 'b -> 'b) -> 'b -> 'a array * int * int option
           -> 'b
val foldri  : (int * 'a * 'b -> 'b) -> 'b -> 'a array * int * int option
           -> 'b
val modifyi : (int * 'a -> 'a) -> 'a array * int * int option -> unit
```

[`a weak] is the type of weak pointers to objects of type 'a. A weak pointer is a pointer that cannot itself keep an object alive. Hence the object pointed to by a weak pointer may be deallocated by the garbage collector if the object is reachable only by weak pointers. In this case, subsequent accesses via the 'get' function will raise Fail "Dangling weak pointer". (We raise an exception instead of returning an option value, because access via a weak pointer to a deallocated object is likely to be a programming error).

Integers, characters, words and booleans will not be deallocated by the garbage collector and will remain reachable forever by a weak pointer. Reals, strings, tuples and other non-nullary constructors may be deallocated by the garbage collector. Compile-time constants, even composite ones, will not be deallocated either.

[weak v] creates and returns a weak pointer to value v.

[get w] returns the value pointed to by weak pointer w, if the value is still alive. Otherwise raises Fail "Dangling weak pointer".

[set(w, v)] makes the weak pointer w point to the value v.

[isweak w] returns true if the value pointed to by w is dead;

returns false otherwise. If an object is reported to be dead, it remains dead. However, an object is reported to be live just if it has not yet been deallocated by the garbage collector. The allocation of any new value may activate the garbage collector and cause the object to die. Thus

```
if not (isweak w) then get w else "blah"
will not raise exception Fail, whereas the following might:
if not (isweak w) then ([1,2] @ [3,4]; get w) else "blah"
because evaluation of the list append may cause w to die.
```

The value of isweak w is the same as that of
`(get w; false)` handle Fail _ => true
 but evaluating the latter expression may have the side effect of keeping w alive for slightly longer, because a pointer to w is returned by get w.

`['a array]` is the type of arrays of weak pointers to objects of type `'a`.

A value of type `'a Weak.weak` (above) is equivalent to, but more efficient than, a one-element `'a Weak.array`. On the other hand, an `'a Weak.array` is more efficient than an `('a Weak.weak) Array.array`.

`[array n]` creates an array of n weak pointers. Initially, any access to the array will raise Fail.

`[sub(a, i)]` returns the object pointed to by cell i (counting from 0) of the array a, if it is live. Raises Fail "Dangling weak pointer" if cell i has never been updated or if the object pointed to has been deallocated by the garbage collector. Raises Subscript if $i < 0$ or $i >= \text{length } a$. To make 'sub' infix, use the declaration
`infix 9 sub`

`[update(a, i, v)]` updates cell i of array a to point (weakly) to the value v. Raises Subscript if $i < 0$ or $i >= \text{length } a$.

`[isdead(a, i)]` returns true if the object in cell i of array a is dead, and false otherwise. Analogous to isweak; see above.

`[length a]` returns the number of elements in a.

`[maxLen]` is the maximal number of elements in an array.

The iterators described below operate on the live elements only. Note that an element $a[k]$ may die in the course of folding f over earlier elements (e.g. $a[1] \dots a[k-1]$). Thus the functions should be used with great care.

`[foldl f e a]` folds function f over the live elements of a, from left to right.

`[foldr f e a]` folds function f over the live elements of a, from right to left.

`[app f a]` applies f to the live elements of a from left to right.

`[modify f a]` applies f to $a[j]$ and updates $a[j]$ with the result $f(a[j])$, for each live element $a[j]$, from left to right.

The following iterators generalize the above ones in two ways:

- . the index j is also being passed to the function being iterated;
- . the iterators work on a slice (subarray) of an array.

The slice $(a, i, \text{SOME } n)$ denotes the subarray $a[i..i+n-1]$. That is, $a[i]$ is the first element of the slice, and n is the length of the slice. Valid only if $0 \leq i \leq i+n \leq \text{length } a$.

The slice (a, i, NONE) denotes the subarray $a[i..\text{length } a-1]$. That is, the slice denotes the suffix of the array starting at i . Valid only if $0 \leq i \leq \text{length } a$. Equivalent to $(a, i, \text{SOME}(\text{length } a - i))$.

slice	meaning	
$(a, 0, \text{NONE})$	the whole array	$a[0..\text{len}-1]$
$(a, 0, \text{SOME } n)$	a left subarray (prefix)	$a[0..n-1]$
(a, i, NONE)	a right subarray (suffix)	$a[i..\text{len}-1]$
$(a, i, \text{SOME } n)$	a general slice	$a[i..i+n-1]$

`[foldli f e (a, i, SOME n)]` folds function f over the live elements of the subarray $a[i..i+n-1]$ from left to right. Raises Subscript if $i < 0$ or $n < 0$ or $i+n > \text{length } a$.

`[foldli f e (a, i, NONE)]` folds function f over the live elements of the subarray $a[i..\text{len}-1]$ from left to right, where $\text{len} = \text{length } a$. Raises Subscript if $i < 0$ or $i > \text{length } a$.

`[foldri f e (a, i, SOME n)]` folds function f over the live elements of the subarray $a[i..i+n-1]$ from right to left. Raises Subscript if $i < 0$ or $n < 0$ or $i+n > \text{length } a$.

`[foldri f e (a, i, NONE)]` folds function f over the live elements of the subarray $a[i..\text{len}-1]$ from right to left, where $\text{len} = \text{length } a$. Raises Subscript if $i < 0$ or $i > \text{length } a$.

`[appi f (a, i, SOME n)]` applies f to successive pairs $(j, a[j])$ for $j=i, i+1, \dots, i+n-1$, provided $a[j]$ is live. Raises Subscript if $i < 0$ or $n < 0$ or $i+n > \text{length } a$.

`[appi f (a, i, NONE)]` applies f to successive pairs $(j, a[j])$ for $j=i, i+1, \dots, \text{len}-1$, where $\text{len} = \text{length } a$, provided $a[j]$ is live. Raises Subscript if $i < 0$ or $i > \text{length } a$.

`[modifyi f (a, i, SOME n)]` applies f to $(j, a[j])$ and updates $a[j]$ with the result $f(j, a[j])$ for $j=i, i+1, \dots, i+n-1$, provided $a[j]$ is live. Raises Subscript if $i < 0$ or $n < 0$ or $i+n > \text{length } a$.

`[modifyi f (a, i, NONE)]` applies f to $(j, a[j])$ and updates $a[j]$ with the result $f(j, a[j])$ for $j=i, i+1, \dots, \text{len}-1$, provided $a[j]$ is live. Raises Subscript if $i < 0$ or $i > \text{length } a$.

Module Word

Word -- SML Basis Library

```

type word = word

val wordSize    : int

val orb         : word * word -> word
val andb        : word * word -> word
val xorb        : word * word -> word
val notb        : word -> word
val ~           : word -> word

val <<          : word * word -> word
val >>          : word * word -> word
val ~>>         : word * word -> word

val +            : word * word -> word
val -            : word * word -> word
val *            : word * word -> word
val div          : word * word -> word
val mod          : word * word -> word

val >            : word * word -> bool
val <            : word * word -> bool
val >=           : word * word -> bool
val <=           : word * word -> bool
val compare      : word * word -> order

val min          : word * word -> word
val max          : word * word -> word

val toString     : word -> string
val fromString   : string -> word option
val scan          : StringCvt.radix
                  -> (char, 'a) StringCvt.reader -> (word, 'a) StringCvt.reader
val fmt           : StringCvt.radix -> word -> string

val.toInt        : word -> int
val.toIntX       : word -> int           with sign extension
val.fromInt      : int -> word

val.toLarge      : word -> word
val.toLargeX     : word -> word           with sign extension
val.fromLarge    : word -> word

val.toLargeWord  : word -> word
val.toLargeWordX : word -> word           with sign extension
val.fromLargeWord: word -> word

val.toLargeInt   : word -> int
val.toLargeIntX  : word -> int           with sign extension
val.fromLargeInt : int -> word

```

[word] is the type of n-bit words, or n-bit unsigned integers.

[wordSize] is the value of n above. In Moscow ML, n=31 on 32-bit machines and n=63 on 64-bit machines.

[orb(w1, w2)] returns the bitwise 'or' of w1 and w2.

[andb(w1, w2)] returns the bitwise 'and' of w1 and w2.

[xorb(w1, w2)] returns the bitwise 'exclusive or' of w1 and w2.

[notb w] returns the bitwise negation (one's complement) of w.

[~ w] returns the arithmetic negation (two's complement) of w.

[<<(w, k)] returns the word resulting from shifting w left by k bits. The bits shifted in are zero, so this is a logical shift. Consequently, the result is 0-bits when k >= wordSize.

[>>(w, k)] returns the word resulting from shifting w right by k bits. The bits shifted in are zero, so this is a logical shift. Consequently, the result is 0-bits when k >= wordSize.

[~>>(w, k)] returns the word resulting from shifting w right by k bits. The bits shifted in are replications of the left-most bit: the 'sign bit', so this is an arithmetical shift. Consequently, for k >= wordSize and wordToInt w >= 0 the result is all 0-bits, and for k >= wordSize and wordToInt w < 0 the result is all 1-bits.

To make <<, >>, and ~>> infix, use the declaration
 infix 5 << >> ~>>

[+]
 [-]
 [*]
 [div]
 [mod] represent unsigned integer addition, subtraction, multiplication, division, and remainder, modulus 2 raised to the n'th power, where n=wordSize. The operations (i div j) and (i mod j) raise Div when j=0. Otherwise no exceptions are raised.

[<]
 [<=]
 [>]
 [>=] compare words as unsigned integers.

[compare(w1, w2)] returns LESS, EQUAL, or GREATER, according as w1 is less than, equal to, or greater than w2 (as unsigned integers).

[min(w1, w2)] returns the smaller of w1 and w2 (as unsigned integers).

[max(w1, w2)] returns the larger of w1 and w2 (as unsigned integers).

[fmt radix w] returns a string representing w, in the radix (base) specified by radix.

radix	description	output format
BIN	unsigned binary	(base 2) [01]+
OCT	unsigned octal	(base 8) [0-7]+
DEC	unsigned decimal	(base 10) [0-9]+
HEX	unsigned hexadecimal	(base 16) [0-9A-F]+

[toString w] returns a string representing w in unsigned hexadecimal format. Equivalent to (fmt HEX w).

[fromString s] returns SOME(w) if a hexadecimal unsigned numeral can be scanned from a prefix of string s, ignoring any initial whitespace; returns NONE otherwise. Raises Overflow if the scanned number cannot be represented as a word. An unsigned hexadecimal numeral must have form, after possible initial whitespace:

[0-9a-fA-F]+

[scan radix getc chars_{src}] attempts to scan an unsigned numeral from the character source chars_{src}, using the accessor getc, and ignoring any initial whitespace. The radix argument specifies the base of the numeral (BIN, OCT, DEC, HEX). If successful, it returns SOME(w, rest) where w is the value of the numeral scanned, and rest is the unused part of the character source. Raises Overflow if the scanned number cannot be represented as a word. A numeral must have form, after possible initial whitespace:

radix	input format
BIN	(0w) ? [0-1]+
OCT	(0w) ? [0-7]+
DEC	(0w) ? [0-9]+
HEX	(0wx 0wX 0x 0X) ? [0-9a-fA-F]+

[toInt w] returns the (non-negative) default size int represented by bit-pattern w. Raises Overflow in case w is not representable as an integer.

[toIntX w] returns the (signed) default size int represented by two's complement bit-pattern w.

[fromInt i] returns the word (bit-pattern) representing integer i.

[toLargeInt w] returns the (non-negative) largest size int represented by bit-pattern w. Raises Overflow in case w is not representable as an integer.

[toLargeIntX w] returns the (signed) largest size int represented by two's complement bit-pattern w.

[fromLargeInt i] returns the word representing integer i.

[toLarge w] returns w.

[toLargeX w] returns w.

[fromLarge w] returns w.

[toLargeWord w] returns w (deprecated).

[toLargeWordX w] returns w (deprecated).

[fromLargeWord w] returns w (deprecated).

Module Word8

```
Word8 -- SML Basis Library

type word = word8

val wordSize    : int

val orb         : word * word -> word
val andb        : word * word -> word
val xorb        : word * word -> word
val notb        : word -> word
val ~           : word -> word

val <<          : word * Word.word -> word
val >>          : word * Word.word -> word
val ~>>         : word * Word.word -> word

val +           : word * word -> word
val -           : word * word -> word
val *           : word * word -> word
val div         : word * word -> word
val mod         : word * word -> word

val >           : word * word -> bool
val <           : word * word -> bool
val >=          : word * word -> bool
val <=          : word * word -> bool
val compare     : word * word -> order

val min         : word * word -> word
val max         : word * word -> word

val toString    : word -> string
val fromString  : string -> word option
val scan         : StringCvt.radix
                  -> (char, 'a) StringCvt.reader -> (word, 'a) StringCvt.reader
val fmt          : StringCvt.radix -> word -> string

valToInt        : word -> int
valToIntX       : word -> int           with sign extension
val fromInt     : int -> word

val toLargeInt   : word -> int
val toLargeIntX  : word -> int           with sign extension
val fromLargeInt : int -> word

val toLarge      : word -> Word.word
val toLargeX     : word -> Word.word     with sign extension
val fromLarge    : Word.word -> word

val toLargeWord  : word -> Word.word
val toLargeWordX : word -> Word.word     with sign extension
val fromLargeWord: Word.word -> word
```

[word] is the type of 8-bit words, or 8-bit unsigned integers in the range 0..255.

[wordSize] equals 8.

[orb(w1, w2)] returns the bitwise 'or' of w1 and w2.
 [andb(w1, w2)] returns the bitwise 'and' of w1 and w2.
 [xorb(w1, w2)] returns the bitwise 'exclusive or' or w1 and w2.
 [notb w] returns the bitwise negation (one's complement) of w.
 [~ w] returns the arithmetic negation (two's complement) of w.
 [<<(w, k)] returns the word resulting from shifting w left by k bits. The bits shifted in are zero, so this is a logical shift. Consequently, the result is 0-bits when k >= wordSize.
 [>>(w, k)] returns the word resulting from shifting w right by k bits. The bits shifted in are zero, so this is a logical shift. Consequently, the result is 0-bits when k >= wordSize.
 [~>>(w, k)] returns the word resulting from shifting w right by k bits. The bits shifted in are replications of the left-most bit: the 'sign bit', so this is an arithmetical shift. Consequently, for k >= wordSize and wordToInt w >= 0 the result is all 0-bits, and for k >= wordSize and wordToInt w < 0 the result is all 1-bits.

To make <<, >>, and ~>> infix, use the declaration:
 infix 5 << >> ~>>

[+]
 [-]
 [*]
 [div]
 [mod] represent unsigned integer addition, subtraction, multiplication, division, and remainder, modulus 256. The operations (i div j) and (i mod j) raise Div when j = 0. Otherwise no exceptions are raised.

[<]
 [<=]
 [>]
 [>=] compare words as unsigned integers.

[compare(w1, w2)] returns LESS, EQUAL, or GREATER, according as w1 is less than, equal to, or greater than w2 (as unsigned integers).

[min(w1, w2)] returns the smaller of w1 and w2 (as unsigned integers).

[max(w1, w2)] returns the larger of w1 and w2 (as unsigned integers).

[fmt radix w] returns a string representing w, in the radix (base) specified by radix.

radix	description	output format
BIN	unsigned binary	(base 2) [01]+
OCT	unsigned octal	(base 8) [0-7]+
DEC	unsigned decimal	(base 10) [0-9]+
HEX	unsigned hexadecimal	(base 16) [0-9A-F]+

[toString w] returns a string representing w in unsigned hexadecimal format. Equivalent to (fmt HEX w).

[fromString s] returns SOME(w) if a hexadecimal unsigned numeral can be scanned from a prefix of string s, ignoring any initial whitespace; returns NONE otherwise. Raises Overflow if the scanned number cannot be represented as a word. An unsigned hexadecimal numeral must have form, after possible initial whitespace:

[0-9a-fA-F]+

[scan radix {getc} chars src] attempts to scan an unsigned numeral from the character source chars src, using the accessor getc, and ignoring any initial whitespace. The radix argument specifies the base of the numeral (BIN, OCT, DEC, HEX). If successful, it returns SOME(w, rest) where w is the value of the numeral scanned, and rest is the unused part of the character source. Raises Overflow if the scanned number cannot be represented as a word. A numeral must have form, after possible initial whitespace:

radix	input format
BIN	(0w)?[0-1]+
OCT	(0w)?[0-7]+
DEC	(0w)?[0-9]+
HEX	(0wx 0wX 0x 0X)?[0-9a-fA-F]+

[toInt w] returns the integer in the range 0..255 represented by w.

[toIntX w] returns the signed integer (in the range ~128..127) represented by bit-pattern w.

[fromInt i] returns the word holding the 8 least significant bits of i.

[toLargeInt w] returns the integer in the range 0..255 represented by w.

[toLargeIntX w] returns the signed integer (in the range ~128..127) represented by bit-pattern w.

[fromLargeInt i] returns the word holding the 8 least significant bits of i.

[toLarge w] returns the Word.word value corresponding to w.

[toLargeX w] returns the Word.word value corresponding to w, with sign extension. That is, the 8 least significant bits of the result are those of w, and the remaining bits are all equal to the most significant bit of w: its 'sign bit'.

[fromLarge w] returns w modulo 256.

[toLargeWord w]

[toLargeWordX w]

[fromLargeWord w] synonyms for toLarge, toLargeX and fromLarge, (deprecated)

Module Word8Array

Word8Array -- SML Basis Library

```

eqtype array
type elem = Word8.word
type vector = Word8Vector.vector

val maxLen : int

val array : int * elem -> array
val tabulate : int * (int -> elem) -> array
val fromList : elem list -> array

val length : array -> int
val sub : array * int -> elem
val update : array * int * elem -> unit
val vector : array -> vector

val copy : {src: array, dst: array, di: int} -> unit
val copyVec : {src: vector, dst: array, di: int} -> unit

val find : (elem -> bool) -> array -> elem option
val exists : (elem -> bool) -> array -> bool
val all : (elem -> bool) -> array -> bool

val app : (elem -> unit) -> array -> unit
val foldl : (elem * 'b -> 'b) -> 'b -> array -> 'b
val foldr : (elem * 'b -> 'b) -> 'b -> array -> 'b
val modify : (elem -> elem) -> array -> unit

val findi : (int * elem -> bool) -> array -> (int * elem) option
val appi : (int * elem -> unit) -> array -> unit
val foldli : (int * elem * 'b -> 'b) -> 'b -> array -> 'b
val foldri : (int * elem * 'b -> 'b) -> 'b -> array -> 'b
val modifyi : (int * elem -> elem) -> array -> unit

val collate : (elem * elem -> order) -> array * array -> order

```

[array] is the type of one-dimensional, mutable, zero-based constant-time-access arrays with elements of type Word8.word, that is, 8-bit words. Arrays a1 and a2 are equal if both were created by the same call to a primitive (array0, array, tabulate, fromList).

All operations are as for Array.array.

Module Word8ArraySlice

Word8ArraySlice -- SML Basis Library

```
type elem = Word8.word
type array = Word8Array.array
type vector = Word8Vector.vector
type vector_slice = Word8VectorSlice.slice

type slice

val length    : slice -> int
val sub       : slice * int -> elem
val update   : slice * int * elem -> unit
val slice    : array * int option -> slice
val full     : array -> slice
val subslice : slice * int option -> slice
val base     : slice -> array * int * int
val vector   : slice -> vector
val copy      : {src: slice, dst: array, di: int} -> unit
val copyVec  : {src: vector_slice, dst: array, di: int} -> unit
val isEmpty  : slice -> bool
val getItem  : slice -> (elem * slice) option

val find      : (elem -> bool) -> slice -> elem option
val exists   : (elem -> bool) -> slice -> bool
val all       : (elem -> bool) -> slice -> bool

val app       : (elem -> unit) -> slice -> unit
val foldl   : (elem * 'b -> 'b) -> 'b -> slice -> 'b
val foldr   : (elem * 'b -> 'b) -> 'b -> slice -> 'b
val modify  : (elem -> elem) -> slice -> unit

val findi    : (int * elem -> bool) -> slice -> (int * elem) option
val appi    : (int * elem -> unit) -> slice -> unit
val foldli  : (int * elem * 'b -> 'b) -> 'b -> slice -> 'b
val foldri  : (int * elem * 'b -> 'b) -> 'b -> slice -> 'b
val modifyi : (int * elem -> elem) -> slice -> unit

val collate : (elem * elem -> order) -> slice * slice -> order
```

[slice] is the type of Word8Array slices, that is, sub-arrays of Word8Array.array values.

The slice (a,i,n) is valid if $0 \leq i \leq i+n \leq \text{size } s$,
or equivalently, $0 \leq i$ and $0 \leq n$ and $i+n \leq \text{size } s$.

A valid slice sli = (a,i,n) represents the sub-array $a[i\dots i+n-1]$, so the elements of sli are $a[i], a[i+1], \dots, a[i+n-1]$, and n is the length of the slice. Only valid slices can be constructed by the functions below.

All operations are as for ArraySlice.slice.

Module Word8Vector

Word8Vector -- SML Basis Library

```
eqtype vector
type elem = Word8.word

val maxLen    : int

val fromList : elem list -> vector
val tabulate : int * (int -> elem) -> vector

val length   : vector -> int
val sub      : vector * int -> elem
val update   : vector * int * elem -> vector
val concat   : vector list -> vector

val find     : (elem -> bool) -> vector -> elem option
val exists   : (elem -> bool) -> vector -> bool
val all      : (elem -> bool) -> vector -> bool

val app      : (elem -> unit) -> vector -> unit
val map      : (elem -> elem) -> vector -> vector
val foldl   : (elem * 'b -> 'b) -> 'b -> vector -> 'b
val foldr   : (elem * 'b -> 'b) -> 'b -> vector -> 'b

val findi   : (int * elem -> bool) -> vector -> (int * elem) option
val appi    : (int * elem -> unit) -> vector -> unit
val mapi    : (int * elem -> elem) -> vector -> vector
val foldli  : (int * elem * 'b -> 'b) -> 'b -> vector -> 'b
val foldri  : (int * elem * 'b -> 'b) -> 'b -> vector -> 'b

val collate : (elem * elem -> order) -> vector * vector -> order
```

[vector] is the type of one-dimensional, immutable, zero-based constant-time-access vectors with elements of type Word8.word, that is, 8-bit words. Type vector admits equality, and vectors v1 and v2 are equal if they have the same length and their elements are equal.

All operations are as for Vector.vector.

Module Word8VectorSlice

Word8VectorSlice -- SML Basis Library

```
type elem = Word8.word
type vector = Word8Vector.vector

type slice

val length    : slice -> int
val sub       : slice * int -> elem
val slice     : vector * int * int option -> slice
val full      : vector -> slice
val subslice  : slice * int * int option -> slice
val base      : slice -> vector * int * int
val vector    : slice -> vector
val concat    : slice list -> vector
val isEmpty   : slice -> bool
val getItem   : slice -> (elem * slice) option

val find      : (elem -> bool) -> slice -> elem option
val exists   : (elem -> bool) -> slice -> bool
val all       : (elem -> bool) -> slice -> bool

val app       : (elem -> unit) -> slice -> unit
val map       : (elem -> elem) -> slice -> vector
val foldl    : (elem * 'b -> 'b) -> 'b -> slice -> 'b
val foldr    : (elem * 'b -> 'b) -> 'b -> slice -> 'b

val findi    : (int * elem -> bool) -> slice -> (int * elem) option
val appi     : (int * elem -> unit) -> slice -> unit
val mapi     : (int * elem -> elem) -> slice -> vector
val foldli   : (int * elem * 'b -> 'b) -> 'b -> slice -> 'b
val foldri   : (int * elem * 'b -> 'b) -> 'b -> slice -> 'b

val collate  : (elem * elem -> order) -> slice * slice -> order
```

[slice] is the type of Word8Vector slices, that is, sub-vectors of Word8Vector.vector values.

The slice (a,i,n) is valid if $0 \leq i \leq i+n \leq \text{size } s$,
or equivalently, $0 \leq i$ and $0 \leq n$ and $i+n \leq \text{size } s$.
A valid slice sli = (a,i,n) represents the sub-vector $a[i\dots i+n-1]$,
so the elements of sli are $a[i], a[i+1], \dots, a[i+n-1]$, and n is
the length of the slice. Only valid slices can be constructed by
these functions.

All operations are as for VectorSlice.slice.

Index

!	value (General), 52, 55	: =	value (General), 52, 55
!=	value (Real), 132, 133	<	value (Char), 27, 29 value (General), 53, 56 value (Int), 61, 62 value (IntInf), 64 value (Real), 132 value (String), 154, 156 value (Time), 168, 169 value (Word), 181, 182 value (Word8), 184, 185
\$	constructor (Msp), 94		
\$\$	constructor (Msp), 94		
%	value (Msp), 92, 95	<<	value (Word), 181, 182 value (Word8), 184, 185
%#	value (Msp), 92, 95	<=	value (Char), 27, 29 value (General), 53, 56 value (Int), 61, 62 value (IntInf), 64 value (Real), 132 value (String), 154, 156 value (Time), 168, 169 value (Word), 181, 182 value (Word8), 184, 185
%%	value (Msp), 92, 95		
%?#	value (Msp), 92, 95	>	value (Char), 27, 29 value (General), 53, 56 value (Int), 61, 62 value (IntInf), 64 value (Real), 132 value (String), 154, 156 value (Time), 168, 169 value (Word), 181, 182 value (Word8), 184, 185
&&	constructor (Msp), 94		
*	value (General), 53, 56 value (Int), 61 value (IntInf), 64 value (Real), 132 value (Word), 181, 182 value (Word8), 184, 185	<>	value (General), 53, 55
+	value (General), 53, 56 value (Int), 61 value (IntInf), 64 value (Real), 132 value (Time), 168, 169 value (Word), 181, 182 value (Word8), 184, 185	=	value (General), 53, 55
-	value (General), 53, 56 value (Int), 61 value (IntInf), 64 value (Real), 132 value (Time), 168, 169 value (Word), 181, 182 value (Word8), 184, 185	==	value (Real), 132, 133
/	value (General), 53, 56 value (Real), 132	>=	value (Char), 27, 29 value (General), 53, 56 value (Int), 61, 62 value (IntInf), 64

value (Real), 132
value (String), 154, 156
value (Time), 168, 169
value (Word), 181, 182
value (Word8), 184, 185
>>
value (Word), 181, 182
value (Word8), 184, 185
?=
value (Real), 132, 133
@
value (List), 71
^
value (General), 53, 55
value (String), 154
~
value (General), 53, 56
value (Int), 61
value (IntInf), 64
value (Real), 132
value (Word), 181, 182
value (Word8), 184, 185
~>>
value (Word), 181, 182
value (Word8), 184, 185
A_EXEC
constructor (FileSys), 43
A_READ
constructor (FileSys), 43
A_WRITE
constructor (FileSys), 43
abrt
value (Signal), 143
Abs
exception (SML90), 142
abs
value (General), 53, 56
value (Int), 61
value (IntInf), 64
value (Real), 132
accept
value (Socket), 145, 147
access
value (FileSys), 42, 43
access_mode
type (FileSys), 42, 43
acos
value (Math), 79
active
type (Socket), 145, 146
add
value (Binaryset), 19
value (Gdbm), 45, 46
value (Hashset), 57
value (Intset), 67
value (Polygdbm), 118
value (Rbset), 129, 130
value (Splayset), 152
add'
value (Rbset), 129
add_break
value (PP), 109, 110
add_newline
value (PP), 109, 110
add_string
value (PP), 109, 110
addChar
value (Buffer), 22
addList
value (Binaryset), 19
value (Hashset), 57
value (Intset), 67
value (Rbset), 129, 130
value (Splayset), 152
address
value (Msp), 93, 96
addString
value (Buffer), 22
addSubString
value (Buffer), 22
ahref
value (Msp), 93, 96
ahrefa
value (Msp), 93, 96
all
value (Array), 3, 4
value (ArraySlice), 10, 11
value (CharArray), 30
value (CharArraySlice), 31
value (CharVector), 32
value (CharVectorSlice), 33
value (Hashset), 57
value (List), 71, 72
value (ListPair), 74
value (Substring), 159, 160
value (Vector), 173, 174
value (VectorSlice), 175, 176

value (Word8Array), 187
value (Word8ArraySlice), 188
value (Word8Vector), 189
value (Word8VectorSlice), 190
allCookies
 value (Mosmlcookie), 91
allEq
 value (ListPair), 74, 75
AlreadyThere
 exception (Gdbm), 45
 exception (Polygdbm), 118
alarm
 value (Signal), 143
aname
 value (Msp), 93, 96
andb
 value (Word), 181, 182
 value (Word8), 184, 185
app
 value (Array), 3, 4
 value (Array2), 6, 7
 value (ArraySlice), 10, 11
 value (Binarymap), 17
 value (Binaryset), 19, 20
 value (CharArray), 30
 value (CharArraySlice), 31
 value (CharVector), 32
 value (CharVectorSlice), 33
 value (Gdbm), 45, 46
 value (Hashset), 57, 58
 value (Intmap), 65
 value (Intset), 67, 68
 value (List), 71, 72
 value (ListPair), 74
 value (NJ93), 104
 value (Option), 108
 value (Polygdbm), 118, 119
 value (Rbset), 129, 130
 value (Redblackmap), 135
 value (Regex), 137, 140
 value (Splaymap), 150
 value (Splayset), 152, 153
 value (Substring), 159, 162
 value (Vector), 173, 174
 value (VectorSlice), 175, 176
 value (Weak), 178, 179
 value (Word8Array), 187
 value (Word8ArraySlice), 188
 value (Word8Vector), 189
 value (Word8VectorSlice), 190
app1
 value (Callback), 24, 26
 value (Dynlib), 39, 40
app2
 value (Callback), 24, 26
 value (Dynlib), 39, 40
app3
 value (Callback), 24, 26
 value (Dynlib), 39, 40
app4
 value (Callback), 24, 26
 value (Dynlib), 39, 41
app5
 value (Callback), 24, 26
 value (Dynlib), 39, 41
appEq
 value (ListPair), 74, 75
appi
 value (Array), 3, 4
 value (Array2), 6, 8
 value (ArraySlice), 10, 12
 value (CharArray), 30
 value (CharArraySlice), 31
 value (CharVector), 32
 value (CharVectorSlice), 33
 value (Vector), 173, 174
 value (VectorSlice), 175, 177
 value (Weak), 178, 180
 value (Word8Array), 187
 value (Word8ArraySlice), 188
 value (Word8Vector), 189
 value (Word8VectorSlice), 190
AppleScript (structure), 2
AppleScriptErr
 exception (AppleScript), 2
apply
 value (Polyhash), 120, 121
applyto
 value (Mysql), 100, 102
 value (Postgres), 123, 126
arctan
 value (NJ93), 104
 value (SML90), 142
area
 value (Msp), 93, 97
arguments
 value (CommandLine), 34
argv

value (Mosml), 85
Array (structure), 3–5
array
 type (Array), 3
 type (Array2), 6
 type (CharArray), 30
 type (CharArraySlice), 31
 type (Dynarray), 38
 type (Weak), 178, 179
 type (Word8Array), 187
 type (Word8ArraySlice), 188
 value (Array), 3
 value (Array2), 6, 7
 value (CharArray), 30
 value (Dynarray), 38
 value (Weak), 178, 179
 value (Word8Array), 187
Array2 (structure), 6–9
ArraySlice (structure), 10–12
Arraysort (structure), 13
as_compile
 value (AppleScript), 2
as_dispose
 value (AppleScript), 2
as_run_script
 value (AppleScript), 2
as_run_text
 value (AppleScript), 2
asin
 value (Math), 79
atan
 value (Math), 79
atan2
 value (Math), 79
atExit
 value (Process), 127

backtrack
 value (Lexing), 69
base
 value (ArraySlice), 10, 11
 value (CharArraySlice), 31
 value (CharVectorSlice), 33
 value (Path), 114, 117
 value (Substring), 159, 160
 value (VectorSlice), 175, 176
 value (Word8ArraySlice), 188
 value (Word8VectorSlice), 190
before

value (General), 52, 55
begin_block
 value (PP), 109, 110
Binarymap (structure), 17–18
Binaryset (structure), 19–20
Bind
 exception (General), 52, 54
bind
 value (Socket), 145, 147
binInstreamOf
 value (Unix), 171, 172
BinIO (structure), 14–16
binOutstreamOf
 value (Unix), 171, 172
blockquote
 value (Msp), 93, 96
blockquotea
 value (Msp), 93, 96
body
 value (Msp), 92, 95
bodya
 value (Msp), 92, 95
Bool (structure), 21
bool
 type (Bool), 21
 type (General), 52, 53
bound
 value (Dynarray), 38
br
 value (Msp), 93, 96
bra
 value (Msp), 93, 96
break_style
 type (PP), 109
browser
 value (Help), 59
bucketSizes
 value (Polyhash), 120, 121
buf
 type (Buffer), 22
 type (Socket), 145, 147
buff_input
 value (Nonstdio), 106
buff_output
 value (Nonstdio), 106
Buffer (structure), 22
bus
 value (Signal), 143
Byte (structure), 23

bytesToString
 value (Byte), 23
byteToChar
 value (Byte), 23

Callback (structure), 24–26

can_input
 value (NJ93), 105

caption
 value (Msp), 93, 97

captiona
 value (Msp), 93, 97

ceil
 value (General), 53, 55
 value (Real), 132, 133

ceiling
 value (NJ93), 104

center
 value (Msp), 93, 96

cflag
 type (Regex), 137, 138

cgi_annotation_server
 value (Mosmlcgi), 87, 89

cgi_api_version
 value (Mosmlcgi), 87, 90

cgi_auth_type
 value (Mosmlcgi), 87

cgi_content_length
 value (Mosmlcgi), 87, 89

cgi_content_type
 value (Mosmlcgi), 87

cgi_document_root
 value (Mosmlcgi), 87, 90

cgi_field_integer
 value (Mosmlcgi), 87, 88

cgi_field_string
 value (Mosmlcgi), 87, 88

cgi_field_strings
 value (Mosmlcgi), 87, 88

cgi_fieldnames
 value (Mosmlcgi), 87, 88

cgi_gateway_interface
 value (Mosmlcgi), 87, 89

cgi_http_accept
 value (Mosmlcgi), 87, 89

cgi_http_cookie
 value (Mosmlcgi), 87, 90

cgi_http_forwarded
 value (Mosmlcgi), 87, 90

cgi_http_host
 value (Mosmlcgi), 87, 90

cgi_http_proxy_connection
 value (Mosmlcgi), 87, 90

cgi_http_referer
 value (Mosmlcgi), 87, 89

cgi_http_user_agent
 value (Mosmlcgi), 87, 89

cgi_is_subreq
 value (Mosmlcgi), 88, 90

cgi_part
 value (Mosmlcgi), 87, 88

cgi_partnames
 value (Mosmlcgi), 87, 88

cgi_parts
 value (Mosmlcgi), 87, 88

cgi_path_info
 value (Mosmlcgi), 87, 89

cgi_path_translated
 value (Mosmlcgi), 87, 89

cgi_query_string
 value (Mosmlcgi), 87, 89

cgi_remote_addr
 value (Mosmlcgi), 87, 89

cgi_remote_host
 value (Mosmlcgi), 87, 89

cgi_remote_ident
 value (Mosmlcgi), 87, 89

cgi_remote_user
 value (Mosmlcgi), 87, 89

cgi_request_filename
 value (Mosmlcgi), 87, 90

cgi_request_method
 value (Mosmlcgi), 87, 89

cgi_request_uri
 value (Mosmlcgi), 87, 90

cgi_script_filename
 value (Mosmlcgi), 87, 90

cgi_script_name
 value (Mosmlcgi), 87, 89

cgi_server_admin
 value (Mosmlcgi), 87, 90

cgi_server_name
 value (Mosmlcgi), 87, 89

cgi_server_port
 value (Mosmlcgi), 87, 89

cgi_server_protocol
 value (Mosmlcgi), 87, 89

cgi_server_software

value (Mosmlcgi), 87, 89
cgi_the_request
 value (Mosmlcgi), 87, 90
Char (structure), 27–29
char
 type (Char), 27
 type (General), 52, 53
 value (Gdimage), 49, 51
CharArray (structure), 30
CharArraySlice (structure), 31
charsize
 value (Gdimage), 49, 51
charToByte
 value (Byte), 23
charUp
 value (Gdimage), 49, 51
CharVector (structure), 32
CharVectorSlice (structure), 33
chDir
 value (FileSys), 42
checkCPUTimer
 value (Timer), 170
checkCPUTimes
 value (Timer), 170
checkGCTime
 value (Timer), 170
checkRealTimer
 value (Timer), 170
chld
 value (Signal), 143, 144
Chr
 exception (General), 52
chr
 value (Char), 27
 value (NJ93), 104
 value (SML90), 142
clear
 value (Buffer), 22
clear_ppstream
 value (PP), 109, 110
clearParser
 value (Parsing), 112, 113
close
 value (Socket), 145, 147
close_in
 value (NJ93), 105
 value (SML90), 142
close_out
 value (NJ93), 105
 value (SML90), 142
closebase
 value (Mysql), 99, 101
 value (Postgres), 122, 124
Closed
 exception (Dynlib), 39
 exception (Gdbm), 45
 exception (Mysql), 99
 exception (Polygdbm), 118
 exception (Postgres), 122
closeDir
 value (FileSys), 42
closeIn
 value (BinIO), 14
 value (TextIO), 164, 165
closeOut
 value (BinIO), 14, 15
 value (TextIO), 164, 166
cmdtuples
 value (Mysql), 99, 101
 value (Postgres), 122, 124
collate
 value (Array), 3, 4
 value (ArraySlice), 10, 12
 value (CharArray), 30
 value (CharArraySlice), 31
 value (CharVector), 32
 value (CharVectorSlice), 33
 value (List), 71, 72
 value (String), 154, 156
 value (Substring), 159, 161
 value (Vector), 173, 174
 value (VectorSlice), 175, 177
 value (Word8Array), 187
 value (Word8ArraySlice), 188
 value (Word8Vector), 189
 value (Word8VectorSlice), 190
ColMajor
 constructor (Array2), 6
color
 constructor (Gdimage), 49, 50
 type (Gdimage), 48, 49
 value (Gdimage), 48, 50
column
 value (Array2), 6, 7
CommandLine (structure), 34
comment
 value (Msp), 92, 95
compare

value (Char), 27, 29
value (Date), 35, 36
value (FileSys), 42, 44
value (Int), 61, 62
value (IntInf), 64
value (Rbset), 129, 131
value (Real), 132, 133
value (Socket), 145, 149
value (String), 154, 156
value (Substring), 159, 161
value (Time), 168, 169
value (Word), 181, 182
value (Word8), 184, 185
compile
 value (Meta), 81, 82
compileStructure
 value (Meta), 81–83
compileToplevel
 value (Meta), 81, 83
compose
 value (Option), 108
composePartial
 value (Option), 108
concat
 value (CharVector), 32
 value (CharVectorSlice), 33
 value (List), 71, 72
 value (Path), 114, 116
 value (String), 154, 155
 value (Substring), 159, 160
 value (Vector), 173
 value (VectorSlice), 175, 176
 value (Word8Vector), 189
 value (Word8VectorSlice), 190
concatWith
 value (String), 154, 155
 value (Substring), 159, 160
connect
 value (Socket), 145, 147
conservative
 value (Meta), 81, 82
CONSISTENT
 constructor (PP), 109
cont
 value (Signal), 143, 144
contains
 value (Char), 27, 28
contents
 value (Buffer), 22
cookiedata
 type (Mosmlcookie), 91
CookieError
 exception (Mosmlcookie), 91
copy
 value (Array), 3, 4
 value (Array2), 6, 8
 value (ArraySlice), 10, 11
 value (CharArray), 30
 value (CharArraySlice), 31
 value (Gdimage), 48, 50
 value (Hashset), 57
 value (Polyhash), 120, 121
 value (Word8Array), 187
 value (Word8ArraySlice), 188
copyResize
 value (Gdimage), 49, 51
copytablefrom
 value (Mysql), 100, 103
 value (Postgres), 123, 126
copytableto
 value (Mysql), 100, 103
 value (Postgres), 123, 126
copyVec
 value (Array), 3, 4
 value (ArraySlice), 10, 11
 value (CharArray), 30
 value (CharArraySlice), 31
 value (Word8Array), 187
 value (Word8ArraySlice), 188
cos
 value (Math), 79
 value (NJ93), 104
 value (SML90), 142
cosh
 value (Math), 79, 80
cptr
 type (Callback), 24, 26
cpu_timer
 type (Timer), 170
createLexer
 value (Lexing), 69
createLexerString
 value (Lexing), 69
cs
 type (StringCvt), 157
 type (TextIO), 164
currentArc
 value (Path), 114, 115

Date
 exception (Date), 35
Date (structure), 35–37
date
 type (Date), 35
 value (Date), 35
datum
 type (Gdbm), 45
day
 value (Date), 35, 36
db
 value (Mysql), 99, 101
 value (Postgres), 122, 124
dbconn
 type (Mysql), 99, 100
 type (Postgres), 122, 124
dbresult
 type (Mysql), 99, 100
 type (Postgres), 122, 124
dbresultstatus
 type (Mysql), 99
 type (Postgres), 122
dd
 value (Msp), 93, 97
dec
 value (NJ93), 104
default
 value (Dynarray), 38
defaultBrowser
 value (Help), 59, 60
delay
 value (Susp), 163
delete
 value (Binaryset), 19, 20
 value (Hashset), 57
 value (Intset), 67
 value (Rbset), 129, 130
 value (Splayset), 152, 153
deleteCookie
 value (Mosmlcookie), 91
depth
 value (Rbset), 129
dest_ppstream
 value (PP), 109, 110
dgram
 type (Socket), 145, 146
dict
 type (Binarymap), 17
 type (Redblackmap), 135
 type (Splaymap), 150
difference
 value (Binaryset), 19, 20
 value (Intset), 67
 value (Rbset), 129, 130
 value (Splayset), 152, 153
dimensions
 value (Array2), 6, 7
dir
 value (Path), 114, 117
dirstream
 type (FileSys), 42
displayLines
 value (Help), 59, 60
Div
 exception (General), 52
 exception (Real), 132
 value (General), 54
div
 value (General), 53, 56
 value (Int), 61
 value (IntInf), 64
 value (Word), 181, 182
 value (Word8), 184, 185
divi
 value (Msp), 93, 96
divia
 value (Msp), 93, 96
divMod
 value (IntInf), 64
dl
 value (Msp), 93, 97
dla
 value (Msp), 93, 97
dlclose
 value (Dynlib), 39, 40
dlHandle
 type (Dynlib), 39
dlopen
 value (Dynlib), 39, 40
dlsym
 value (Dynlib), 39, 40
Domain
 exception (General), 52
doubleVec
 value (Mosml), 85
drawArc
 value (Gdimage), 48, 50
drawLine

value (*Gdimage*), 48, 50
drawPixel
 value (*Gdimage*), 48, 50
drawPolygon
 value (*Gdimage*), 48, 50
drawRect
 value (*Gdimage*), 48, 50
drop
 value (*List*), 71, 72
dropI
 value (*StringCvt*), 157
 value (*Substring*), 159, 161
dropR
 value (*Substring*), 159, 161
dt
 value (*Msp*), 93, 97
dummyAction
 value (*Lexing*), 69
Dynarray (*structure*), 38
Dynlib (*structure*), 39–41
dyntype
 type (*Mysql*), 100
 type (*Postgres*), 123
dynval
 type (*Mysql*), 100
 type (*Postgres*), 123
dynval2s
 value (*Mysql*), 100, 102
 value (*Postgres*), 123, 126

e
 value (*Math*), 79
eflag
 type (*Regex*), 137, 139
elem
 type (*BinIO*), 14
 type (*CharArray*), 30
 type (*CharArraySlice*), 31
 type (*CharVector*), 32
 type (*CharVectorSlice*), 33
 type (*TextIO*), 164, 165
 type (*Word8Array*), 187
 type (*Word8ArraySlice*), 188
 type (*Word8Vector*), 189
 type (*Word8VectorSlice*), 190
em
 value (*Msp*), 93, 96
Empty
 constructor (*Msp*), 94

 exception (*List*), 71
empty
 value (*Binaryset*), 19
 value (*Hashset*), 57
 value (*Intmap*), 65
 value (*Intset*), 67
 value (*Rbset*), 129, 130
 value (*Splayset*), 152
end_block
 value (*PP*), 109, 110
end_of_stream
 value (*NJ93*), 105
 value (*SML90*), 142
endOfStream
 value (*BinIO*), 14, 15
 value (*TextIO*), 164, 165
eq
 value (*IntInf*), 64
eqclasses
 value (*Listsort*), 76
equal
 value (*Binaryset*), 19
 value (*Hashset*), 57, 58
 value (*Intset*), 67
 value (*Rbset*), 129, 130
 value (*Splayset*), 152
errLocation
 value (*Location*), 77
errMsg
 value (*Location*), 77
errormessage
 value (*Mysql*), 99, 101
 value (*Postgres*), 122, 124
errorMsg
 value (*OS*), 107
errPrompt
 value (*Location*), 77
execute
 value (*Mysql*), 99, 101
 value (*Postgres*), 122, 124
 value (*Unix*), 171
executeInEnv
 value (*Unix*), 171
exists
 value (*Array*), 3, 4
 value (*ArraySlice*), 10, 11
 value (*CharArray*), 30
 value (*CharArraySlice*), 31
 value (*CharVector*), 32

value (CharVectorSlice), 33
value (Hashset), 57
value (List), 71, 72
value (ListPair), 74, 75
value (Vector), 173, 174
value (VectorSlice), 175, 176
value (Word8Array), 187
value (Word8ArraySlice), 188
value (Word8Vector), 189
value (Word8VectorSlice), 190
exit
value (Process), 127
exn
type (General), 52, 53
exnMessage
value (General), 53, 55
exnName
value (General), 52, 55
exp
value (Math), 79
value (NJ93), 104
value (SML90), 142
explode
value (NJ93), 104
value (SML90), 142
value (String), 154, 155
value (Substring), 159, 161
ext
value (Path), 114, 117
Extended
constructor (Regex), 138
extract
value (String), 154
value (Substring), 159, 160

Fail
exception (General), 52
failure
value (Process), 127
fast_really_input
value (Nonstdio), 106
fastwrite
value (Gdbm), 45, 46
value (Polygdbm), 118, 119
fields
value (Regex), 137, 140
value (String), 154, 155
value (Substring), 159, 162
file
value (Path), 114, 117
file_exists
value (Nonstdio), 106
file_id
type (FileSys), 42, 44
fileAddr
value (Socket), 145, 146
fileDgram
value (Socket), 145, 147
fileId
value (FileSys), 42, 44
fileSize
value (FileSys), 42, 44
fileStream
value (Socket), 145, 146
FileSys (structure), 42–44
fill
value (Gdimage), 48, 50
fillBorder
value (Gdimage), 48, 50
fillPolygon
value (Gdimage), 48, 50
fillRect
value (Gdimage), 48, 50
filter
value (List), 71, 72
value (Option), 108
value (Polyhash), 120, 121
find
value (Array), 3, 4
value (ArraySlice), 10, 11
value (Binarymap), 17
value (Binaryset), 19, 20
value (CharArray), 30
value (CharArraySlice), 31
value (CharVector), 32
value (CharVectorSlice), 33
value (Gdbm), 45, 46
value (Hashset), 57, 58
value (Intset), 67, 68
value (List), 71, 72
value (Polygdbm), 118
value (Polyhash), 120
value (Rbset), 129, 130
value (Redblackmap), 135
value (Splaymap), 150
value (Splayset), 152, 153
value (Vector), 173, 174
value (VectorSlice), 175, 176

value (Word8Array), 187
 value (Word8ArraySlice), 188
 value (Word8Vector), 189
 value (Word8VectorSlice), 190
 findi
 value (Array), 3, 4
 value (ArraySlice), 10, 12
 value (CharArray), 30
 value (CharArraySlice), 31
 value (CharVector), 32
 value (CharVectorSlice), 33
 value (Vector), 173, 174
 value (VectorSlice), 175, 176
 value (Word8Array), 187
 value (Word8ArraySlice), 188
 value (Word8Vector), 189
 value (Word8VectorSlice), 190
 first
 value (Substring), 159, 160
 flag
 type (Dynlib), 39, 40
 flatten
 value (Msp), 92, 94
 floatVec
 value (Mosml), 85
 floor
 value (General), 53, 55
 value (Real), 132, 133
 flush_out
 value (NJ93), 105
 flush_ppstream
 value (PP), 109, 110
 flushOut
 value (BinIO), 14, 15
 value (TextIO), 164, 166
 fmt
 value (Date), 35, 36
 value (Int), 61, 62
 value (IntInf), 64
 value (Real), 132, 133
 value (Time), 168, 169
 value (Word), 181, 182
 value (Word8), 184, 185
 fname
 value (Mysql), 99, 101
 value (Postgres), 122, 124
 fnames
 value (Mysql), 99, 101
 value (Postgres), 122, 124
 fnumber
 value (Mysql), 99, 101
 value (Postgres), 122, 125
 fold
 value (Array2), 6, 8
 value (Gdbm), 45, 46
 value (Hashset), 57, 58
 value (NJ93), 104
 value (Polygdbm), 118, 119
 value (Regex), 137, 140
 foldi
 value (Array2), 6, 8
 foldl
 value (Array), 3, 4
 value (ArraySlice), 10, 11
 value (Binarymap), 17
 value (Binaryset), 19, 20
 value (CharArray), 30
 value (CharArraySlice), 31
 value (CharVector), 32
 value (CharVectorSlice), 33
 value (Intmap), 65
 value (Intset), 67, 68
 value (List), 71, 72
 value (ListPair), 74, 75
 value (Rbset), 129, 130
 value (Redblackmap), 135
 value (Splaymap), 150
 value (Splayset), 152, 153
 value (Substring), 159, 162
 value (Vector), 173, 174
 value (VectorSlice), 175, 176
 value (Weak), 178, 179
 value (Word8Array), 187
 value (Word8ArraySlice), 188
 value (Word8Vector), 189
 value (Word8VectorSlice), 190
 foldlEq
 value (ListPair), 74, 75
 foldli
 value (Array), 3, 4
 value (ArraySlice), 10, 12
 value (CharArray), 30
 value (CharArraySlice), 31
 value (CharVector), 32
 value (CharVectorSlice), 33
 value (Vector), 173, 174
 value (VectorSlice), 175, 177
 value (Weak), 178, 180

value (Word8Array), 187
value (Word8ArraySlice), 188
value (Word8Vector), 189
value (Word8VectorSlice), 190
foldr
 value (Array), 3, 4
 value (ArraySlice), 10, 11
 value (Binarymap), 17
 value (Binaryset), 19, 20
 value (CharArray), 30
 value (CharArraySlice), 31
 value (CharVector), 32
 value (CharVectorSlice), 33
 value (Intmap), 65
 value (Intset), 67, 68
 value (List), 71, 72
 value (ListPair), 74, 75
 value (Rbset), 129, 130
 value (Redblackmap), 135
 value (Splaymap), 150
 value (Splayset), 152, 153
 value (Substring), 159, 162
 value (Vector), 173, 174
 value (VectorSlice), 175, 176
 value (Weak), 178, 179
 value (Word8Array), 187
 value (Word8ArraySlice), 188
 value (Word8Vector), 189
 value (Word8VectorSlice), 190
foldrEq
 value (ListPair), 74, 75
foldri
 value (Array), 3, 4
 value (ArraySlice), 10, 12
 value (CharArray), 30
 value (CharArraySlice), 31
 value (CharVector), 32
 value (CharVectorSlice), 33
 value (Vector), 173, 174
 value (VectorSlice), 175, 177
 value (Weak), 178, 180
 value (Word8Array), 187
 value (Word8ArraySlice), 188
 value (Word8Vector), 189
 value (Word8VectorSlice), 190
font
 type (Gdimage), 48, 49
fonta
 value (Msp), 93, 96
force
 value (Susp), 163
form
 value (Msp), 94, 97
forma
 value (Msp), 94, 98
formatable
 value (Mysql), 100, 103
 value (Postgres), 123, 126
fpe
 value (Signal), 143
frag
 type (General), 52, 54
frame
 value (Msp), 94, 98
framea
 value (Msp), 94, 98
frameset
 value (Msp), 94, 98
fromCString
 value (Char), 27, 29
 value (String), 154, 156
fromDefault
 value (Real), 132, 133
fromInt
 value (Int), 61
 value (IntInf), 64
 value (Real), 132, 133
 value (Word), 181, 183
 value (Word8), 184, 186
fromLarge
 value (Int), 61
 value (IntInf), 64
 value (Word), 181, 183
 value (Word8), 184, 186
fromLargeInt
 value (Word), 181, 183
 value (Word8), 184, 186
fromLargeWord
 value (Word), 181, 183
 value (Word8), 184, 186
fromList
 value (Array), 3
 value (Array2), 6, 7
 value (CharArray), 30
 value (CharVector), 32
 value (Dynarray), 38
 value (Vector), 173
 value (Word8Array), 187

value (`Word8Vector`), 189
`fromMicroseconds`
 value (`Time`), 168
`fromMilliseconds`
 value (`Time`), 168
`fromPng`
 value (`Gdimage`), 48, 49
`fromReal`
 value (`Time`), 168, 169
`fromSeconds`
 value (`Time`), 168
`fromString`
 value (`Bool`), 21
 value (`Char`), 27, 28
 value (`Date`), 35, 37
 value (`Int`), 61, 62
 value (`IntInf`), 64
 value (`Path`), 114, 116
 value (`Real`), 132, 133
 value (`String`), 154, 155
 value (`Time`), 168, 169
 value (`Word`), 181, 183
 value (`Word8`), 184, 186
`fromtag`
 value (`Mysql`), 100
 value (`Postgres`), 123
`fromTimeLocal`
 value (`Date`), 35, 37
`fromTimeUniv`
 value (`Date`), 35, 37
`fromUnixPath`
 value (`Path`), 114, 117
`fromWord`
 value (`Signal`), 143
`ftype`
 value (`Mysql`), 100
 value (`Postgres`), 123
`ftypes`
 value (`Mysql`), 100
 value (`Postgres`), 123
`full`
 value (`ArraySlice`), 10, 11
 value (`CharArraySlice`), 31
 value (`CharVectorSlice`), 33
 value (`Substring`), 159, 160
 value (`VectorSlice`), 175, 176
 value (`Word8ArraySlice`), 188
 value (`Word8VectorSlice`), 190
`fullPath`

value (`FileSys`), 42, 43
`Gdbm` (**structure**), 45–47
`GdbmError`
 exception (`Gdbm`), 45
 exception (`Polygdbm`), 118
`Gdimage` (**structure**), 48–51
`General` (**structure**), 52–56
`generator`
 type (`Random`), 128
`get`
 value (`Weak`), 178
`getbool`
 value (`Mysql`), 100, 102
 value (`Postgres`), 123, 125
`getc`
 value (`Substring`), 159, 160
`getCookie`
 value (`Mosmlcookie`), 91
`getCookieValue`
 value (`Mosmlcookie`), 91
`getcptr`
 value (`Callback`), 24, 26
`getCurrentLocation`
 value (`Location`), 77
`getdate`
 value (`Mysql`), 99, 102
 value (`Postgres`), 122, 125
`getdatetime`
 value (`Mysql`), 100, 102
 value (`Postgres`), 123, 125
`getDir`
 value (`FileSys`), 42, 43
`getdynfield`
 value (`Mysql`), 100, 102
 value (`Postgres`), 123, 125
`getdyntup`
 value (`Mysql`), 100, 102
 value (`Postgres`), 123, 126
`getdyntups`
 value (`Mysql`), 100, 102
 value (`Postgres`), 123, 126
`getEnv`
 value (`Process`), 127
`getinetaddr`
 value (`Socket`), 145, 147
`getInt`
 value (`Mysql`), 99, 102
 value (`Postgres`), 122, 125

getItem
 value (ArraySlice), 10, 11
 value (CharArraySlice), 31
 value (CharVectorSlice), 33
 value (List), 71, 73
 value (VectorSlice), 175, 176
 value (Word8ArraySlice), 188
 value (Word8VectorSlice), 190
 getLexeme
 value (Lexing), 69, 70
 getLexemeChar
 value (Lexing), 69, 70
 getLexemeEnd
 value (Lexing), 69, 70
 getLexemeStart
 value (Lexing), 69, 70
 getopt
 value (Option), 108
 getOrder
 value (Rbset), 129
 getParent
 value (Path), 114, 116
 getreal
 value (Mysql), 99, 102
 value (Postgres), 122, 125
 getstring
 value (Mysql), 99, 102
 value (Postgres), 122, 125
 gettime
 value (Mysql), 100, 102
 value (Postgres), 123, 125
 getTransparent
 value (Gdimage), 48, 50
 getVolume
 value (Path), 114, 116
 Graphic
 exception (General), 52

 h1
 value (Msp), 92, 96
 h2
 value (Msp), 92
 h3
 value (Msp), 92
 h4
 value (Msp), 92
 h5
 value (Msp), 92
 h6

value (Msp), 92
 hash
 value (FileSys), 42, 44
 value (Hashset), 57, 58
 value (Polyhash), 120, 121
 value (Rbset), 129
 hash_param
 value (Polyhash), 120, 121
 hash_table
 type (Polyhash), 120
 Hashset (structure), 57–58
 hasKey
 value (Gdbm), 45, 46
 value (Polygdbm), 118, 119
 Hd
 exception (NJ93), 104
 hd
 value (List), 71
 value (NJ93), 104
 head
 value (Msp), 92, 95
 Help (structure), 59–60
 help
 value (Help), 59
 helpdirs
 value (Help), 59
 host
 value (Mysql), 99, 101
 value (Postgres), 122, 124
 hour
 value (Date), 35, 36
 hr
 value (Msp), 93, 96
 hra
 value (Msp), 93, 96
 html
 value (Msp), 92, 95
 htmlcolors
 value (Gdimage), 48, 50
 htmldoc
 value (Msp), 92, 95
 htmlencode
 value (Msp), 94, 98
 hup
 value (Signal), 143

 Icase
 constructor (Regex), 138
 ignore

value (*General*), 52, 55
ill
 value (*Signal*), 143
image
 type (*Gdimage*), 48, 49
 value (*Gdimage*), 48, 49
img
 value (*Msp*), 93, 97
imga
 value (*Msp*), 93, 97
implode
 value (*NJ93*), 104
 value (*SML90*), 142
 value (*String*), 154, 155
in_flags
 type (*Socket*), 145, 148
in_stream_length
 value (*Nonstdio*), 106
inc
 value (*NJ93*), 104
incheckbox
 value (*Msp*), 94, 98
INCONSISTENT
 constructor (*PP*), 109
indexfiles
 value (*Help*), 59
inetAddr
 value (*Socket*), 145, 146
inetDgram
 value (*Socket*), 145, 147
inetStream
 value (*Socket*), 145, 147
inhidden
 value (*Msp*), 94, 98
inpassword
 value (*Msp*), 94, 98
input
 value (*BinIO*), 14
 value (*Msp*), 94, 98
 value (*NJ93*), 104
 value (*SML90*), 142
 value (*TextIO*), 164, 165
input1
 value (*BinIO*), 14, 15
 value (*TextIO*), 164, 165
input_binary_int
 value (*Nonstdio*), 106
input_char
 value (*Nonstdio*), 106
 input_line
 value (*NJ93*), 105
 input_value
 value (*Nonstdio*), 106
inputa
 value (*Msp*), 94, 98
inputAll
 value (*BinIO*), 14, 15
 value (*TextIO*), 164, 165
inputc
 value (*NJ93*), 105
inputLine
 value (*TextIO*), 164, 165
inputN
 value (*BinIO*), 14, 15
 value (*TextIO*), 164, 165
inputNoBlock
 value (*BinIO*), 14, 15
 value (*TextIO*), 164, 165
inradio
 value (*Msp*), 94, 98
inreset
 value (*Msp*), 94, 98
insert
 value (*Binarymap*), 17
 value (*Gdbm*), 45, 46
 value (*Intmap*), 65
 value (*Polygdbm*), 118
 value (*Polyhash*), 120
 value (*Redblackmap*), 135
 value (*Splaymap*), 150
installPP
 value (*Meta*), 81, 82
instream
 type (*BinIO*), 14
 type (*NJ93*), 104
 type (*SML90*), 142
 type (*TextIO*), 164
insubmit
 value (*Msp*), 94, 98
Int (*structure*), 61–63
int
 type (*General*), 52, 53
 type (*Int*), 61
 type (*IntInf*), 64
 value (*Signal*), 143
Interrupt
 exception (*General*), 52
intersection

value (Binaryset), 19, 20
value (Intset), 67
value (Rbset), 129, 130
value (Splayset), 152, 153
intext
 value (Msp), 94, 98
IntInf (structure), 64
Intmap (structure), 65–66
intmap
 type (Intmap), 65
Intset (structure), 67–68
intset
 type (Intset), 67
intv
 type (Rbset), 129
Invalid_argument
 exception (General), 52
InvalidArc
 exception (Path), 114
Io
 exception (General), 52
isAbsolute
 value (Path), 114, 115
isAlpha
 value (Char), 27, 28
isAlphaNum
 value (Char), 27, 28
isAscii
 value (Char), 27, 28
isCanonical
 value (Path), 114, 116
isCntrl
 value (Char), 27, 28
isdead
 value (Weak), 178, 179
isDigit
 value (Char), 27, 28
isDir
 value (FileSys), 42, 43
isDst
 value (Date), 35, 36
isEmpty
 value (ArraySlice), 10, 11
 value (Binaryset), 19
 value (CharArraySlice), 31
 value (CharVectorSlice), 33
 value (Hashset), 57, 58
 value (Intset), 67
 value (Rbset), 129, 130
value (Splayset), 152
value (Substring), 159, 160
value (VectorSlice), 175, 176
value (Word8ArraySlice), 188
value (Word8VectorSlice), 190
isGraph
 value (Char), 27, 28
isHexDigit
 value (Char), 27, 28
isLink
 value (FileSys), 42, 43
isLower
 value (Char), 27, 28
isNull
 value (Mysql), 100, 102
 value (Postgres), 123, 125
isPrefix
 value (String), 154, 155
 value (Substring), 159, 162
isPrint
 value (Char), 27, 28
isPunct
 value (Char), 27, 28
isRegistered
 value (Callback), 24, 25
isRelative
 value (Path), 114, 115
isRoot
 value (Path), 114, 115
isSome
 value (Option), 108
isSpace
 value (Char), 27, 28
isSubset
 value (Binaryset), 19
 value (Hashset), 57, 58
 value (Intset), 67
 value (Rbset), 129, 130
 value (Splayset), 152
isSubstring
 value (String), 154, 155
 value (Substring), 159, 162
isSuccess
 value (Process), 127
isSuffix
 value (String), 154, 155
 value (Substring), 159, 162
isUpper
 value (Char), 27, 28

isweak
 value (Weak), 178

itemEnd
 value (Parsing), 112, 113

itemStart
 value (Parsing), 112, 113

join
 value (Option), 108

joinBaseExt
 value (Path), 114, 117

joinDirFile
 value (Path), 114, 116

kill
 value (Signal), 143
 value (Unix), 171, 172

last
 value (List), 71

length
 value (Array), 3
 value (ArraySlice), 10
 value (CharArray), 30
 value (CharArraySlice), 31
 value (CharVector), 32
 value (CharVectorSlice), 33
 value (List), 71, 72
 value (Vector), 173
 value (VectorSlice), 175
 value (Weak), 178, 179
 value (Word8Array), 187
 value (Word8ArraySlice), 188
 value (Word8Vector), 189
 value (Word8VectorSlice), 190

lexbuf
 type (Lexing), 69

Lexing (structure), 69–70

li
 value (Msp), 93, 97

liberal
 value (Meta), 81, 82

List (structure), 71–73

list
 type (General), 52, 54
 type (List), 71

listDir
 value (Mosml), 85

listen
 value (Socket), 145, 147

listItems
 value (Binarymap), 17
 value (Binaryset), 19, 20
 value (Gdbm), 45, 46
 value (Hashset), 57, 58
 value (Intmap), 65
 value (Intset), 67, 68
 value (Polygdbm), 118, 119
 value (Polyhash), 120
 value (Rbset), 129, 130
 value (Redblackmap), 135
 value (Splaymap), 150
 value (Splayset), 152, 153

listKeys
 value (Gdbm), 45, 46
 value (Polygdbm), 118, 119

ListPair (structure), 74–75

Listsort (structure), 76

ln
 value (Math), 79, 80
 value (NJ93), 104
 value (SML90), 142

load
 value (Meta), 81, 83

loaded
 value (Meta), 81, 83

loadOne
 value (Meta), 81, 83

loadPath
 value (Meta), 81, 83

localOffset
 value (Date), 35, 37

Location
 type (Location), 77

Location (structure), 77–78

log10
 value (Math), 79, 80

log2
 value (IntInf), 64

lookahead
 value (BinIO), 14, 15
 value (NJ93), 105
 value (SML90), 142
 value (TextIO), 164, 165

makestring
 value (General), 53, 56

map
 value (Binarymap), 17, 18

value (CharVector), 32
value (CharVectorSlice), 33
value (Gdbm), 45, 46
value (Intmap), 65
value (List), 71, 72
value (ListPair), 74
value (Msp), 93, 97
value (Option), 108
value (Polygdbm), 118, 119
value (Polyhash), 120, 121
value (Rbset), 129, 130
value (Redblackmap), 135, 136
value (Regex), 137, 140
value (Splaymap), 150, 151
value (String), 154, 155
value (Vector), 173, 174
value (VectorSlice), 175, 176
value (Word8Vector), 189
value (Word8VectorSlice), 190
mapa
 value (Msp), 93, 97
mapEq
 value (ListPair), 74, 75
mapi
 value (CharVector), 32
 value (CharVectorSlice), 33
 value (Vector), 173, 174
 value (VectorSlice), 175, 177
 value (Word8Vector), 189
 value (Word8VectorSlice), 190
mapMono
 value (Rbset), 129, 130
mapPartial
 value (List), 71, 72
 value (Option), 108
mark0
 value (Msp), 92, 95
mark0a
 value (Msp), 92, 95
mark1
 value (Msp), 92, 95
mark1a
 value (Msp), 92, 95
Match
 exception (General), 52
Math (structure), 79–80
max
 value (Int), 61, 62
 value (IntInf), 64
minChar
 value (Char), 27
minInt
 value (Int), 61
 value (IntInf), 64
minute

value (*Date*), 35, 36
mk_ppstream
 value (*PP*), 109
mkAbsolute
 value (*Path*), 114, 116
mkCanonical
 value (*Path*), 114, 116
mkDict
 value (*Binarymap*), 17
 value (*Redblackmap*), 135
 value (*Splaymap*), 150
mkDir
 value (*FileSys*), 42, 43
mkLoc
 value (*Location*), 77
mkPolyTable
 value (*Polyhash*), 120, 121
mkRelative
 value (*Path*), 114, 116
mkTable
 value (*Polyhash*), 120
mod
 value (*General*), 53, 56
 value (*Int*), 61, 62
 value (*IntInf*), 64
 value (*Word*), 181, 182
 value (*Word8*), 184, 185
mode
 type (*Gdimage*), 48, 49
modify
 value (*Array*), 3, 4
 value (*Array2*), 6, 7
 value (*ArraySlice*), 10, 12
 value (*CharArray*), 30
 value (*CharArraySlice*), 31
 value (*Weak*), 178, 179
 value (*Word8Array*), 187
 value (*Word8ArraySlice*), 188
modifyi
 value (*Array*), 3, 4
 value (*Array2*), 6, 8
 value (*ArraySlice*), 10, 12
 value (*CharArray*), 30
 value (*CharArraySlice*), 31
 value (*Weak*), 178, 180
 value (*Word8Array*), 187
 value (*Word8ArraySlice*), 188
modTime
 value (*FileSys*), 42, 43

 month
 type (*Date*), 35
 value (*Date*), 35, 36
Mosml (*structure*), 85–86
Mosmlcgi (*structure*), 87–90
Mosmlcookie (*structure*), 91
Msp (*structure*), 92–98
Mysql (*structure*), 99–103

 name
 value (*CommandLine*), 34
nCols
 value (*Array2*), 6, 7
ne
 value (*IntInf*), 64
new
 value (*Buffer*), 22
newgen
 value (*Random*), 128
newgenseed
 value (*Random*), 128
Newline
 constructor (*Regex*), 138
nfields
 value (*Mysql*), 99, 101
 value (*Postgres*), 122, 124
nilLocation
 value (*Location*), 77
NJ93 (*structure*), 104–105
Nl
 constructor (*Msp*), 94
NO_RECVS
 constructor (*Socket*), 147
NO_RECVS_OR_SENDS
 constructor (*Socket*), 147
NO_SENDS
 constructor (*Socket*), 147
NonMonotonic
 exception (*Rbset*), 129
Nonstdio (*structure*), 106
not
 value (*Bool*), 21
 value (*General*), 53, 55
notb
 value (*Word*), 181, 182
 value (*Word8*), 184, 185
Notbol
 constructor (*Regex*), 139
notContains

value (Char), 27, 28
Noteol
constructor (Regex), 139
NotFound
exception (Binarymap), 17
exception (Binaryset), 19
exception (Gdbm), 45
exception (Hashset), 57
exception (Intmap), 65
exception (Intset), 67
exception (Polygdbm), 118
exception (Rbset), 129
exception (Redblackmap), 135
exception (Splaymap), 150
exception (Splayset), 152
NotInt
exception (Msp), 92
noTransparent
value (Gdimage), 48, 50
NotWriter
exception (Gdbm), 45
exception (Polygdbm), 118
now
value (Time), 168
nRows
value (Array2), 6, 7
nth
value (List), 71
value (NJ93), 104
nthtail
value (NJ93), 104
ntuples
value (Mysql), 99, 101
value (Postgres), 122, 124
Null
exception (Mysql), 99
exception (Postgres), 122
null
value (List), 71
numItems
value (Binarymap), 17
value (Binaryset), 19, 20
value (Gdbm), 45, 46
value (Hashset), 57, 58
value (Intmap), 65
value (Intset), 67
value (Polygdbm), 118, 119
value (Polyhash), 120
value (Rbset), 129, 130
value (Redblackmap), 135
value (Splaymap), 150
value (Splayset), 152, 153
o
value (General), 52, 55
offset
value (Date), 35, 36
oid
constructor (Postgres), 124
type (Mysql), 99
type (Postgres), 122, 124
ol
value (Msp), 93, 97
ola
value (Msp), 93, 97
open_append
value (NJ93), 105
open_in
value (NJ93), 104
value (SML90), 142
open_in_bin
value (NJ93), 105
value (Nonstdio), 106
open_out
value (NJ93), 105
value (SML90), 142
open_out_bin
value (NJ93), 105
value (Nonstdio), 106
open_out_exe
value (Nonstdio), 106
openAppend
value (BinIO), 14, 15
value (TextIO), 164, 166
openbase
value (Mysql), 99, 100
value (Postgres), 122, 124
openDir
value (FileSys), 42
openIn
value (BinIO), 14
value (TextIO), 164, 165
openmode
type (Gdbm), 45
openOut
value (BinIO), 14, 15
value (TextIO), 164, 166
option

exception (General), 52
exception (Option), 108
Option (structure), 108
option
 type (General), 52, 53
 type (Option), 108
 value (Msp), 94, 98
options
 value (Mysql), 99, 101
 value (Postgres), 122, 124
orb
 value (Word), 181, 182
 value (Word8), 184, 185
ord
 value (Char), 27
 value (NJ93), 104
 value (SML90), 142
order
 type (General), 52, 53
ordof
 value (NJ93), 104
orthodox
 value (Meta), 81, 82
OS (structure), 107
OSAerr
 type (AppleScript), 2
OSAID
 type (AppleScript), 2
out_flags
 type (Socket), 145, 148
Out_of_memory
 exception (General), 52
output
 value (BinIO), 14, 15
 value (NJ93), 105
 value (SML90), 142
 value (TextIO), 164, 166
output1
 value (BinIO), 14, 15
 value (TextIO), 164, 166
output_binary_int
 value (Nonstdio), 106
output_byte
 value (Nonstdio), 106
output_char
 value (Nonstdio), 106
output_value
 value (Nonstdio), 106
outputc
 value (NJ93), 105
 value (TextIO), 164
 value (TextIO), 164
 value (TextIO), 164
 Overflow
 exception (General), 52
p
 value (Msp), 92, 96
pa
 value (Msp), 92, 96
packString
 value (Byte), 23
padLeft
 value (StringCvt), 157, 158
padRight
 value (StringCvt), 157, 158
ParamMissing
 exception (Msp), 92
parentArc
 value (Path), 114, 115
ParseError
 exception (Parsing), 112
parseTables
 type (Parsing), 112
Parsing (structure), 112–113
part
 type (Mosmlcgi), 87
part_data
 value (Mosmlcgi), 87, 88
part_field_integer
 value (Mosmlcgi), 87, 89
part_field_string
 value (Mosmlcgi), 87, 88
part_field_strings
 value (Mosmlcgi), 87, 88
part_fieldnames
 value (Mosmlcgi), 87, 88
part_type
 value (Mosmlcgi), 87
partition
 value (List), 71, 72
passive
 type (Socket), 145, 146
Path
 exception (Path), 114
Path (structure), 114–117

peek
 value (Binarymap), 17
 value (Binaryset), 19
 value (Gdbm), 45, 46
 value (Hashset), 57
 value (Intmap), 65
 value (Polygdbm), 118, 119
 value (Polyhash), 120
 value (Redblackmap), 135
 value (Splaymap), 150
 value (Splayset), 152
peekInsert
 value (Polyhash), 120
peekVal
 value (Parsing), 112
pf_file
 type (Socket), 145, 146
pf_inet
 type (Socket), 145, 146
pi
 value (Math), 79
pipe
 value (Signal), 143
Polygdbm (structure), 118–119
Polyhash (structure), 120–121
polyHash
 value (Hashset), 57, 58
port
 value (Mysql), 99, 101
 value (Postgres), 122, 124
pos_in
 value (Nonstdio), 106
pos_out
 value (Nonstdio), 106
position
 value (Substring), 159, 162
Postgres (structure), 122–126
pow
 value (IntInf), 64
 value (Math), 79
PP (structure), 109–111
pp_to_string
 value (PP), 109, 110
ppconsumer
 type (PP), 109
ppstream
 type (General), 52, 53
pre
 value (Msp), 93, 96

precision
 value (Int), 61
 value (IntInf), 64
pred
 value (Char), 27, 28
print
 value (NJ93), 104
 value (TextIO), 164, 166
printDepth
 value (Meta), 81
printLength
 value (Meta), 81
printseq
 value (Msp), 92, 94
printVal
 value (Meta), 81
prmap
 value (Msp), 92, 94
proc
 type (Unix), 171
Process (structure), 127
prsep
 value (Msp), 92, 94

quietdec
 value (Meta), 81, 84
quit
 value (Meta), 81
 value (Signal), 143
quot
 value (Int), 61, 62
 value (IntInf), 64
quotation
 value (Meta), 81, 84
quotRem
 value (IntInf), 64

radix
 type (StringCvt), 157
Random (structure), 128
random
 value (Random), 128
randomlist
 value (Random), 128
range
 value (Random), 128
rangelist
 value (Random), 128
Rbset (structure), 129–131

readDir
 value (FileSys), 42
reader
 type (StringCvt), 157
readLink
 value (FileSys), 42, 43
Real (structure), 132–134
real
 type (General), 52, 54
 type (Math), 79
 type (Real), 132
 value (General), 53, 55
real_timer
 type (Timer), 170
realfmt
 type (StringCvt), 157
realPath
 value (FileSys), 42, 43
reap
 value (Unix), 171, 172
recvArr
 value (Socket), 146, 148
recvArr'
 value (Socket), 146, 148
recvArrFrom
 value (Socket), 146, 149
recvArrFrom'
 value (Socket), 146, 149
recvVec
 value (Socket), 146, 148
recvVec'
 value (Socket), 146, 148
recvVecFrom
 value (Socket), 146, 149
recvVecFrom'
 value (Socket), 146, 149
Redblackmap (structure), 135–136
ref
 constructor (General), 54
 type (General), 52, 54
regcomp
 value (Regex), 137, 138
Regex
 exception (Regex), 137
Regex (structure), 137–141
regex
 type (Regex), 137
regexec
 value (Regex), 137, 139
 regexecBool
 value (Regex), 137, 139
 region
 type (Array2), 6, 8
 register
 value (Callback), 24, 25
 regmatch
 value (Regex), 137, 139
 regmatchBool
 value (Regex), 137, 139
 regnexec
 value (Regex), 137, 139
 regnexecBool
 value (Regex), 137, 139
rem
 value (Int), 61, 62
 value (IntInf), 64
remove
 value (Binarymap), 17
 value (FileSys), 42, 43
 value (Gdbm), 45, 46
 value (Intmap), 65
 value (Polygdbm), 118, 119
 value (Polyhash), 120
 value (Redblackmap), 135
 value (Splaymap), 150
rename
 value (FileSys), 42, 43
reorganize
 value (Gdbm), 45, 47
 value (Polygdbm), 118, 119
replace
 value (Regex), 137, 139
replacel
 value (Regex), 137, 139
replacer
 type (Regex), 137
reset
 value (Buffer), 22
 value (Mysql), 99, 101
 value (Postgres), 122, 124
resultstatus
 value (Mysql), 99, 101
 value (Postgres), 122, 124
retrieve
 value (Binaryset), 19
 value (Hashset), 57
 value (Intmap), 65
 value (Splayset), 152

rev
 value (List), 71, 72
revapp
 value (Binarymap), 17
 value (Binaryset), 19, 20
 value (Intmap), 65
 value (Intset), 67, 68
 value (NJ93), 104
 value (Rbset), 129, 130
 value (Redblackmap), 135
 value (Splaymap), 150
 value (Splayset), 152, 153
revAppend
 value (List), 71, 72
revfold
 value (NJ93), 104
rewindDir
 value (FileSys), 42
rgb
 type (Gdimage), 48, 49
 value (Gdimage), 48, 50
rmDir
 value (FileSys), 42, 43
round
 value (General), 53, 55
 value (Real), 132, 133
row
 value (Array2), 6, 7
RowMajor
 constructor (Array2), 6
RTLD_LAZY
 constructor (Dynlib), 40
RTLD_NOW
 constructor (Dynlib), 40
run
 value (Mosml), 85
runresult
 type (Mosml), 85
sameDesc
 value (Socket), 145, 149
sameSign
 value (Int), 61, 62
 value (IntInf), 64
 value (Real), 132, 133
scan
 value (Bool), 21
 value (Date), 35, 37
 value (Int), 61, 62
 value (IntInf), 64
 value (Real), 132, 133
set
 type (Binaryset), 19
 type (Hashset), 57
 type (Rbset), 129
 type (Splayset), 152
 value (Weak), 178
setCookie
 value (Mosmlcookie), 91
setCookies
 value (Mosmlcookie), 91
setTime
 value (FileSys), 42, 43
setTransparent

value (*Gdimage*), 48, 50
showquery
 value (*Mysql*), 100, 103
 value (*Postgres*), 123, 126
shutdown
 value (*Socket*), 145, 147
shutdown_mode
 type (*Socket*), 145
sign
 value (*Int*), 61, 62
 value (*IntInf*), 64
 value (*Real*), 132
Signal (*structure*), 143–144
signal
 type (*Signal*), 143
 type (*Unix*), 171
sin
 value (*Math*), 79
 value (*NJ93*), 104
 value (*SML90*), 142
singleton
 value (*Binaryset*), 19
 value (*Hashset*), 57
 value (*Intset*), 67
 value (*Rbset*), 129, 130
 value (*Splayset*), 152
sinh
 value (*Math*), 79, 80
Size
 exception (*General*), 52
size
 value (*Buffer*), 22
 value (*Gdimage*), 48, 49
 value (*String*), 154
 value (*Substring*), 159, 160
skipWS
 value (*StringCvt*), 157, 158
sleep
 value (*Process*), 127
slice
 type (*ArraySlice*), 10
 type (*CharArraySlice*), 31
 type (*CharVectorSlice*), 33
 type (*VectorSlice*), 175
 type (*Word8ArraySlice*), 188
 type (*Word8VectorSlice*), 190
 value (*ArraySlice*), 10
 value (*CharArraySlice*), 31
 value (*CharVectorSlice*), 33
 value (*Substring*), 159, 160
 value (*VectorSlice*), 175
 value (*Word8ArraySlice*), 188
 value (*Word8VectorSlice*), 190
SML90 (*structure*), 142
sock
 type (*Socket*), 145, 146
sock_addr
 type (*Socket*), 145, 146
sock_desc
 type (*Socket*), 145
sockDesc
 value (*Socket*), 145, 149
Socket (*structure*), 145–149
sort
 value (*Arraysort*), 13
 value (*Listsort*), 76
sorted
 value (*Arraysort*), 13
 value (*Listsort*), 76
Span
 exception (*General*), 52
 exception (*Substring*), 159
span
 value (*Substring*), 159, 162
specialfiles
 value (*Help*), 59
Splaymap (*structure*), 150–151
Splayset (*structure*), 152–153
splitAt
 value (*Substring*), 159, 162
splitBaseExt
 value (*Path*), 114, 117
splitDirFile
 value (*Path*), 114, 116
splitl
 value (*StringCvt*), 157
 value (*Substring*), 159, 161
splitr
 value (*Substring*), 159, 161
sqrt
 value (*Math*), 79
 value (*NJ93*), 104
 value (*SML90*), 142
startCPUTimer
 value (*Timer*), 170
startRealTimer
 value (*Timer*), 170
status

type (Process), 127
value (Mysql), 99, 101
value (Postgres), 122, 124
std_err
 value (NJ93), 105
std_in
 value (NJ93), 104
 value (SML90), 142
std_out
 value (NJ93), 105
 value (SML90), 142
stdErr
 value (TextIO), 164, 166
stdIn
 value (TextIO), 164, 165
stdOut
 value (TextIO), 164, 166
stdoutPng
 value (Gdimage), 48, 50
stop
 value (Signal), 143, 144
Str
 constructor (Regex), 140
str
 value (String), 154, 155
stream
 type (Socket), 145, 146
streamsOf
 value (Unix), 171
String (structure), 154–156
string
 type (General), 52, 54
 type (String), 154
 value (Gdimage), 49, 51
 value (Substring), 159, 160
StringCvt (structure), 157–158
stringToBytes
 value (Byte), 23
stringUp
 value (Gdimage), 49, 51
strong
 value (Msp), 93, 96
style
 type (Gdimage), 48, 49
sub
 value (Array), 3, 4
 value (Array2), 6, 7
 value (ArraySlice), 10
 value (CharArray), 30
value (CharArraySlice), 31
value (CharVector), 32
value (CharVectorSlice), 33
value (Dynarray), 38
value (Msp), 93, 96
value (String), 154
value (Substring), 159, 160
value (Vector), 173
value (VectorSlice), 175
value (Weak), 178, 179
value (Word8Array), 187
value (Word8ArraySlice), 188
value (Word8Vector), 189
value (Word8VectorSlice), 190
subArray
 value (Dynarray), 38
sublist
 value (Rbset), 129, 131
Subscript
 exception (General), 52
subset
 value (Rbset), 129, 131
subslice
 value (ArraySlice), 10, 11
 value (CharArraySlice), 31
 value (CharVectorSlice), 33
 value (VectorSlice), 175, 176
 value (Word8ArraySlice), 188
 value (Word8VectorSlice), 190
substitute
 value (Regex), 137, 140
substitute1
 value (Regex), 137, 140
Substring
 exception (NJ93), 104
Substring (structure), 159–162
substring
 type (General), 52, 54
 type (Substring), 159
 value (NJ93), 104
 value (String), 154
 value (Substring), 159, 160
succ
 value (Char), 27
success
 value (Process), 127
sup
 value (Msp), 93, 96
Sus

constructor (Regex), 140
Susp (structure), 163
susp
 type (Susp), 163
symbolEnd
 value (Parsing), 112, 113
symbolStart
 value (Parsing), 112
symHandle
 type (Dynlib), 39
SysErr
 exception (General), 52
 exception (OS), 107
syserror
 type (General), 52, 54
 type (OS), 107
system
 value (Process), 127
systemInfo
 value (Mosml), 86

table
 type (Gdbm), 45
 type (Polygdbm), 118
 value (Msp), 93, 97
tablea
 value (Msp), 93, 97
tabulate
 value (Array), 3
 value (Array2), 6, 7
 value (CharArray), 30
 value (CharVector), 32
 value (Dynarray), 38
 value (List), 71, 72
 value (Vector), 173
 value (Word8Array), 187
 value (Word8Vector), 189
take
 value (List), 71
take1
 value (StringCvt), 157
 value (Substring), 159, 161
taker
 value (Substring), 159, 161
tan
 value (Math), 79
tanh
 value (Math), 79, 80
td
 value (Msp), 93, 97
tda
 value (Msp), 93, 97
term
 value (Signal), 143
terminate
 value (Process), 127
textarea
 value (Msp), 94, 98
textareaa
 value (Msp), 94, 98
textInstreamOf
 value (Unix), 171, 172
TextIO (structure), 164–167
textOutstreamOf
 value (Unix), 171, 172
th
 value (Msp), 93, 97
tha
 value (Msp), 93, 97
Time
 exception (Time), 168
Time (structure), 168–169
time
 type (Time), 168
 value (Mosml), 85
Timer (structure), 170
title
 value (Msp), 92, 95
t1
 value (List), 71
 value (NJ93), 104
tmpName
 value (FileSys), 42, 44
toCString
 value (Char), 27, 29
 value (String), 154, 156
toDefault
 value (Real), 132, 133
toInt
 value (Int), 61
 value (IntInf), 64
 value (Word), 181, 183
 value (Word8), 184, 186
toIntX
 value (Word), 181, 183
 value (Word8), 184, 186
tokens
 value (Regex), 137, 140

value (String), 154, 155
value (Substring), 159, 162
toLarge
 value (Int), 61
 value (IntInf), 64
 value (Word), 181, 183
 value (Word8), 184, 186
toLargeInt
 value (Word), 181, 183
 value (Word8), 184, 186
toLargeIntX
 value (Word), 181, 183
 value (Word8), 184, 186
toLargeWord
 value (Word), 181, 183
 value (Word8), 184, 186
toLargeWordX
 value (Word), 181, 183
 value (Word8), 184, 186
toLargeX
 value (Word), 181, 183
 value (Word8), 184, 186
toLower
 value (Char), 27, 28
toMicroseconds
 value (Time), 168, 169
toMilliseconds
 value (Time), 168
toPng
 value (Gdimage), 48, 49
toReal
 value (Time), 168, 169
toSeconds
 value (Time), 168
toString
 value (Bool), 21
 value (Char), 27, 28
 value (Date), 35, 36
 value (Int), 61, 62
 value (IntInf), 64
 value (Path), 114, 116
 value (Real), 132, 133
 value (String), 154, 155
 value (Time), 168, 169
 value (Word), 181, 182
 value (Word8), 184, 185
totalCPUTimer
 value (Timer), 170
totalRealTimer
 value (Timer), 170
toTime
 value (Date), 35, 37
toUnixPath
 value (Path), 114, 117
toUpperCase
 value (Char), 27, 28
toWord
 value (Signal), 143
Tr
 constructor (Regex), 140
tr
 value (Msp), 93, 97
tra
 value (Msp), 93, 97
transform
 value (Binarymap), 17, 18
 value (Intmap), 65, 66
 value (Polyhash), 120, 121
 value (Redblackmap), 135, 136
 value (Splaymap), 150, 151
translate
 value (String), 154, 155
 value (Substring), 159, 162
traversal
 type (Array2), 6
triml
 value (Substring), 159, 160
trimr
 value (Substring), 159, 160
Trs
 constructor (Regex), 140
trunc
 value (General), 53, 56
 value (Real), 132, 133
truncate
 value (NJ93), 104
tstp
 value (Signal), 143
tt
 value (Msp), 93, 96
ttin
 value (Signal), 143, 144
ttou
 value (Signal), 143, 144
tty
 value (Mysql), 99, 101
 value (Postgres), 122, 124

ul
 value (Msp), 93, 96
ula
 value (Msp), 93, 97
UnequalLengths
 exception (ListPair), 74
union
 value (Binaryset), 19, 20
 value (Intset), 67
 value (Rbset), 129, 130
 value (Splayset), 152, 153
unit
 type (General), 52, 53
Unix (structure), 171–172
unpackString
 value (Byte), 23
unpackStringVec
 value (Byte), 23
unregister
 value (Callback), 24, 25
unzip
 value (ListPair), 74
update
 value (Array), 3, 4
 value (Array2), 6, 7
 value (ArraySlice), 10
 value (CharArray), 30
 value (CharArraySlice), 31
 value (CharVector), 32
 value (Dynarray), 38
 value (Vector), 173
 value (Weak), 178, 179
 value (Word8Array), 187
 value (Word8ArraySlice), 188
 value (Word8Vector), 189
urlencode
 value (Msp), 94, 98
use
 value (Meta), 81, 82
usr1
 value (Signal), 143, 144
usr2
 value (Signal), 143, 144

validVolume
 value (Path), 114, 115
valOf
 value (Option), 108
valuepoly

value (Meta), 81, 84
var
 value (Callback), 24, 26
 value (Dynlib), 39, 40
vec2list
 value (Msp), 92, 95
vecDouble
 value (Mosml), 85
vecFloat
 value (Mosml), 85
Vector (structure), 173–174
vector
 type (Array), 3
 type (BinIO), 14
 type (CharArray), 30
 type (CharArraySlice), 31
 type (CharVector), 32
 type (CharVectorSlice), 33
 type (General), 52, 54
 type (TextIO), 164, 165
 type (Vector), 173
 type (Word8Array), 187
 type (Word8ArraySlice), 188
 type (Word8Vector), 189
 type (Word8VectorSlice), 190
 value (Array), 3
 value (ArraySlice), 10, 11
 value (CharArray), 30
 value (CharArraySlice), 31
 value (CharVectorSlice), 33
 value (General), 53, 56
 value (VectorSlice), 175, 176
 value (Word8Array), 187
 value (Word8ArraySlice), 188
 value (Word8VectorSlice), 190
vector_slice
 type (CharArraySlice), 31
 type (Word8ArraySlice), 188
VectorSlice (structure), 175–177
verbose
 value (Meta), 81, 84

Weak (structure), 178–180
weak
 type (Weak), 178
 value (Weak), 178
weekDay
 value (Date), 35, 36
weekday

type (*Date*), 35
welcome
 value (*Help*), 59
with_pp
 value (*PP*), 109, 110
withhtable
 value (*Gdbm*), 45
 value (*Polygdbm*), 118
withtables
 value (*Gdbm*), 45
Word (*structure*), 181–183
word
 type (*General*), 52, 54
 type (*Word*), 181
 type (*Word8*), 184
Word8 (*structure*), 184–186
word8
 type (*General*), 52, 54
Word8Array (*structure*), 187
Word8ArraySlice (*structure*), 188
Word8Vector (*structure*), 189
Word8VectorSlice (*structure*), 190
wordSize
 value (*Word*), 181
 value (*Word8*), 184
wseq
 type (*Msp*), 92, 94

xL
 value (*Location*), 77, 78
xLR
 value (*Location*), 77, 78
xorb
 value (*Word*), 181, 182
 value (*Word8*), 184, 185
xR
 value (*Location*), 77, 78
xxLR
 value (*Location*), 77, 78
xxRL
 value (*Location*), 77, 78
xy
 type (*Gdimage*), 48, 49

year
 value (*Date*), 35, 36
yearDay
 value (*Date*), 35, 36
yyexit